Vol. 30, No. 5

MAY, 1935

\$1 a Year, 20 Cents a Copy

PICKS and SHOVELS

By O. E. POTTER

What? No "Hooch"?

Some of the joys and griefs of the contractor for the widening of the Livingstone Channel in the Detroit River between the Canadian and Detroit shores were described by W. J. Mortherry in a recent issue of the du Pont Margaine. The most disconniction Magazine. The most disappointing experience, to the workmen at least, came when one of the long cofferdams was unwatered to permit dry excavation.

Back in the days before Repeal, this

ection was said to have been on the oute of rum-runners who smuggled quor from Canada, making from one six round trips every 24 hours. So was believed that when this section as dried up, plenty of whiskey, wine ad beer of the F. O. B. variety (flung verboard), dumped by the rum-runners hen the Law was too hot on their trail,

However, when the river bottom within the cofferdam was exposed, the eager expectations of the workmen were shattered. We are told that only a few shattered. We are told that only a few bottles of liquor and some cases of beer were recovered. What a blow!

The Moral Is

There was a dirt moving contractor To whom cost was never a factor. He bid just below Where he thought it would go

So now he's greasing a tractor.

Penny Ante and Morale

"You boys have got to quit playing enny ante around this job. You are nt out here by the Welfare Department out here by the Welfare Department because you are up against it and need work. I'm not going to let you gamble away what you are earning," exploded a well-meaning Superintendent on a PWA job. For a week or so after the ban on penny ante, the men were out-of-sorts during the noon layoff and at other times when there were (Continued on page 23)

In This Issue

Dituminous Koads	
Bonneville Dam	2, 6
Bridges	1
Bulletins and Pamphlets	38, 39
Business Outlook	6
Cartoon	4
Concrete Roads	8
Dams	2
Dredging	
Editorials	4
Future Highway Work	1
Legal Decisions	12
Lubrication	16
Road Maintenance	21, 23, 32
Road Widening	2, 8
Safety in Construction	
Skyline Drive	37
Stabilised Roads	2
Tunnels	11

Apalachicola Bay Bridge



Clamming Out One of the Caissons at Pier 4 Before Pouring the Tremie Seal

Highway Program for 1935-36 Assured

Hayden - Cartwright Amendment Preserves Contract System and Assures Continuance of Federal Aid for Roads

WITH the passage of the Emergency Relief Bill, carrying the Hayden-Cartwright Amendment, the largest Fedcartwright Amendment, the largest red-eral appropriation for highways in his-tory has been authorized. Federal and state appropriations for highways for 1935 and 1936 will total \$1,355,000,000, according to a statement from the American Road Builders' Association.

The earmarked national funds for highways, streets and grade-crossing elimination, together with the funds already authorized under the Hayden-Cartwright Act of last year, amount to \$1,005,000,000. If the states match the Federal Aid already authorized it will Federal Aid already authorized, it will add \$250,000,000 more to the highway program, or a grand total of \$1,255,000,000. Also there will be available the state money used for highways outside of that used for matching Federal Aid, estimated at \$100,000,000.

Provisions of Act

Provisions of Act
This new highway legislation continues the apportionment of the highway funds to the states in accordance with the Hayden-Cartwright Act. The apportionments for grade-crossing elimination funds are in proportion to the mileage of highways, mileage of railroads and population. It provides for the expenditures of these funds by state highway departments under the Federal Highway Act of November 9, 1921, as amended, and the Hayden-Cartwright Act of June 18, 1934. No part of the Act of June 18, 1934. No part of the hads need be matched by the states. It also provides that the funds shall

be spent under rules and regulations prescribed by the President, which undoubtedly will be similar to the rules and regulations under the Hayden-Cartwright Act.

Preference in employment of labor shall be given to persons receiving relief, except those in executive, administrative, supervisory and highly skilled positions. The President is authorized (Continued on page 33)

5-Mile Bridge and Causeway New Florida Road Link

THE new 5-mile combined bridge and causeway being built by the State Road Department of Florida as PWA Project 843, across Apalachicola Bay, is a much-needed link in the chain of is a much-needed link in the chain of surfaced roads built in this section by the State during the last six years. It will also be an important link in the Gulf Highway extending from Galveston, Texas, through Louisiana, Mississippi, Alabama, and on to Pensacola, Fla., thence through Fort Walton, Fla., Panama City, Analgebicola, Tallahase. Panama City, Apalachicola, Tallahas-see and down the west coast of Florida.

see and down the west coast of Florida.

For many years a private company provided inadequate ferry service across the Bay. Within the last two years the State has operated a free ferry over the same route but still with long waits for through traffic. The bridge will eliminate all this and provide a sea-going causeway longer than that connecting Galveston Island with the mainland. The city of Apalachicola will benefit greatly by the improved traffic link as, with the beautiful drive on either side of that city, traffic is bound to be increased. The next important city to the west is 65 miles away and to the east, 74 miles.

Five Contracts for Project

The work is divided into five separate contracts, three of which will furnish the subjects of the four articles in this series: the concrete piers for the main river span; the causeway formed by hydraulic dredging; the bridge see by hydraulic dredging; the bridge sections on composite pile bents; and the floating concrete mixing plant and the casting yard for the 20 miles of concrete hand-rail. From the Apalachicola or Hardaway Contrg. Co. **Built Concrete Piers for** River Crossing with Floating Plant

western end of the bridge the work is

MITIMOU NO TOMONO.	
Embankment Approach	
Main River Crossing and Swing Span	2,589.81 feet
Causeway Embankment	5,999.56 feet
file Trestle with Concrete Deck	3,000.44 feet
Causeway Embankment	2,999.56 feet
Pile Treatle with Concrete Deck	9.394.71 feet
Embankment to Shore	2,005.51 feet
Grading of East Bay Approach	7,800.00 feet
Total Length of Contracts	34,284.10 feet

The contractors for the various sections of the work and their bids were as follows: Duval Engineering & Contracting Co., hydraulic embankment and bulkhead protection, \$222,550.61; Hardaway Contracting Co., all concrete piers for the main river crossing, \$137,-336.20; Doullut & Ewin, all trestle pile driving, concrete deck and hand-rails, \$681,748.19; Nashville Bridge Co., steel superstructure for the swing span of the main river bridge, \$73,979.10; Penton-Mathis Construction Co., grading the approach at the east end of the bridge, \$14,224.34. The total cost of above PWA contracts, exclusive of engineering, is \$1,129,838.44.

Construction of Concrete Piers

The concrete piers consist of two legs tied by concrete beams at about midheight and at the top but with separate foundations and footings. In this contract there were nine piers and a swing span of 285 feet with a 1,500-foot pile trestle approach.

The pier footings measure 11 feet x 13 feet 6 inches neat for each leg and (Continued on page 15)

WIDENING A HEAVILY-TRAVELED TEXAS HIGHWAY



& E. M. Photo

Truck-Mixed Concrete Hauled 5 Miles for Beaumont Project. See page 8

Aggregate Production and Concrete Handling on Bonneville Project

(Photo on page 44)

BONNEVILLE PWA Project, on the Columbia River near Portland, Ore., aside from railroad and highway relocations, is being handled in two main contracts. One includes the power house substructure and navigation locks between Bradford Island and the Oregon shore; the other is the spillway dam between the Island and the Washington shore. The latter has progressed to the point where the cofferdams are being unwatered and excavation started.

The power house substructure and locks are now well ahead of schedule. The present article deals with that part of the undertaking, outlining the meth-ods used in the production and storage ods used in the production and storage of concrete aggregates and cement, together with the mixing and placing of the concrete. The plant and equipment were designed for this phase of the work.

A birdseye view of the situation is this: sand and gravel are dredged from the Willamette River at the outskirts of Portland by two dredges and fine sand


Portland by two dredges and fine sand is secured by a third dredge from the mouth of a slough near the Columbia River. The materials are barged to the production plant built for the purpose on the Willamette in the city of Porton the williamette in the city of Port-land, where the oversize is crushed and all aggregates washed and classified. They are then shipped by railroad ap-proximately 40 miles to the site, in 60-

Concrete aggregates go into open storage on Bradford Island. The cement, also coming in by train, goes into a steel silo. Cement, sand and gravel meet at the batching plant located on the brow of the cliff overlooking the the brow of the cliff overlooking the power house excavation. The mixed concrete is transported by locomotive and dump car to a loading dock immediately under the cableway, and thence by bucket to the forms.

Portland Production Plant

This plant was built by the General Construction Co. The materials are unloaded from the barges by a Williams 5-yard clamshell bucket, on a 120-foot boom, delivering to a bin over the grizzly in the case of the Willamette materials, and a separate bin for the Columbia River sand.

Four and one-half inch oversize from Four and one-half inch oversize from the grizzly is passed through a Wheeling 10 x 36-inch jaw crusher. The crushed materials are returned to the barge and again pass to the grizzly. Fines pass by way of a Stephens-Adamson apron feeder to a Link-Belt bucket elevator, 12 x 24 inches, and then to a



Telsmith revolving screen, 5 x 14 feet. This takes out 3-inch and 1½-inch sizes which go to bins.

Oversize from the revolving screen passes a 3-foot Symons cone crusher and thence, by a 10 x 20-inch Link-Belt bucket elevator to a 3 x 8-foot Allis-Chalmers 3-deck vibrating screen. This delivers 34-inch, 1½-inch and 3-inch materials to their respective bins.

The three grades of materials are then passed through Telsmith radial gates to a 30-inch belt conveyor built by the H. W. Sharp Co. of Portland. The fine Columbia River sand from its bin also passes through the radial gates to this conveyor. From it the materials are fed to a Stepheng-Adamson swing. are fed to a Stephens-Adamson swing belt conveyor delivering to cars along side. Dodge-Timken bearings and Re-public Rubber Co. belt are used in all

Handling the Fines

Going back to the Telsmith revolving Going back to the Telsmith revolving screen, the fines from it first come to two 3 x 8-foot Stephens-Adamson double-deck vibrating screens. The output of these screens is minus %-inch to ¼-inch, fines, and plus %-inch to ¾-inch. The latter goes over to the ¾-inch bin in the first line, while the first is delivered direct to cars or to storage as desired, leaving the fines, which go to a Perkins revolving classifier. Mud and silt from the classifier go to

waste while the materials of ½-inch mesh go to a bin and thence by a Telsmith radial gate to a 30-inch H. W. Sharp belt conveyor, to a Stephens-Adamson swing belt conveyor, and to This part of the installation is a

duplicate of the part described above. Wash water is secured by a Byron-Jackson deep-well pump driven by a General Electric turbine type motor. This water is introduced just before the

Telsmith revolving screen and also at the double-deck vibrating screens.

The normal capacity of this plant is one 60-car train per 24 hours.

Power Equipment, Porland Production Plant Apparatus
Biectric Moters

Williams Bucket 156 hp holat

156 hp integ Apparatus
Williams Bucket
Jaw crusher
Apron feeder
Bucket elvartor (1224)
Bevolving acreen
Cone crusher
Bucket olvartor (1020)
Bucket olv Turrope Gates V-belt Bockwood Baidwin chain Turrope



Belt Conveyors in the Portland Production Plant Loading Aggregate for Bonneville



Locomotive and Double Dump Car for Transporting Concrete to the Loading Platform

Aggregate Storage at Bonneville

The aggregates go onto a 16,000-cubic The aggregates go onto a 16,000-cubic yard open storage area on Bradford Island. In connection with it is a materials handling plant designed by H. W. Sharp of Portland, who, in conjunction with the Balzer Machinery Co. of that city, furnished all the equipment for the batching plant. The capacity is 250 cubic yards of materials per hour. Sand and gravel are lifted 80 feet, by a bucket elevator, from a one-car capa-

a bucket elevator, from a one-car capa-city track hopper to a 30-inch inclined cross conveyor 75 feet long, delivering to another 30-inch conveyor 451 feet long over a storage tunnel. Discharge to pile is by means of a 30-inch Dodge tripper. (Continued on page 10)

Stabilized Roads a Real Job

Care and Thought Needed for Proper Building of This Type of Low-Cost Road

By H. G. SOURS, County Engineer, Summit County, Akron, Ohio

THERE are probably as many varied types of low-cost construction as there are of the high types and the there are of the high types and the proper exercise of engineering ingenuity and judgment in selecting the right type, considering requirements and costs, is just as important in this field, as it is in the field of high types. The stabilized traffic-bound type of secondary road is not suitable to cover the entire field of secondary improvements any more than any one type of hard surface more than any one type of hard surface is suitable under all conditions, but there is a field in which it fits.

Definitions

The stabilized road is simply defined as one made up of a graded combina-tion of fine and coarse aggregates proportioned so as to permit the minimum amount of displacement of the component particles after once in place, cemented together with the proper amount of clay which acts as a binding agent. The resistance of the coarse and ine particles to sliding over each other is known as internal friction; sharp, angular and to some extent flat materials have a higher factor of internal friction than round and will make a more stable

(Continued on page 17)

Pumping Highway Fill for Widening Job

(Photos on page 44)

TRAFFIC has increased so rapidly on U.S. 90, the nation's thoroughfare from New Orleans east to Florida since the new free bridges were opened by the State of Louisiana a few ago that the existing 20-foot roadway proved inadequate and work is now un-derway to widen it to 41 feet. The derway to widen it to 41 feet. The original embankment was thrown up original embankment was thrown up by clamshell and dipper dredges from borrow pits on either side of the center line. On May 5, 1934, Wilbanks & Pierce, Inc., of New Orleans was award-ed the contract for delivering about 2,-200,000 cubic yards of dredged fill to these old borrow pits to widen the exist. these old borrow pits to widen the exist-ing fill, after the material had dried out, by pulling it in and up with drag-

Two small dredges, the Illinois and the Grizzly, were first used on this work. As soon as the new dredge Man-atee was completed she was put onto the work and on June 15, 1934 started delivering from 10,000 to 12,000 cubic yards of material, dry measurement, to the pits each 24 hours through a pipe line varying from 800 to 3,500 feet long. The contract required that the dredge work only from the Lake Catherine side and that promote in the contract required that the dredge work only from the Lake Catherine side and that promote in the contract required that the dredge work only from the Lake Catherine side and that promote in the contract required that the contract req dredge work only from the Lake Catherine side and that no material be dredged closer than 250 feet to the shore. When the dredge worked in the marsh it was required to work at least 700 feet from the center line of the highway. The material varied from mostly fine sand to stiff pipe clay, but the two smaller dredges worked in large areas of mucky clay. The material in all cases dried out readily in a few days and by the time the fills were completed, handled perfectly by dragline. pleted, handled perfectly by dragline.

The Pipe Line

The discharge pipe of the dredge was

The Dredge Manatee Handled 12,000 Yards of Earth Every 24 Hours on Louisiana Project

18 inches in diameter and the minimum length was 700 feet plus the pontoon line of from 100 to 1,000 feet. The longest length of line used was about 3,500 feet with no appreciable diminution in the output of the dredge which was not pushed to its limit on this contract. The individual pipe lengths varied from 12 to 16 feet. The pressure in the pipe line varied from 35 to 85 pounds.

Inasmuch as all the dredging had to be done on one side of the road and the be done on one side of the road and the borrow pits on both sides had to be filled, the pipe line had to be carried across the roadway. Continuous pumping and continuous heavy traffic created a problem that required careful study to prevent interruption of the work. The Superintendent designed a bridge to carry traffic over the pipe line where it crossed the roadway and flattened one of the pipe sections to about 14 inches so that it would require less rise in the so that it would require less rise in the bridge. When pressure was put on the pipe and there was no heavy truck on the bridge the pipe resumed its circular cross section and lifted the bridge. This was overcome by raising the center of the bridge to permit the pipe to have its proper clearance.

The bridge was well-built and sufficiently strong to carry the heavy truck

ficiently strong to carry the heavy truck and bus traffic which uses this thoroughfare. The three approach sections on either side were duplicates and the center section was horizontal. The two end sections which took the first blow of approaching traffic measured 5 feet (Continued on page 31)

Thousands OF MILES

ads

d for Type

ineer,

varied ion and nd the genuity

et type, osts, is as it is stabil-ondary

entire ts any

defined mbinas procompoplace, proper inding se and

other sharp, iterials riction stable

11

 \mathbf{dc}

itee ls of s on

nimum

ontoon The

about

iminuwhich is con-

varied ure in to 85

had to

nd the

to be carried pump-reated study k. The

lge to here it ed one inches in the

truck ed its

aising e. d suf-

truck

rough-ons on ne cen-

e two 5 feet

t

any surface is, but



INSTEAD OF Hundreds

U. S. No. 37 near Frankfort, Ky., showing portion of twelve-mile section which has a serviceable, skidproof, low-cost Texaco surface


Traffic counts prove that hundreds of miles of expensive, heavy-duty paving have been constructed, where lighter types would have been entirely adequate.

Thousands of miles of low-cost, traffic-resisting asphalt surfacing could have been built for the price of the small mileage of hard-surfacing obtained.

Before designing a new road, study carefully existing and anticipated traffic. It is very likely that one or more inches of low cost road-mix or pre-mix TEXACO Asphalt surfacing will furnish an ideal solution. This sound policy brings good roads to far more taxpayers and reduces automobile operating cost on a substantially greater mileage of highways.

CHICAGO CLEVELAND KANSAS CITY HOUSTON DALLAS BUFFALO

THE TEXAS COMPANY Asphalt Sales Dept. 135 East 42nd Street





NEW YORK PHILADELPHIA RICHMOND BOSTON JACKSONVILLE

Contractors and **Engineers Monthly**

THE NATIONAL BUSINESS MAGAZINE OF THE CONSTRUCTION INDUSTRY

Issued Monthly by Buttenheim-Dix Publishing Corp. Publication Office; Mount Morris, Ill. Editorial Office; 470 Fourth Avenue, New York City

THEODORE REED KENDALL Editor
GEORGE CONOVER Vice President
HERBERT K. SAXE TOM DIX
EDGAR J. BUTTENHEIM General Manager
MYRON Med EOD Advertising Manager

> BRANCH OFFICES Chicaga, Ill., Daily Nows Blôg., Tem Dix, President Clevaland, Ohio, 643 Hanna Blôg., George Conover, Vice President San Francisco, Calif., 397 Mills Blôg., Duncan A. Scott

Point Number 1-Highway Construction

At last Franklin Delano Roosevelt has spoken, the only man who can speak with any authority in the semi-dictatorship we are enjoying in this free country, and now we know in some measure how the money from the \$4,800,000,000 work relief fund is to be expended. We congratulate the President that he has chosen as Number One of his Eight-Point Program, "Highway construction, grade crossing elimination." These are the two fields in which there are established agencies ready with the plans for At last Franklin Delano Roosevelt has lished agencies ready with the plans for the rapid placing of these funds in active service and in such a manner that the communities in which the projects are located will receive benefits both immediate, in the employment of the citizens in need of work, and in the future in the value of improved highways and grade crossing eliminations to make safer the traveled way of the motorist

and the passenger on the railroad train.

The well-organized state highway departments have been ready with plans for their highway systems for many years. These plans have been completed for exercise years and the furnishing of years. These plans have been completed for several years and the furnishing of further funds from the Federal treasury for their translation into reality will benefit every state in the country through the money which will be expended for the materials of construction, wages which go into all fields of trade and the creation of capital assets in the expectation. in the structures themselves.

Of interest also to other branches of construction industry are other 'points" of the President's program. The construction of the electric transmission lines necessary to the carrying out of the rural electrification program, the construction of low-cost housing in the rural and urban areas, soil erosion and reforestation, all will require the services of the contractors of the nation in their successful and economical completion. We hope that the President will realize the folly of using these funds entirely for the creation of a political machine, but will see to their fair and honest distribution through the normal channels of industry to recreate private endeavor which has been in the invalid state for so many years.

Recovery Acts Adopted by Seven More States

Now that it has become increasingly Now that it has become increasingly evident that the National Industrial Recovery Act will be extended, with strengthening additions, for a period of at least two years, the importance of urging the enactment of State Industrial Recovery Acts comes to the forefront, according to a release from the Construction Code Authority.

Seven states have adopted uniform State Industrial Recovery Acts and similar measures have been introduced into the legislatures of twenty-three others, according to information received from the NRA State Relations Officer. These states are Idaho, New

The President did not include any statement that funds would be used for airport work, but Secretary of Commerce Roper has made a plea for some slice of the four billion odd million dollars for that purpose. He has not stated at this writing just how the money will be expended but if it will be to improve in a permanent manner the airports of the smaller communities and prove in a permanent manner the air-ports of the smaller communities and make them of greater service as emerg-ency landing fields for large planes and if the work will be done by well-ad-ministered forces of local unemployed labor using unemployed engineers to direct the work, there is hope for great improvements to this new transportation industry. We feel that large airport grading projects should be awarded by contract to continue the policy we have urged before that the organizations of contractors throughout the nation be continued as units of labor for large construction projects.

Keeping Wild Steers off the Pavement

We have heard contractors in various parts of the country tell about what they would like to do to some of the "wild Indians" who would break through any kind of a barrier and drive onto con-crete less than 12 hours old. On this trip through the southwest, we even saw a grocery truck make a wild dash onto some concrete about an hour old in order to save a run around a city block. It remained for Red Williams, Super-

intendent for Russ Mitchell on a job in Brazoria County, Texas, to face the real problem of keeping a herd of over 1,000 wild steers off his new slab. He was warned that this herd, which included some Brahma steers, would come by his job on a certain day. Knowing full well that all the laborers, Rangers, and troops that could be mustered would clear out when those wild beasts turned on them, Williams set up a four-wire barbed wire fence along the new turned on them, Williams set up a four-wire barbed wire fence along the new slab for a distance of about 1,200 feet where there was the best chance of trouble. The fence posts were old rail-road ties set solidly into the grade at the edge of the slab. And the scheme worked!

Mexico, Wyoming, Oregon, Washington, Indiana and West Virginia.

As applying particularly to the Con-struction Code, information has been re-ceived from the Indiana Code Compliance Bureau, a coordinated Construction Code administrative agency which operates a joint bid depository in Indianapolis, that previous to the enactment of the Indiana Industrial Recovery Act, which was signed March 9, it was difficult to interest the smaller contractors in filing duplicate bids but that since its enactment, compliance has improved immeasurably.

The states which have enacted State Recovery Acts are, in addition to those noted above: California, Colorado, Illi-nois, New York, Wisconsin, Ohio, South Carolina, Utah, and Virginia.

Engineer Presents Both Sides of Question

To the Editor Contractors and Engineers Monthly

We are inclined to agree that there is We are inclined to agree that there is ground for some complaint regarding certain practices in charging contractors for plans and for bidding documents. At the same time, there is another side to the question.

In some cases, bidding is by invitation and not many sets of plans are needed.

However, where bidding is open, as in public work, it may well be that the cost of duplicating contract documents is quite an item in the fee of any engi-The difficulty arises not so much from the general contractor as from the multiplicity of hopeful subcontrac-tors and material and equipment deal-ers, all of whom have a proper interest in the undertaking.

Reasonable competition is

tageous to the client and he should bear the cost, but unless this cost can be determined in advance, and is included in the fee, it is difficult—particularly on public work-for the engineer to make

any recovery.

In our own practice we have finally adopted the procedure of requiring a deposit for all plans and specifications, the amount of the deposit being roughly proportional to the cost of reproduc-In the event a legal proposal is submitted, the full amount of the desubmitted, the full amount of the de-posit is refunded when the plans are returned. If no proposal is submitted, half of the deposit is refunded when the plans are returned. In addition to giving out plans in this manner, we also place them on file in our office and with contractors' associations under conditions that permit of examination and

This method is not entirely satisfactory, but it does not penalize a bona fide bidder and it divides the burden with equipment dealers and others who wish to take off quantities in their own offices.

Your correspondent describes a situ-ation that is undoubtedly vexing to the contractor who bids widely. Insofar as the practice runs counter to the advan-tage of the client, it should be possible to institute remedies, largely by educa-tion of the client. It would, we believe, help if contractor and engineer associations could themselves agree as to what constitutes fair practice.

George B. Gascoigne CONSULTING ENGINEER

Cleveland, Ohio March 26, 1935


Charge for Plans Justified, Says Chicago Engineer

To the Editor
Contractors and Engineers Monthly
In regard to the matter of a charge frequently made for plans by consulting engineers, I am of the opinion that those persons making the charge of "racketeering" have spoken without having knowledge of the matter.

When work is advertised, these days, there is such a demand for plans as to constitute a real burden on an office un-less some charge is made. Not only do general contractors want plans, but every possible sub, many civil engineerpartments of colleges, all material supply houses, and so on. Frequently as many as twenty or twenty-five sets of plans are requested, and it is rarely that even the postage is forwarded. When the plans are returned, they are fre-quently mutilated, dirty and unusable, and if the deposit is denied there is always trouble. Since these costs usually are borne by the consultant, and the specifications are usually typed, it may be seen that the problem is not as simple as it might appear. ple as it might appear.

The practice in this office is as fol-

lows: our arrangement with our client is to furnish a definite number of sets



Courtesy Midwest Golfe

"Can I give you a lift, lady?"

Moving and Re-Erecting The Vatican Obelisk

Early in the first century A.D., Emperor Caius Caligula brought from Heliopolis to Rome the shaft now known as the Vatican Obelisk, which today stands in the center of the plaza in from of St. Peter's. How this 325-ton shaft of granite, 88 feet long, was conveyed to Rome and set up in the Circus of Nero does not appear to be recorded. In 1585 it was found in a dirty and un-frequented part of the city, tipped 17 inches from the vertical and with in pedestal buried in rubbish and mud.

It fell to a 42-year old engineer, It fell to a 42-year old engineer, Dominicus Fontana, to be awarded a prize for the best plans for moving it by lowering the shaft to a horizontal position and moving it the required 825 feet on rollers and re-erecting it with pulleys, ropes and capstans. He calculated the weight of the shaft, sheathing and metal attachments to be 350 tom and decided upon forty capstans and and decided upon forty capstans and tackles operated by 800 men and 75 horses to lift the obelisk. This was sup-plemented by five 40-foot levers and wood and iron wedges driven between the bottom of the shaft and its base, for the initial lifting. The work started April 28, 1586. The gigantic task was finally completed about the middle of September at a complete cost of \$44,000.

The development of our highways to date is the outstanding advance in America's social and economic progress in the twentieth century. These roads in the twentieth century. These roads have remade the habits of our people and revolutionized our business. have integrated this country as nothing else could have done. They brought communities and people out of isolacommunities and people out of isola-tion. At the moment, no less than 45, 000 communities in the United States are without any facilities of transport other than the people's highways.

-Roy F. Brisson, Director, National Highway User Conference.

Few, if any of the accidents reported during 1934 to the Construction Sec-tion of the National Safety Council, did not present means of remedying conditions, if subjected to analysis. Let's make 1935 a record year for safety in construction!

of plans and specifications (usually four) to him at his office. Plans are also on file in our office and space is provided, so that any one wishing to do o may examine and work over the same. The successful bidder of course same. The successful bidder of course gets as many plans as he needs. All others are charged the cost of the same. We consider this fair. We might note in passing that under the code the cost of reproductions have been nearly doubled in the past two years.

Paul E. Green

MARR, GREEN & OPPER ENGINEERS

Chicago, Ill. April 3, 1935

light ned 1 ork w this type ates. V and he orthwe several

includin

tract fo

for 6.9' 5-foot

The

lanta,

1934.

Sa

plant u and ac by a (30,000 hired The Caterpi Caterpi fine gr not an entirely ing sta to the

limina

backfil

the ma

Whe

difficul sprink gallon off box strikean ang entirel was pu

ahead man. worke shape was li ylene was p

Wh that t four s feet w 24 in inches

stakes

The

Sand-Asphalt Paving on 6.97-Mile Project

(Photos on page 44)

3. S.

cting

D., Emfrom

known in front

on shaft

rcus of rded. In

and unoped 17 with its

nud. ngineer,

arded a oving it rizontal red 825

it with e calcu-leathing 50 tons ans and

and 75

vas supers and between

started ask was ddle of 44,000.

ways to

nce in

rogress e roads

people s. They nothing brought

f isolaan 45, States

ansport ys. way Usen

eported on Seccil, did

condi

fety in

usually ans are

pace is

g to do ver the course

s. All e same. ht note he cost

nearly

OPPER

k

A interesting example of the far-reaching effect of the rulings of the U. S. Bureau of Public Roads came light on a sand-asphalt paving project near Mobile, Ala. Formerly the state specifications ruled out any but pugmill mixers for the sand asphalt. Special provisions for this project permitted the use of a rotary mixer as the project and the Rule of the Rule work was a NRH project and the Bu-reau of Public Roads had permitted his type of mixer on other work in other states. When the bids were opened, it was ound that a contractor who uses such a mixer of his own manufacture was low and he was awarded the contract.

The job was on Alabama Route 42 northwest of Mobile and is a link in northwest of Mobile and is a nms in several paving projects of recent date, including concrete paving. The contract for the sand-asphalt paving was for 6.97 miles of 20-foot roadway with shoulders on either side. The 5-foot shoulders on either side. The paving was entirely over an old right-of-way except where curves were eased.

Grading

Grading
The contractor, Sam E. Finley of Atlanta, Ga., started grading January 10, 1934, but did not set up his asphalt plant until the latter part of February and actual paving did not start until April 19, 1934. Grading was handled with an Austin elevating grader pulled by a Caterpillar Sixty, loading about 30,000 cubic yards of earth to four hired trucks hauling within the free haul distance of 1,000 feet.

The fine grade was struck with a Caterpillar Thirty-Five diesel pulling a Caterpillar 12-foot blade grader. The fine grade and form crew consisted of

fine grade and form crew consisted of two men digging the trench, which was not an arduous task as the grade was entirely through sand, four men driving stakes, two men setting the 3 x 6inch forms, two men nailing the forms to the stakes and lining them up, two men driving stakes to grade and preliminary lining of forms, two graders who hand-finished the trench, two men backfilling the form trench and tamping the material, two men back lining up

the material, two men back lining up the forms, a water boy and a foreman. Where the grade was dry and hence difficult to work, as it was all sand, a sprinkling truck consisting of a 500-gallon tank mounted on a Chevrolet truck was used just ahead of the strike-off board used by the grade crew. This strike-off consisted of a 4 x 12-inch board cut to the crown of the road with an angle iron on the bettom and with an angle iron on the bottom and with bolts every 6 inches to adjust the iron to the crown or to take out the crown entirely on superelevated curves. This was pulled by the 8-ton Buffalo-Springfield tandem roller which was kept ahead to roll the grade. The grade crew on this work consisted of the foreman, and six men. A similar crew worked at night to get the grade in shape ahead. At that time the work was lighted by a pair of Oxweld-Acetylene carbic lights, and the strike-off was pulled by a tractor.

Form-Setting

While the specifications required that the 3 x 6-inch forms be dressed only on the top and one side the contractor used material dressed on all four sides, and in lengths of 10 to 15 feet. The forms were staked every 2 feet with special stakes every 2 x 42. feet with special stakes cut from 2 x 4's, 24 inches long and tapered for 21 inches. The forms were nailed to the stakes with one nail driven inward and one outward. There was a stake on either side of each joint also nailed.

Plant Operation

The mixing plant, including the

Portable Hot-Mix Plant of Contractor's Design Handled 300 Tons Daily on Alabama Contract

drier, was delivered to the site by three specially-built motor trucks which haul it from one job to another and was set up in a sand pit near the center of the up in a sand pit near the center of the contract. Unfortunately there was an excess of fines in the pit so that coarser sand had to be hauled in from another sand had to be hauled in from another pit about ½ mile away, by two 1½-yard Ford trucks. The material was clammed out to a stockpile by a Link-Belt crane with a 50-foot boom and a 3/4-yard Williams bucket. By selecting




Pulling the Strike-Off Just Ahead of Spreading the Sand Asphalt

from one pile or the other the crane operator supplied the proper mixture of material to the feeding gate where three men pushed the sand toward the bucket elevator to the rotary drier. There was another man at the top of

the bucket elevator to watch the de-

livery to the drier.

The rotary drier was 35 feet long and 5 feet in diameter and was heated by two fuel oil torches at the discharge (Continued on page 26)



NORTHWEST ENGINEERING CO, 1727 Steger Bldg., 28 E. Jackson Blvd., Chicago, III.

SHOVELS, CRANES, DRAGLINES, PULLSHOVELS,

GASOLINE, OIL, DIESEL OR ELECTRIC

Big Dragline Ferried on Scows

The Columbia Construction Co., contractor for the main spillway dam of tractor for the main spillway dam of the Bonneville project, had been using a Bucyrus-Monighan 75-B walking drag-line on the Washington side of the Co-lumbia River on channel diversion work. When this was completed in Feb-ruary of this year, it was desired to move the dragline across the channel to the south cofferdam on Bradford Island. About a quarter of a mile of very swift current intervened. The 443-ton equipment was brought over safely on a ferry consisting of two

over safely on a ferry consisting of two 38-foot x 120-foot barges fastened side

by side. Shore docks were built on both sides of the river, with adjacent bulkhead docks alongside to secure the necessary depth of water at the shore line. In the meantime, eight 36-inch steel I-beams had been mounted on the barges beams had been mounted on the barges crosswise of the two and parallel with each other. Two beams on each side were placed adjoining and the others spaced between, supported in upright position by timbering.

The ends of the I-beams were made to project about 6 feet over the side of one of the barges. When the barges were manipulated into the bulkhead on the Washington side to load, the ends

Washington side to load, the ends of the I-beams projected out over the shore dock. Water was then pumped into the barges and they were sunk until the ends of the beams rested on the shore dock. The dragline was then walked onto the barges over the I-beams, which were also its support on the barges during the trip. Water was then pumped out until the I-beams floated clear of the dock.

Lines from the cofferdam across the river held the barges as they were swung.

river held the barges as they were swung out into the stream, controlled by two out into the stream, controlled by two tugs. Thus the unique ferry was floated downstream and around until it came into slack water behind the cofferdam. Then it was towed up into the bulkhead at the unloading dock, swung into position so that the projecting beams were over the shore dock, the barges again sunk until the hearms rested on the dock.

sunk until the beams rested on the dock, and the dragline was walked off.

It took about 10 days to do the whole job, including building of the docks and bulkheads. But the actual crossing was safely accomplished in about an hour and a half.

Asphalt Industry Outlook Better Than Ever, Says Boye

The opportunities for expansion of the asphalt industry are greater now than ever before, said B. L. Boye, re-cently reelected President of The Asphalt Institute, citing use of asphalt in protecting Mississippi River banks, the greater use of asphalt in PWA high-ways, and the increasing speed of cars,

USE RIGHT BUCKET FOR THE JOB



Hayward makes all four — clam shell, drag-line, electric motor, orange peel. A Hayward recommendation is unprejudiced.



HAYWARD BUCKETS



Barges Bearing the Heavy Dragline Being Swung Into Position. A Diesel Seventy-Five in the Foreground Assists in the Operations.

rendering flexible roads a necessity.

Pointing out that highways of the future must be non-rigid and resilient

mobile speeds, Mr. Boye explained that Sir Malcolm Campbell's speed tests are made at Daytona Beach because the packed sand is resilient.

"Today's best highways," said Mr. bye, "although smooth at today's Boye, "although smooth at today's speeds, would tear a car to pieces at the potentially greater speeds of the future. Roads of tomorrow will reduce future. vibration 40 per cent via two-course construction, a foundation and a wearing surface." ing surface.

Patterson Foundry Appoints New Research Man

Patterson Foundry & Machine Co., of East Liverpool, Ohio, has announced the appointment of Oliver F. Redd to the Research Department. Mr. Redd, who has specialized in engineering physics and has for several years been engaged in development engineering work in the Western Electric Department of the Bell Telephone Laboratories in Chicago, will do research work in connection with mixing, agitating, grinding and other problems and also in the development of new or modified equipment for the process industries.

WHY THOUSANDS





ence for Dodge."

NK P. RUPRECHT.

T JUST doesn't belong in the lowest-priced field, but it is"..."Dodge wins over the other two lowest-priced trucks by an amazing margin"... that's what thousands of smart truck buyers every-where who have tried "all three" are

has built extra value into Dodge trucks from one end to the other. Dodge pioneered full-floating rear axles in lowest-priced trucks, to save you money on upkeep. Dodge pioneered valve seat inserts, to save you gas and valve grinding costs.

Only Dodge Has Hydraulic Brakes Among the three lowest-priced Dodge alone gives you safe, sure, dependable, money-saving hydraulic Depeni **DODGE TRUCKS**

brakes. Dodge perfected hydraulic brakes stay equalized ... save tires, brake linings and adjustment expense. Dodge alone of the three lowest-priced

trucks gives you an oil filter. Only Dodge gives you 4 piston rings...the others 3. Dodge gives you 4 main bearings...the

Of the three lowest-priced trucks, Dodge is the only one built in an exclusive truck plant by trained truck craftsmen.


No wonder thousands are switching to Dodge! Check the three lowest-priced trucks for money-saving features... then check the delivered prices. You can see in three minutes why Dodge is the best

> DODGE DIVISION-CHRYSLER MOTORS





11/2-TON CHASSIS AND CAB 6-cylinder — 136" wheelbase — Full-floating rear axle, hydraulic brakes, valve seat inserts, roller-bearing universals—18 recognised, money-saving features. (Body, hoist and special equipment extra).



commercial express—6-cylinder—111¼" wheelbase. Amaz-ing low price—with 18 high-priced features to save you money every mile it is driven. Fast, dependable, sturdy. Compare it! See your Dodge dealerand ask him for a "show-down" against the other lowest-priced trucks.



Dev of The A

Right ad-build

faced a s eliminate in gradin oped. The contained mit-a Since a ty too cum forms and or back the place er ur Originall The opera and coule seat. Th plete uni a "One-M o practio includ One man maintain roads the patrol un approxim F

> trol of th center to operation ibility wa the unit originall provemen onal po then to machines tors. Fre nally use tracks we The use aintena the patre there was ditional machine. develope tires and

As the

grader de ation of

Durin motor gr covered. able for Anoth veloped now Pl ordinary ment co construc

whereas now ple 12 mont

forded a

the Sing

or four-

Havin neers to controls. efficienc an impr ator to increase the cha Advertisement

Development of the **Motorized Grader**

the

its

By A. O. TECKEMEYER

of The Austin-Western Road Machinery Co.

Right after the Great War, when Right after the Great War, when road-building was resumed, contractors faced a shortage of labor. Partly because of this condition a machine to eliminate a good deal of hand work in grading between forms was developed. This was a Grader with a self-contained power unit ahead of the blade right a combination tractor grader. contained power unit ahead of the blade unit—a combination tractor grader. Since a two unit grader and tractor was too cumbersome to use between the forms and could not be turned readily, nor backed up, this made quite logical the placement of the blade ahead of the power unit, all carried on one frame. Originally steel tired wheels were used. The operator sat directly above the blade so that he had a direct view of his work and could control his tractor from the Thus one man operated the complete unit and it was generally called a "One-Man Grader." The machine was so practical that the field was enlarged to include the maintenance of roads.

One man with a power grader could maintain the same number of miles of roads that four separate horse-drawn patrol units could cover at a saving of approximately 50%.

Refinements of Design

As the use of the one-man power grader developed and the low cost oper-stion of this unit was discovered, improvements were made—First the con-trol of the machine was changed from center to rear for it was found that the operation of the machine and the vis-ibility was such that a man could operate the unit more efficiently from a control back of the motor. The power plant was originally a 20 h.p. engine, but as improvements were made in design additional power was added: first to 30 h.p., then to 42 h.p. until at present such machines are designed with 53 h.p. motors. From the steel tired wheels originally used, the next step was to solid rubber. At about the same time crawler The use of crawlers however involved a number of problems, and the cost of maintenance over the number of miles the patrol grader operated proved expensive. As a result of these handicaps there was developed a set of four driving wheels on the rear, affording additional traction and stability for the ditional traction and stability for the machine. As pneumatic tires were developed they supplanted solid rubber tires and among other advantages afforded a means of using four tires on the Single Drive and eight on the dual or four-wheel drive machine.

During this gradual evolution of the motor grader various new uses were dis-

During this gradual evolution of the motor grader various new uses were discovered. The speed of operation and ease of control made it eminently suitable for scarifying.

Another attachment that was developed with merit was the front V-type Snow Plow. This increased the use of the machine considerably because the ordinary type of road grading equipment could be used only during the construction or maintenance season, construction or maintenance season, whereas the Motor Grader with the snow plow and the blade could be used 12 months of the year.

Hydraulic Controls

Having power available caused engineers to wonder why some of this couldn't be made to operate the various controls, thus increasing the use and efficiency of the Motor Grader. Such am improvement would enable the operator to do more work with less effort, increase the work done and improve the character of the work. The use

of hydraulic and mechanical power control was a jump of just a few years ago. The power controls were made to operate the various blade movements operate the various blade movements such as raising and lowering the blade and scarifier, side shifting and reversing of the blade. The only manual control remaining was the steering of the machine. But the application by Austin-Western of hydraulic power controls facilitated the easy adoption of the hydraulic steer so that now Motor. the hydraulic steer so that now Motor Graders are available with every control accomplished through small levers which can be operated with the pressure

of one finger.
Along with the improved operation of the controls and new design of the drive arrangement, additional stability was built into the Motor Grader. In place of working only on top of the road, the machine could be used for ditch work and rough to be used for ditch work and rough to the road. ditch work and rough grading. The development of the wide front axle and

Advertisement

leaning wheel provided stability for the front end to enable the machine to cut a

Another refinement of Motor Grader Another refinement of Motor Grader design was the addition of wider range speed adjustments. Originally the machines had three-speed transmissions of 1 to 4 miles per hour. The present Motor Grader uses six speeds forward and has a range of speeds from 1½ to 13 miles per hour and two speeds reverse, enabling each job to be done at the most economical speed.

Wide Field of Usefulness

Motor Graders are used now by all who have ever used any type of road machinery. The Lane Company of Con-necticut, McDonald Construction Com-pany of New York, the Atkinson Paving Company of Portland, Oregon, the Inland Construction Company of Omaha, Sam E. Findley of Atlanta, Georgia, and Frederickson and Watson Advertisement

of California, are all contractors using one or more modern power controlled four-wheel Drive Motor Graders on four-wheel Drive Motor Graders on their work. Practically every State gov-their work. Practically every State in ernment operates a Motor Grader, and some employ as many as five hundred. Pennsylvania has used Motor Graders in the development of its program which required the taking over of many miles of town roads. Cities and villages use them for maintaining and building outlying streets as well as for snow removal work, and with the addition of a bulldozer on the front of the machine, have given them the job of keeping city dumps level. Counties use the machine for maintaining, oil mix, cleaning of

ditches, and snow removal work.

The present powerful hydraulically controlled Motor Grader with eight driving tires signifies progress in the highest degree because it means more work accomplished at less cost.

UP TO 85% BROUGHT

INTO PLAY AS NEEDED

Automatic Weight Concentration

The New PLUS in Road Rolling-RESERVE PRESSURE

QUALITY POINT ...

Within 1/4-Inch Surface Variation Under 10-Foot Straight Edge.

PROFIT POINT . . .

Rolling Time 30% to 50% Less-No Cross Rolling.

 The center roll of a Roll-A-Plane is a sentinel placed on guard in the plane of the front and rear rolls, to detect and reduce every irregularity. The diagrams at the right show how it becomes selfactuating after once being lowered into position. The greater the irregularity to be reduced, the greater the force brought to bear at the third pressure point—up to 85% of the machine's weight if necessary. The center roll exerts a negligible force when no high spot appears but concentrates a practically irresistible force in a kneading, compacting, leveling action when an irregularity is met. Its alignment in relation to the other rolls establishes a frue plane which is transferred to the surface being rolled.

Engineers are discovering new values in the principle as more and more Roll-A-Planes are put into service. Contractors and highway officials are discovering a new conception of levelness and a new low cost for quality roads. The industry is accepting as its standard the Roll-A-Plane, or Austin-Western Rollers on which the Roll-A-Plane feature can be added later. A new booklet now on the press describes the Roll-A-Plane process. Send the coupon.

The Austin-Western Road Machinery Co.

Home Office: Aurora, Illinois Cable Address: AWCO, Aurora



Widening Texas Road with Truck Mixers

CONTRACTOR who believes that | truck mixers can solve many of his small but numerous concreting prob-lems recently completed an NRM concrete widening project in southeastern Texas. State Route 8 leads from Beaunexas. State Route 8 leads from Beaumont to eastern Texas and was originally built 18 feet wide. Last summer a contract was let for widening this 3 feet on each side for a distance of 1.4 miles within the city limits of Beaumont. While nothing can beat the 27E paver for pouring 20-foot pavement, the constant moving and pouring of payrow. constant moving and pouring of narrow strips on widening projects is a job just made for the truck mixer. Using a pair of Rex truck mixers with aluminum drums it was possible to mount them on Chevrolet trucks and thus secure economical units able to travel rapidly. With an average haul of 5.2 miles the mixer trucks made their trips in 20 minutes loaded. Thus when a stretch of grade was ready for pouring, the Superintendent called for the trucks to start loading and they showed up on

start loading and they showed up on the job 20 minutes later ready to pour. Work started on July 9 and pouring began on July 11, 1934. One side, a strip 36 inches wide, 9 inches thick at the old concrete, 7 inches thick at the forms and 1.4 miles long, was poured in seven working days with two of the Rex truck mixers hauling the 5.2 miles from the batching plant and carrying a 9-sack batch of 1.8 cubic yards absolute volume.

solute volume.

Crossings Opened in 72 Hours

It was found that a 500-pound modulus of rupture on the standard test beam, normally requiring 10 days' cur-ing, could be secured in 72 hours with the use of high-early-strength cement. The specifications permitted the Resident Engineer to open any section of the pavement in case of emergency whenever the beams showed the 500-pound modulus. Thus side roads serving small communities, entrances to filling stations and roadside stands could be opened promptly, saving much inconvenience and loss of business and minimizing the amount of bridging needed to carry the side-road traffic.

Preparation of Grade for Pouring

Because the old shoulder of the original road was so hard packed by traf-fic, it was impossible to break it up with hand picks. A McCormick-Deer-ing tractor with a Lakewood scarifier was put in to loosen the 3-foot strip to a depth of 9 inches against the old concrete and 7 inches at the form line. The old slab was of 9-6-9-inch section. The loosened sand-clay shoulder material was mucked out with a 2-up mule team and fresno, the owner of which worked his 30 hours and then put another la-borer on for the second 30 hour period the team was permitted to work.

A fine grade crew of about fourteen negro laborers then went in with mat-tocks and shovels and trimmed the grade, four of them cutting the form trench slightly deeper than the grade for the 9-inch Blaw-Knox steel forms which were used for the outer 7-inch thickness of slab. The widening strip sloped 34-inch from the old slab in its 3-foot width. At first the form setters were permitted to place the forms from the old slab but the final form line was found to be wavy because of the variations of the older pavement. The line then was set about every 30 feet and the intermediate pins and grade set by

eye, giving a much more even result. Two men set forms to line and grade and then three men behind lined up the forms and the fine grade crew filled in against them where the trench had been cut low to accommodate the deeper

Broussard-Warfield Handled NRM Project in Beaumont, Texas with 5-Mile Haul

forms. This section was hand tamped to give a firm foundation. The three men who lined up the forms were finishers who were naturally most interested in having the forms accurate. This division of labor would not have been possible, of labor would not have been possible, however, if pouring had been done every day which would have required a separate crew for the two operations. Two reinforcing bars ½-inch in diameter, not dipped or painted, and measuring 40 feet in length were placed in the widening strip to give continuous reinforcement. They were set 6 inches and 18 inches from the form line and 2 inches above the grade, using sheet metal pins through which they were threaded.

Batching and Pouring

The contractor's batching plant was located at his permanent yard about 5.2 miles average haul from this contract. A P & H crane with a 50-foot boom unloaded the gravel and sand from the gondola cars with a Blaw-Knox clamshell and filled the bin of the Johnson batching plant. Because of the few hours a day that batching was actually in progress it was found more economical to employ one man to handle both the crane and batching

by weight.

The truck mixers drove up to the batching plant and backed under to receive their individual batches of 2,237 pounds of sand, and 3,981 pounds of gravel. They then drove to the cement house where two laborers emptied the 9 bags of cement into the drum and filled the water tank with 5.8 gallons of water per sack of cement, which produced a workability factor of 80. The batches were mixed the entire trip to


Upon arriving, the truck, which de-livered the concrete from the rear, ran alongside the strip and the concreting crew took charge. The driver drove ahead slowly as directed after the radial (Continued on page 29)



with Pneumatic Rubber Tire and Roller Bearing

LANSING COMPANY LANSING, MICHIGAN

Chicago New York Minne Philadelphia San Francisco Minneapolis



Upper Illustration: Paver laying a bituminous course on an old concrete pavement. This job was laid in two 11 ft. strips joined at the center. One passage of the machine mixed and spread this crushed stone and asphalt to the entire satisfaction of the Engineers.

Lower Illustration: Shows the more common practice of applying a bituminous course to an old gravel or stone road, mixing and spreading the entire width of the course by making round trips. Note the uniform finish and clean edges in both illustrations.



The Adams Line includes Leaning Wheel Graders, Motor Graders, Elevating Graders, Dump Trailers, Road Maintainers, Rotary Scrapers, Road Rippers, Scarifiers, Plows and Horse-Drawn Earth Moving Tools. Write for catalogs and folders describing these items.

a Better Finish

On your bituminous "road mix" jobs, why not get better results and at the same time save money by using a machine especially designed for this work? Adams Retread Paver mixes bituminous coated ag-

gregate three times in one trip. Compare this with the many trips necessary with single blade machines. Mixing costs are reduced and a better mix is obtained because it is accomplished while the bituminous ma-terial is in its most liquid state.

The same machine spreads the mixed material to exact width and cross-section desired, smooth as a floor and ready for rolling. Edges are straight and clean cut —hand work is practically eliminated. A better finish

Before starting another job, talk this over with your local Adams representative or distributor or write for complete details.

J. D. ADAMS COMPANY

Branches, Representatives and Dis throughout United States

MS RET



ich pro-O. The

trip to nich de

ear, ran acreting drove e radial

F-25

cu. ft.

Tire

d

get by

vith

ma-

loor

cut

RER YOU MORE TRACTION GREATER SAFETY-LONGER WEAR-AT HIGHER SPEEDS

FIRESTONE patented construction features enable us to give you a tire with higher shoulders—wider and deeper non-skid tread.

The cords in the body are Gum-Dipped, giving greater strength and longer flexing life.

The two extra layers of Gum-Dipped cords under the tread give a firmer union between tread and body which holds this heavy non-skid tread securely to the tire body.

Equip today with these safe and economical tires! You will get uninterrupted service, maintain faster schedules and get safety protection beyond anything you have heretofore experienced.

Call on the Firestone Service Store or Service Dealer now and start reducing your operating costs

today.

★ ★ ★ ★ Listen to the Voice of Firestone—featuring Richard Crooks, Gladys Swarthout, or Nelson Eddy — every Monday night over N. B. C. — W E A F Network . . . A Five Star Program



AUTO SUPPLIES FOR TRUCKS AND BUSES

FIRESTONE TRUCK FIRESTONE BRAKE FIRESTONE
TYPE BATTERIES HEAVY DUTY BLOCKS and HEAVY FAN SPARK DUTY LINING BELTS PLUGS Firestone For quick





starts and longer mileage.

For better braking control.



estone

Aggregate Handling and Concreting at Bonneville Dam

(Continued from page 2)

Another 30-inch conveyor, on 460-foot centers, runs through the tunnel. Nineteen radial gates admit the materials from the piles to this conveyor, which in turn feeds to a 400-foot 30-inch inclined conveyor to the batching plant.

The conveying equipment is operated throughout by Allis-Chalmers Falk-geared motors with the exception of the one on the bucket elevator, which is provided with chain drive. Motors are 123 has for the life. 15 has for the cross conhp for the lift, 15 hp for the cross conveyor, 25 hp for the conveyor over storage, 20 hp for the tunnel and 50 hp for the incline. Dodge D.T.I. troughing rolls are used with Dodge-Timken roller bearings and Republic Rubber Co. belt.

Cement Handling and Storage

Located 80 yards from the batching plant is a 15-car capacity steel tank on a steel tower for cement storage. The cars are unloaded by a manually-oper-ated dragline scraper into a hopper. A Fuller-Kinyon pumping unit, located below ground level under the hopper, delivers either direct to the batching plant through an underground pipe, or into the storage tank above. A 60 hp G-E motor operates this unit.

Batching and Mixing Plant

This plant, supported on 14-inch H-beams and rising about 100 feet, has a capacity of about 2,000 cubic yards of concrete a day. The Cramer Machinery Co. of Portland furnished this plant which was designed and fabricated for this job by the C. S. Johnson Co.

At the top of the plant is a centrally located cement compartment of 750

located cement compartment of 750 barrels capacity, together with radially disposed aggregate bins having a total capacity of 1,200 tons. Two grades of stone and three of sand enter these compartments through a distribution chart partments through a distributing chute.
Water comes from a tank adjoining the
mixing plant. Indicators showing at the d mixing operator's station indicate when the cement compartment is full or empty. Four classes of concrete are batched—A, B, and C concrete and

On the floor below are the weigh batchers and the control station for the entire batching and mixing plant. There are seven interlocking, air-operated weigh batchers. Weighing is automatic, with an accuracy within one per cent. A graphic recorder shows the weight

of each material in every batch, together with the consistency of the concrete. This record is on one sheet of paper, being coordinated and accurate to one per cent. The pendulum type scales are of Kron make and the two batch meters

Koehring.

A collecting cone receives the discharge from the batchers and delivers it to an air-operated swivel chute lead-

Slackline

Cableways

underwater

excavation

ing to the two mixers below. Water passes through a separate part of the chute to the mixers.

The single operator is in full view of the batchers, recorder and consistency indicators. He sees the mixers through floor windows, and through a side dow he sees the concrete train and load-ing platform of the hi-line. He controls and dumps the mixers, operates the and dumps the mixers, operates the swivel chute and by lever selects the class of concrete to be mixed. As stated, the system is interlocked. It is impossible to short mix, charge an un-dump mixer or one not in a position to be charged. Lights indicate when each operation is finished and when the next may begin.

Moving the Concrete

There are two 3-yard mixers. They are tilted to discharge to a two-hopper dump car of 6 yards capacity. mixers and car were manufactured by the Norris K. Davis Co. of San Fran-The locomotive is a Plymouth Type 6 Model DLC with St. Paul hydraulic hoist. The shuttle track on which it operates is 250 feet long to the loading platform. This train operates in synchronism with the 1½-minute mixing period of the plant.

The car dumps direct to a 6-yard

The car dumps direct to a 6-yard bucket traveling on the cableway direct to the forms. The cableway leads from an A-frame head tower located on the Island to two movable tail towe Island to two movable tail towers op-erating on a radial track on the hillside above the locks. The tower runway is 600 feet long and the span of the Roeb-ling and Leschen cables is 1,390 feet. This cableway will not quite serve the upper and lower ends of the locks and part of the power house wall. Concrete will be laid in these places by a Rex Pumpcrete unit to be installed on the loading dock. After placing, the concrete is internally vibrated by Viber machines at 4,000 strokes per minute. No special cement has been used on

this work. The concrete is made with the standard cement of the Oregon Portland Cement Co. from its Lime and Oswego plants, and the Beaver Portland Cement Co. from the Gold Hill plant.

Personnel

New

Pus

Typica

Varied

9-Foot

COLO this

be const Gulch a

Slope of Leadvill

through holed th

Waters

down t

tinental

and ser water fi

and sug first wa month.

an orga awarded 20,334-

of Puel Mar At th

an altit

plenty cold. road is winter i it is in road ov

Elect Colo. volt lin from th tated th

The straigh

provide concret

betwee

The the nei the gra east poportal.

portals

It h

on a si

tunnel

nature

illustr

Th

for

W

thi

The general contractor on the power house substructure and navigation local is the General Construction Co. and J. F. Shea Co., Inc., of Portland, Ore. The General Superintendent is Ben Cook The Resident Engineer is Captain J. S. Gorlinski, Corps of Engineers, U.S.A.

> THE FAMOUS ANTGRIP STRAIGHTEDGE

straight under tremendous nill presses, it STAYS straig edges:—one sharp-con scraping; the other ro raightedging. Write for circular

L&M

Manufacturing Company Largest Exclusive Manufacturers of Poving Hand Tests 18382 BEREA ROAD, CLEVELAND, OHIO



Crescent Scrapers long range dirtmoving SAUERMAN BROS. 464 S. Clinton St., Chicago

CLETRAC CRAWLER TRACTORS

THE CLEVELAND TRACTOR COMPANY · Cleveland, Ohio

New Water Tunnel Pushed in Rockies

locks and J. e. The Cook

J. S. U.S.A.

Tools H10

Typical Drilling Rounds Varied to Meet Conditions on 9-Foot, 5½-Inch Tunnel for West Slope Waters

COLORADO cantaloupes instead of thirsty Southern Californians will be consuming the waters from Lincoln Gulch and its tributaries on the West Slope of the Rocky Mountains near Leadville, Colo., when a 3.7-mile tunnel through Independence Pass, which was holed through in February, is completed. Waters which normally would flow down the Colorado River to Hoover Dam will be carried beneath the Con-Dam will be carried beneath the Con-tinental Divide to Twin Lakes Reservoir and sent down the Arkansas River to water fields of Rocky Ford cantalopes and sugar beets. It is expected that the first water will be turned through this

The Twin Lakes Reservoir Canal Co., an organization of Colorado farmers, awarded the contract for driving the 20,334-foot tunnel to Platt Rogers, Inc., of Pueblo, Colo.

Many Difficulties Encountered

At the west portal, the tunnel is at an altitude of 10,503 feet, which means plenty of snow, long winters and intense cold. The east portal at an elevation of 10,453 feet is 3.7 miles away but by road is 20 miles away in summer. In winter the distance is 194 miles because it is impossible to maintain an open road over Independence Pass after snow

Electric power is secured from Aspen, Colo. 25 miles away, over a 13,000-volt line. The west portal is 6 miles from the main highway which necessitated the building of a new road.

Tunnel Plans

Tunnel Plans

The tunnel is a horseshoe-shaped straight bore, 9 feet 5½ inches in diameter and 20,334 feet long. The plans provided for an 8-foot 2-inch interior diameter to allow for a 6 to 9-inch concrete lining about 6,000 feet of which has been completed. In addition to this, between 2,500 and 3,000 feet will be Gunited on the back and ribs.

The total rock excavation will be in the neighborhood of 56,000 cubic yards, the grade is 0.25 per cent, making the east portal 50 feet lower than the west portal. The tunnel is worked from two

portal. The tunnel is worked from two faces with one heading at each of the

Drilling and Blasting


It has been impossible to standardize on a single drilling round for the entire tunnel, because of the widely varying nature of the rock. The typical round illustrated was devised by Frank J. Kane, tunnel superintendent. The cut

There's no better reason for buying the HYB-LUM WHEELBARROW than this:-

IT WILL SAVE YOU MONEY

Our booklet tells you HOW Let us send you a copy uminum Corporation, Jackson, Mich.





A Typical Round Used in Tunnel. Figures Refer to Order of Firing.

holes were drilled 11 or 12 feet, the No. 1 delay holes were 8 feet, while the side holes were drilled to a 9-foot depth using 10-foot steel. This round pulled approximately 8 feet of rock.

A 40 per cent gelatin Extra L.F. dynamite was used, and the average round was loaded with a charge of 160 to 190 pounds although it dropped as low as

68 pounds and went as high as 235

The second cartridge from the bottom of the hole was the primer cartridge. The holes were loaded to within 2½ feet of the collar and no stemming was used. The 26 holes of a single round were primed with Hercules all-metal de-lay electric blasting caps which were fired from a 440-volt line. These new delay electric blasting caps were (Continued on page 22) Bucyrus-Erie Co. Moves New York Office

Bucyrus-Erie Co., South Milwaukee, Wis., moved its New York offices on April 1 from 270 Broadway to the thirty-sixth floor of the RCA Building, Rockefeller Plaza. J. C. Alexander is Eastern Sales Manager in charge of the New York Office.

N S VA



ennsylvania is one of the leading States in the construction of modern ads. In a single year (1930) FLEX-PLANES were used on 119 projects for installing contraction joints to control cracks and produce a traffic guide line. Travelers often comment on the fine work and straight joint lines.

Equipment Furnished By

FLEXIBLE ROAD JOINT MACHINE COMPANY

WARREN, OHIO



Avoid Legal Pitfalls

These brief abstracts of court decisions may aid you. Local ordinances or state laws may alter conditions in your community. If in doubt consult your own attorney.

Edited by A. L. H. STREET, Attorney-at-Law.

Danger in Threats To Prosecute

To Prosecute

Contractors who enjoyed Will Rogers in his picture, "Young as You Feel," may have approved his act in compelling the villain to turn over to the heroine \$40,000 he owed her, by threatening to have the swindler arrested. But if any contractor be thus inspired to use similar means to make an embezzling employee or some other crooked debtor diagorge, we suggest that the contractor at least omit invitations to Tom, Dick and Harry to come in and hear the threat made.

Evidently, our hero did not know that he was committing a felony—blackmail—when he forced the villain to indorse a draft for \$40,000 by threatening to have warrants for his arrest served upon him. Nor did he seem to realize that by inviting everyone in the neighborhood to come in and witness the unveiling of a worthless "monument sold" to the villain, he was supplying thirty or forty witnesses to his own commission of a felony.

One who is disposed to collect debts under threats of prosecution will do well to make the threats to the debtor in private. Better yet, he will leave it to his lawyer to let the debtor understand what is apt to happen if the latter does not pay what he owes.

Limits on Supervising **Engineer's Authority**

"Has the engineer a right to bind the owner by agreeing to this?" is a question that every contractor should ask himself every time that an engineer directs the doing of work not contemplated by an original contract. It is easy to assume inaccurately that the engineer stands in the shoes of owner in every instance.

To illustrate, a municipal contractor was lately denied right to recover for extra work authorized by the city engineer, because the contract required approval of the city council, which was not obtained. (New York Supreme Court, Appellate Division: Bewley v. City of Lockport, 263 N. Y. S. 109).

Custom as Element of Contracts

"Please pay us for the piling and lumber we furnished you for building those state highway bridges for the State," requested a

we furnished you for building those state highway bridges for the State," requested a lumber company.

"But the State has not paid us yet for building the bridges," replied the contractor. "It is customary in this neck of the woods for the material man to wait until the contractor is paid before expecting payment."

"We are not bound by any such custom, if it exists," rejoined the lumber company. "In the first place, the contract calls for payment to us within thirty days after delivery of the material. And it is well-settled law that a custom can never be proved to contradict the explicit provisions of a contract. A custom may be proved to give proper interpretation to a provision in a contract that is doubtful or ambiguous in its meaning, but never to contradict the plain wording of an agreement. And, in the second place, a custom must be reasonable, before it becomes an implied part of a contract. The custom you rely upon would defeat our right to recover under the statutory bond you gave the State as contractor, and is therefore unreasonable."

"The lumber company is right in its contentions," declared the Arkansas Supreme Court in the case of National Lumber & Creosoting Co. v. Mullins, 59 S. W. 2d, 493.

Federal Building Contractor Subjected to State Tax

Subjected to State Tax

"Please ante \$250 for the privilege of engaging in the business of contracting in Virginia," said the Commonwealth to an Illinois construction company.

"But we are not doing business in Virginia," demurred the company. "We are creeting a post office building in Lynchburg, but the site belongs to Uncle Sam and Virginia does not have jurisdiction over an inch of it."

"Yes, but how are you going to do the job without using the abutting sidewalks and streets, which belong to Virginia?" queried the Commonwealth. "And when you use them as an incident to performing your contract you are doing business in Virginia, although the completed building will stand wholly upon federal land."

"Commonwealth is right," declared the Supreme Court of Appeals of Virginia in the case of Ralph Sollitt & Sons Construction Co. v. Commonwealth of Virginia, 172 S. E. 290.

"Were it possible for the contractor to do the job without interfering with public use of the abutting streets, no valid tax could be levied. The contractor can not be taxed for mere use of the streets in common with the public, for transportation of materials, etc. But his shutting the public off from use of abutting sidewalks and streets and taking possession of the same for use in construction operations does afford a basis for taxation."

Question of Interest

Question of Interest

"It is not merely a matter of interest, but of principle," might have complained the State of Washington had it been disposed to pun in the case of Brewster v. State, 16 Pac. 2d, 813.

A trial court had awarded judgment for more than \$18,000, and added to it interest on that amount at 6 per cent per annum since the job was completed. The Supreme Court of the state upheld the principal item, but struck off the interest allowance. The court followed the rule generally recognized by the courts throughout the country—that where there is a bona fide dispute as to how much money has been earned under a contract, no interest accrues before the amount has been liquidated by judgment. But interest would have been proper from the date of the completion and acceptance of the job, had there been no dispute as to the amount earned by the contractor.

Another point decided in the same case was that the contractor was not entitled to pay on account of overhaul eliminated by the state, where the contract called for payment on a unit basis and reserved right in the state to increase or decrease the quantities of work to be performed.

Liability for Faulty Work

Store building burned. Merchant having lease moved out. Landlord hired contractor to rebuild. Contractor rebuilt. Tenant moved back in. Building collapsed. Merchant sued Contractor for damages. Contractor defeated suit. Texas Court of Civil Appeals said (Nedler v. Neece Lumber Co., 63 S. W. 2d, 403).

(Nedler v. Neece Lumber Co., 63 S. W. 2d, 403):

"After the completion and acceptance of a building, the liability of the builder [to third parties] for accidents caused by defective construction ceases and the liability attaches to the owner, whether the damages are attributable to his own negligence or to the negligence of the builder."

"A CHRYSLER

WILL DO IT BETTER"

Ürg

ably a annua \$22,0

highw

Trum of P

ent I the a

Thi the I an e Citize Th



. . and Boss, there's no question of its performance and quality. It will save us money too."


More and more buyers of Industrial Engines are eliminating the element of chance by turning to the dependability and long life that only engine building specialists such as Chrysler can give. More and more Industrial Engine users are taking advantage of Chrysler's gigantic engineering laboratories and Chrysler's mammoth production facilities for the solution of their power problems.

Chrysler Industrial Engines are built to finer limits of precision. They cost less to buy and less to maintain. Possessing enviable records for ruggedness and long life a Chrysler Industrial Engine is the answer to many industrial power problems. There Chrysler Industrial Engine which will do your job better. Investigate and see for yourself, without obligation, of course.

CHRYSLER CORPORATION . AMPLEX DIVISION . DETROIT, MICHIGAN



of all orders for BUFFALO-SPRING-FIELDS in recent years have come from users. The other third have come from those who investi-gated and were impressed with the generous measure od will existing for these rollers.



BUFFALO-SPRINGFIELD ROLLERS

are obtainable in sizes from 1½ to 17 tons—3-wheel or to dem—attachments for grading, scarifying, etc., optiona

THE BUFFALO-SPRINGFIELD ROLLER CO. Springfield, Ohio

PORTABLE ASPHALT PLANTS TOWER TYPE

LARGE CAPACITIES HOT OR COLD MIX

Accurate control of materials to comply with any standard specifications for bituminous mixtures.

Send for Bulletin T-248

HETHERINGTON AND BERNER INC

Indianapolis, Indiana

\$22,000,000 a Year Urged for Minn. Roads

If Minnesota is to provide "reasonably adequate" highway service for the public on the expanded state system, an annual expenditure of approximately \$22,000,000 should be made on trunk highways.

This is the conclusion of experts of the United States Bureau of Public Roads who spent the past year making an exhaustive study of Minnesota's highway problems at the request of the Citizens' Interim Highway Committee authorized by the 1933 Legislature.

authorized by the 1933 Legislature.

The \$22,000,000 annual expenditure which is recommended by Dr. Henry Trumbower, economist for the Bureau of Public Roads, and H. R. Briggs, statistician for the Bureau, for the present 11,300-mile trunk system is about the amount which was spent yearly on the old 6,700-mile system. If expendi-

tures on the enlarged system were made on the same scale as on the old system, the yearly amount would be more than \$36,000,000, the report states.

On the basis of state revenues existing in 1933 and 1934, with Federal Aid, the Highway Department would have only slightly more than \$13,000,000 a year income for the trunk system, Commissioner N. W. Elsberg estimates. If the Legislature provides sufficient additional revenues to match Federal Aid, this amount will be brought up to about \$20,000,000 a year, including the aid allowance of \$3,400,000.

As to the division of trunk highway costs between the large cities and the rural districts, the report states that in 1932, rural residents paid 33 per cent of the motor vehicle license fees and gas tax, while they accounted for 30 per cent of the traffic on the trunk system. The report concludes that the city areas contribute slightly less in trunk highway revenues than their proportion of travel would call for.

Regarding the general costs of the Minnesota highway system, the report

says:

"Judged by similar states where studies have been made, the Minnesota highway expenditures in general are not abnormal, and those made by the local units of government, especially the towns, are low. The imposts against motor vehicles in Minnesota are less than those in adjoining states and in the country as a whole."

New Diesel Engines with 100 to 150 Hp


One of the features of the new diesel engine recently announced by the Murphy Diesel Co., Ltd., Milwaukee, Wis., is the new fuel injection system which combines the fuel pump and nozzle and is placed in the center of the cylinder head, surrounded by four valves. This injector unit is actuated directly by two camshafts, one on each side. Oil is delivered to the injectors

under 10 pounds pressure, surplus oil being returned to the fuel tank. Actual injector pressure of the fuel into the combustion chamber ranges from 2,000 pounds at idle speed to 4,500 pounds at maximum rpm, this pressure being concentrated in the tip of the injector.

Other features of this new 6-cylinder 53%, x 616 unit are greatling stating with

Other features of this new 6-cylinder 53/4 x 61/2 unit are gasoline starting with auxiliary fuel burned within its own combustion chambers; oil-tight and dust-tight construction; improved cooling and lubrication system with water and oil pumps mounted directly on the crankshaft; oil-bath Donaldson-type air cleaners built into the inlet manifold to form an integral part of the engine; centrifugal, flyball-type governor, controlling a hydraulic servo motor which permits control of speed variations from full load to no load; and general symmetrical design.

The first of this new line of diesels is the MD-6 of 100 to 150 hp, which will be followed later by smaller en-





Compacting Road Surface With a Bros Oilmix Roller

Compacting the Surfaces of Oil-Mix Roads

Every highway engineer has been faced with the problem of preparing oil-mix pavement surface so that it would not be cut, rutted, and thrown by speed traffic. The compaction method generally used, that of opening the road to regulated traffic, gave rise to a device made by the Wm. Bros Boiler & Mfg. Co., Road Machinery Division, Minneapolis, Minn., for the purpose of compacting such surfaces.

The Bros rubber-tired Oilmix roller

The Bros rubber-tired Oilmix roller is a platform trailer mounted on nine tires, 7.50 x 15, staggered front and rear. The width across the rear tires is 5 feet, filling the distance between the dual tires of the largest truck. The platform is a steel tray bolted to the frame and covering a tank in the frame which will hold 2 tons of steel punchings. It is 6 feet wide, 7 feet long and 3 feet 3 inches high. The gross load permissible is 7 tons, including the roller. This roller may be towed behind a truck, motor patrol or pneumatic-tired tractor and compacts the surface of fresh or disked oil-mix pavement. The roller plus the dual tires of the towing

roller plus the dual tires of the towing truck cover a path almost 8 feet wide and it is claimed that three trips of this unit over each portion of the road gives a smooth compacted surface, sealed against penetration of moisture and

ready for use by traffic.

This roller may also be used to compact disintegrating shoulders of oil-mix roads a year old, or to roll roads which have been torn up by disking and bladed out without re-oiling.

Zinc Dust Paint for Many Uses

Metallic zinc powder industrial paint, Metallic zinc powder industrial paint, designed as a primer and finishing coat for iron, steel and galvanized surfaces to protect them against rust and corrosion, is described in a new booklet recently issued by the New Jersey Zinc Sales Co., 160 Front St., New York City. This paint, which is claimed to withstand sudden temperature changes and various climatic conditions, will also completely obliterate in one coat any background of color.

Copies of this booklet may be secured by interested contractors and engineers direct from the company.

direct from the company.

Bulk Cement Batching Plant for Sale

One factory reconditioned and guaranteed plant, consisting of 250-bbl. Beaumont bin, 40 bbl. per hour Sprout-Waldron screw conveyor unloading and elevating unit, complete with gasoline engine, roller chain drives, air compressor and generator. Price \$1200, f.o.b. Muncy, Pa. Sprout, Waldron & Co., Inc., Muncy, Pa.

Two Air-Cooled Stages On V-Type Compressor

With the compressor cylinder arranged in two banks in a true V with a special baffle immediately back of the fan which puts the cooling air on and around the cylinders and not between them, a new line of Plus Portable twostage air-cooled compressors has been announced by the Sullivan Machinery Co., 814 Wrigley Bldg., Chicago, Ill. These compressors are made in four sizes, 105 cubic feet, 160 cubic feet, 210 cubic feet, and 315 cubic feet.

The design allows complete inspection of both intake and discharge valves, the entire piston head and the cylinder walls. Sullivan Micro-Lift valves with large area and light weight eliminate valve pounding.

The inter-cooling is said to be so effi-

clent that the hand can be held comfortably on the high pressure intake. All gasoline-powered models have Buda engines. Model 105 is gasoline-powered

only and Models 160, 210 and 315 are supplied with either gasoline engines or Caterpillar diesel engines.

2-Yard Shovel-Dragline **Excavates for Aqueduct**

(Photo on page 44)

Work on Sections 20 through 23 of the Colorado River Aqueduct near San Jacinto, Calif., which was awarded to the Griffith Co., Los Angeles, Calif., for approximately \$1,700,000, involves the excavation and construction of about 12 miles of aqueduct between San Jacinto and Riverside. The excavation Jacinto and Riverside. The excavation includes both rock and dirt cut for a ditch approximately 30 feet wide and 15 feet deep.

Excavation is being done by a Lima 801 combination shovel and dragline of

2-yard capacity, powered by a Wau-kesha Hesselman diesel oil engine, re-cently purchased from Smith Booth Usher Co., equipment distributor of Los

Angeles. This is the first Lima shove of this size to operate in Southern California.

CONCRETE VIBRATORS

Air operated vibrators for all classes of concrete construction including Bridge deck slabs, Dams and Locks, Highway pavement and Concrete products.

Write for circulars and engineering data.

MUNSELL CONCRETE VIBRATORS



NOW, in a few minutes' time and absolutely without cost or the slightest obligation, any contractor can learn the true facts about lubricants in relation to low operating costs. For through the medium of this remarkable "cards on the table" demonstration kit, Alemite brings you to the basic principles in the make-up of all lubricants. With your own eyes you can see the real cause of many equipment breakdowns and lay-ups-judge for yourself the proper course to follow in obtaining the most value for your lubricant dollar.

Here's Why You Should Get the Truth Without Delay

Right now, revolutionary changes and advances are being made in lubricants. Engineering improvements made by leading equipment manufacturers demand increased efficiency in the lubrication of gears and bearings. Extreme-Pressure Lubricants are on the way in. As an operator you are entitled to know what they are, what they do and what qualities they should possess under actual operating conditions. A demonstration from the Alemite Kit will put you "in on the ground floor."

ALEMITE Jemprite SPECIALIZED LUBRICANTS

As pioneer in the field of specialized lubrication, Alemite has developed Extreme-Pressure Lubricants that meet and actually exceed the most rigid specifications of equipment manufacturers-Alemite Temprite Lubricants that assure an extra margin of safety against repairs-give fully 200% plus protection for every moving part. This remarkable series includes new and improved Tractor-Roll lubricants, and lubricants which assure positive lubricating efficiency in extremes of heat and cold in plain or antifriction bearings and all types of gears. Regardless of the extent of your operations you can get visual proof of their money-saving, repair-preventing efficiency. Remember: Visual proof. Send in the coupon now.

ALEMITE CORPORATION

(Division of Stewart-Warner Corp'n.)
1850 DIVERSEY PARKWAY
CHIC CHICAGO, ILLINOIS Stewart-Warner-Alemite Corp'n. of Canada, Ltd., Belleville, Ont., Can.

(Division of Stewart-Warn 1850 Diversey Parkwa I'd like to learn the tr Lubricants for contract	y, Chicago, Illinois
Name	
Address	
City	
Firm Name	State

Con for

are sup ing. T 50 to 5 and cut Over th poured of Dou scribed other similar in thic and all cut off

neal.

The

lengths over in No. 3 s There Kierna driving tion p extract piling. Afte

and pr

poured semi-c rectan The s inches ing or in hei gether 5 feet 5 feet CORCT

The to the built 171/2 below pier i of 15 feet h

coping

inford direct

S

Concreting Plant for Apalach. Bridge

(Continued from page 1)

0

all

uc-

eck gh-

ete

E

are supported on 22 piles for each footing. These are untreated piles driven 50 to 55 feet below mean water level and cut off to about 30 feet in length. Over them a seal of tremie concrete was Over them a seal of tremie concrete was poured from the floating concrete plant of Doullut & Ewin which will be described in a subsequent article. All other concrete for this contract was similarly furnished. The seal varied in thickness from 12 feet to 16 feet 6 inches. After the seal had been poured the largest teach of the contract was seal and the contract was seal of the contract and allowed to cure for a few da cofferdam was pumped out and the piles cut off in the dry one foot above the

The steel sheet piling for the cofferdams for these piers consisted of 180 lengths of Carnegie, M-106, 60 feet and over in length, and 84 pieces of Larssen No. 3 section 60 feet and over in length. There were 16 corner sections for the first and 8 for the second. Two Mc-Kiernan-Terry No. 7 double-acting steam pile hammers were used for driving the sheet piling and a No. 9B3 of the same make for the foundation piling. A Vulcan No. 400 pile extractor was used for pulling the sheet piling. The river bottom at the pier with the pier w ites was chiefly fine sand and silt.

After the cofferdams had been sealed and pumped out all other work was in the dry. The footings varied from 3 to 4 feet in height, on top of which was poured the pier proper consisting of semi-circular noses on the outsides and rectangular sections toward the center. The slender piers measuring 5 feet 6 inches both ways at the base and taperinches both ways at the base and tapering on a batter of $\frac{3}{6}$ -inch per foot to 3×3 feet under the bridge seat varied in height from 39 to 48 feet. The pairs of columns of the piers were tied together by a cross beam $2\frac{1}{2}$ feet wide by 5 feet deep and 20 feet long at about 5 feet above water level and another concrete beam 5 feet deep under the concrete beam 5 feet deep under the coping.

The Swing Span Pier

The swing span Pier

The swing span pier built similarly to the other eight piers within a steel sheet piling cofferdam is circular and built on 134 untreated piles with a seal 17½ feet thick carried down to 42 feet below mean water level. The swing span pier is 34 feet wide, with circular ends of 15¾-foot radii. The footing is 4 feet high with a mattress of ½-inch reinforcing bars on &-inch centers in both inforcing bars on 8-inch centers in both directions, placed 3 feet above the cut-

23

20' Spread, 1/2" Chips Backward or Forward

KOB Disc Spreader

Spreads sand, gravel, chips, shale, cinders, or chloride.

smoother job with more coverage, and varying widths.

Fits any dump truck, large or small. Write for further information

KOB MFG. CO.

320 L. Brown St., Milwanks

off of the foundation piles and 9 inches below the center of the footing course. The pier base is 25 feet in diameter and of cellular construction with the outside wall 2 feet 6 inches thick, the four interesting of the construction of the constr tersecting web walls 2 feet thick and the central column formed by them 6 feet square. The bridge seat course 2 feet thick has a 6-inch fillet.

Quantities

Pier 5, the Pivot Pier of the Swing Bridge

Seal concrete

Class AA concrete (for use in salt water)

Reinforcing steel.

Untreated wood piling.

Pier 3, Typical of the Other Sev in salt 588 cubic yards 8,279 pounds 5,360 feet 147 cubic yards in salt 147 cubic yards

The spans for the bridge structure between the piers vary from 66 feet 6 inches to 83 feet. The bridge deck is carried on I-beam stringers. Six coats of brushed-on bituminous waterproofing were applied to the pier columns up to the underside of the coping.

Floating and Other Equipment

The floating equipment on this contract consisted of five barges measuring 30 x 100 x 7-foot draft, on two of which were mounted stiffleg derricks and the remaining three were used for materials and service. The 5-ton American derrick had an 84-foot boom and was operated by a 2-drup Lidgerwood hoist and ated by a 2-drum Lidgerwood hoist and the barge carried a 40-hp Lookout boiler and a 40-hp Mundy auxiliary boiler. The 10-ton derrick had a 90foot boom, a 3-drum Lambert hoist and weidner boiler and a 40-hp Lambert boiler as auxiliary. A 1-yard Owen clamshell bucket was used for cleaning out the cofferdams and was carried by the derrick barge engaged in that work at the time. There were two 1-yard Insley bottom-dump, one 34-yard Blaw-Knox and one 34-yard tremie-type con-



Cross Section and Photo of Elongated Roller-Gate Concrete Bucket Placing Concrete in Piers

crete buckets for the barge handling concreting and also 64 feet of 8-inch and 80 feet of 10-inch galvanized iron spiral tremie pipe. Later the tremie (Continued on page 36)

AND LOWER MAINTENANCE COSTS ARE YOURS IN ANY CEDAR RAPIDS PLANT YOU BUY




CEDAR RAPIDS STONE SIZING PLANT

WHATEVER YOUR REQUIREMENTS MAY BE IN THE MATERIAL PRODUCING OR HANDLING FIELD, YOU WILL ALWAYS FIND A CEDAR RAPIDS PLANT THAT WILL

ASK FOR OUR CATALOGS AND BULLE-




CEDAR RAPIDS JAW CRUSHER





TRAVELING ROAD MIX PLANT






SCREENING AND LOADING PLANT




CEDAR RAPIDS SYMONS VIBRATOR SCREEN



PORTABLE WASHING PLANTS







IOWA MANUFACTURING COMPANY

Lubrication Queries

Question

We have had to have an unusual number of visits from service men lately because of breakdowns and "freezing" bearings. Several times they have told us that the trouble has been in the lubrication of these bearings. We have always used plenty of oil and grease and can see no reason why we have had so much trouble. Can you help us?—Detroit, Mich.

Answer

We could preach a sermon on the text ou have so well stated. Following the old Yankee custom of answering one question by asking another, here's one for you. Why is it that contractors, who take a great deal of time in investigation before purchasing construction equip-ment valued at thousands of dollars, should give so little consideration to the type of oils used in their ma-chinery?

chinery?

In our series of articles in 1934, we stressed over and over again the necessity of buying the proper lubricating oils or greases for construction equipment. Quality at a slightly higher price than cheap inferior grades of lubricants is the best insurance against breakdowns and their attendant time losses. Always select the better grade of lubricant of proper consistency for the lubricant of proper consistency for the particular bearing.

Question

With our machines working three shifts a day we don't like to lay them off at the end of every shift for lubrication. Is it not just as well to lubricate them once every other day, using more oil and grease, than to give them just a and grease, than to give them just a little lubrication three times a day?— Oak Park, Ill.

Answer

Either of the extremes you suggest is bad. A mere "lick and a promise" means too little grease or oil and the chance that spent grease and oil will not be expelled by the fresh lubricant. On the other hand, the use of an excessive amount of lubricant at infrequent intervals is even worse. It is only quent intervals is even worse. It is only the lubricant which actually reaches the bearings that can do its work. Oil merely poured over some part of the machine runs off, collects dirt, and per-forms no useful function.

Follow the definite instructions given Follow the definite instructions given in your service manual for the engine or machine you are using, both as to frequency of lubrication and as to the quality and quantity of lubricants to use. The time required to do this will pay large dividends in long life and continued efficient operation of your equipment. The manufacturer has made a careful study of the lubrication of his a careful study of the lubrication of his machines and has given you his best advice in the service manual because he is placing his reputation in your hands.

COMPLETE CUTTING AND WELDING **APPARATUS**

The Alexander Milburn Co. 1400 W. Baltimore St. Balti

Lehman Elected Chairman of Blaw-Knox Co.

At a recent meeting of the Board of Directors of the Blaw-Knox Co., Pittsburgh, Pa., Albert C. Lehman, President, was elected to the newly-created office of Chairman of the Board in appreciation of his thirty years of service to the company since its inception, the resolution of the Board stated.

Irvin F. Lehman, Vice President, who has also been associated with the company since its early days, was elected President and Frank Cordes was made Senior Vice President.

The following were re-elected: Chester H. Lehman, Vice President; Robert F. McCloskey, Vice President; George L. Dumbauld, Treasurer; H. B. Loxterman, Secretary; B. L. Hirshfield, Chairman, Finance Committee; Paul W. Klein, Assistant Treasurer; H. S. Strassburger, Assistant Treasurer, and Assist burger, Assistant Treasurer and Assistant Secretary; and P. A. McCullough,

Protecting Wood Structures Against Decay and Termites

Those interested in wooden structures will find much valuable information in a new booklet just published by the Tennessee Eastman Corp., dealing with the protection of wood against decay, dry rot and termites. The booklet is entitled "Preservation with Eastman NO-D-K" and takes up the varie methods of preservation, setting for definite recommendations for the difference ent types of construction. Its pages as well illustrated with photographs and

diagrams to make it easily understood
Copies of this booklet are available
free to readers of Contractors and
Engineers Monthly by writing to the Tennessee Eastman Corp., Kingspor



SIDE O TRUK SHOULDER MAINTAINER works road shoulders thoroughly at an average cost of 15c per mile. Get the facts on this proven way of making road maintenance dollars go farther.

THE BURCH CORPORATION, Crestline, Ohio

ROAD AND SHOULDER MAINTAINERS CRACK FILLERS SFREADERS FOR STONE, ASPHALT, AND CHIPS CAR UNLOADERS CONVEYORS TRENCH FILLERS ROAD AND STREET CASTINGS SECTIONAL CAST IRON PIPE THE ROSS SNOW PLOW

For BETTER ROADS al LOWER

HE WALKER has reserve power a-plenty to fill the bucket to overflowinghoist rapidly . . . swing the machine quickly. No time lost here—and no time lost in moving because, due to the walking traction, the machine takes the shortest path between working points. Investigate The Walker for your next job. Manufactured by Bucyrus-Monighan Company, Chicago, Illinois.



EXCAVATING, DRILLING, AND MATERIAL-HANDLING EQUIPMENT...SOUTH MILWAUKEE, WISCONSIN

Stahi a Rea

The resi being pul hesion; the The pla work is a ture absor limits of the cohesiv

Ru Bank-ru this type of ago many dered su but it has es prese detrimenta may be gr is of no by the int ficient size clay, the fi within sat sized grav not particu as far as (it does car The clay ecessity e for a clay value or p ore ecor hesive cla sary becar quired. pure clay most desi

> There a truction fully. Wh a new gra existing r done by coarse ag shoulder. is suitabl bladed on must be h The clay lumpy; the or rolling have dry ing done material i acted. brought f coarse ma the actual Mixing and forth

which, co ave more

tor, or by ordinary 1 work mu teeth do depth. T most eff equipmen et at any of cutting material mix in la

s bladed If the we it should down unt moisture prolonger supplied

Stabilized Roads a Real Job

(Continued from page 2)

The resistance of the soil particles to being pulled apart is known as cohesion; this might simply be referred to as the stickiness of the clay.

The plastic index of a material often referred to in papers on stabilization work is a measure of its range of moisture absorption within its dry to wet limits of plasticity; it is a measure of the cohesive properties of the soil fines.

Run-of-Bank Aggregate

Bank-run gravel gives good results in his type of construction. A few years ago many of these banks were not considered suitable for surfacing material but it has been found that the clay and fines present are desirable rather than detrimental. The fact that one bank may be graded differently from another is of no serious consequence because, by the introduction of some of the de-ficient sizes and the proper amount of clay, the finished product can be brought within satisfactory limits. The larger-sized gravel should be removed. It is not particularly detrimental to the road, as far as construction is concerned, but it does cause difficulty in maintenance. The clay in the subgrade may be used if it is suitable, thereby avoiding the necessity of hauling it in. If not suitable it is usually profitable to search for a clay which has a high cohesive value or plasticity index. It is usually more economical to haul a highly cohesive clay a greater distance if necessary because of the lesser quantity required. All clay soil banks contain fines other than pure clay, but it is the pure clay content which is needed. The most desirable clay soils are those which, coming from the bank, do not have more than 50 per cent silt.

Mixing as far as construction is concerned, but

Mixing


There are several methods of con-There are several methods of construction which are being used successfully. Where the work is being done on a new grade rather than stabilizing an existing road, the mixing can best be done by first depositing the gravel or coarse aggregate in a windrow on one shoulder and the clay on the opposite shoulder. If the clay in the subgrade is suitable it may be scarified and bladed onto the shoulder: if not, clay bladed onto the shoulder; if not, clay must be hauled from a suitable deposit. must be hauled from a suitable deposit. The clay should be pulverized if it is lumpy; this may be done by blading or rolling. The desirable condition is to have dry weather when the mixing is being done and some rains when the mixed material is being laid down and compacted. The windrows should then be trungly from the shoulders and appeared pacted. The windrows should then be brought from the shoulders and spread over the road in alternating layers of coarse material and clay. This distributes the material uniformly and makes the state of the state o

the actual mixing more effective.

Mixing may be done by blading back and forth with a blade grader and tractor, or by a multiple blade drag or an ordinary harrow. With the harrow the work must be done in layers as the teeth do not mix effectively the entire depth. The heavy road disc harrow is a most effective and economical piece of equipment for mixing. The discs can be equipment for mixing. The discs can be set at any desired angle and are capable of cutting through the entire depth of material so that it is not necessary to mix in layers.

Spreading

After mixing is complete the material is bladed to the shoulders in windrows. If the weather is extremely dry or wet it should be left there and not laid down until it has the proper amount of moisture to compact well. If there is a prolonged dry season the water can be supplied with sprinkling tanks. The (Continued on page 25)



ETNY

BITUMINOUS DISTRIBUTORS

NEW— A more compact assembly of pump, valves and circulating system, making insulation easier, allowing the valves to be readily heated from the motor exhaust, reducing the weight of the unit about 300 pounds, and permitting the distributor to be mounted 4 inches lower on the truck without reducing the road clearance of the spray bars.

NEW— Leakless valves, which eliminate the drip-drip which has up till now been so annoying to operators. These leakless valves are being enthusiastically received.

NEW— The fifth wheel driven tachometer, more accurate and satisfactory than one driven from either the front wheel or the transmission. On the way to and from the job, the fifth wheel


Have you a post-card handy? Just write on it: 504, with your name and address, and we'll send you promptly a copy of our Bulletin 504, which will give you a better, more complete idea of these two new ETNYRES. The same general design and principle of operation that have made the ETNYRE Model F so popular are retained, and we predict that because of their practicability and simplicity, ETNYRE Distributors will continue to be the standard for years to come.



E. D. ETNYRE & COMPANY

400 JEFFERSON ST.,

OREGON, ILL.





At the Rattle Snake Dump, the 60-inch Stacker . . it is telescopically extensible 50 feet . . is equipped with a 150 ft. boom, caterpillar mounted to swing through 180 degrees

MOVING A I A MILE WITH JEFFREY CONVEYORS

Two of the Jeffrey 60-inch Conveyor Lines (below) leading to the dump . . they travel 600 feet per minute . . handle upward of 4,000 tons per hour.



WORLD'S LARGEST CON-VEYOR SYSTEM SPEEDS EXCAVATION AT GRAND COULEE

Dirt, more dirt, yet more dirt.. it's flowing fast from the Grand Coulee excavation. In 300 working days or less the last of some 14 million bank yards will be gone out, all carried by Jeffrey Conveying Equipment.

Seven large Heavy Duty Feeders, two self-propelled distributing Stackers and 21/2 miles of Belt Conveyors designed and manufactured by Jeffrey accomplish this Herculean task, disposing of the excavated dirt and the filling of the cofferdam. The one system on the west bank alone handles 4,000 tons per hour. The rubber belts are carried on Jeffrey anti-friction Reliance and Hercules Idlers, operating continuously through three 7-hour shifts each day.

On your next job, large or small, call on us.

The Jeffrey Manufacturing Company

949-99 North Fourth Street, Columbus, Ohio



A general view (below) of the excavation job . . showing Jeffrey Feeder Conveyors converging to Jeffrey Surge Feeder and Jeffrey Main Line Conveyor (right-background) climbing a mountain. The Jeffrey Conveyors breasting the piling are being used to fill the 3,000 ft. cofferdam. Well over a mile and a half of Jeffrey Conveyors are shown.





Are I

Conclos the Mixed WITH

ing time and how The cor Rogers, S. Bures preventi with the and mus phase of profits w

almost e approximente cost. El a direct tends to does not of equiple assuradversel labor. In hours of decrease tion of cause an transport chinery. Table of avoid bined major.

major shows t

lays on of pote amount cost of

delays

ing equito the content of \$6,000 have phave collaboration between the save beautiful to the save pump.

Thir Up dealt requipm cent of all aved duced by 21. per ce ciency age coper ce materia

agement on the labor a cent be that a struction ments relative terials.

This tion per MONTH 1, 1935

Subsiday of

Are You Losing Profits **Through Lost Time?**

Conclusion of Studies of the Construction of **Mixed-Bituminous Roads**

WITH this installment we conclude this discussion of the factors causing time losses on bituminous road jobs and how such losses may be prevented. The conclusion presented by C. F. Rogers, Assistant Highway Engineer, U. S. Bureau of Public Roads, is that the prevention of time losses must begin with the designing and planning the job and must be followed through in every phase of the work, if there are to be any profits when the job is done.

Avoidable Delays Costly

The costs of labor and equipment are almost equal and together they produce approximately 40 per cent of the total cost. Elimination of time losses effects a direct saving in labor costs and also tends to reduce equipment costs but does not necessarily reduce the amount does not necessarily reduce the amount of equipment required. It should not be assumed that greater efficiency will adversely affect the employment of labor. There will be a decrease in the hours of labor per mile of road but the decreased costs will permit the construction of a greater total mileage and cause an increase in the production and transportation of materials and machinery.

D

S OF one

belle

yors this

the

west belts

hifts

chinery.

Table 11 shows the amount and cost of avoidable delay for all projects combined by causes and includes both major and minor delays. Table 12 major and minor delays. Table 12 shows the amount and cost of such delays on each project. This dissipation of potential profit on all projects amounts to nearly 8 per cent of the cost of the projects. On one project delays arising from a shortage of hauling equipment resulted in losses equal to the cost of two 5-ton trucks. In another case bin delays caused a loss of \$6,000 when half of this amount would have provided facilities which would have completely eliminated this delay. have completely eliminated this delay. have completely eliminated this delay. Losses from insufficient dryer capacity have been found large enough to supply a battery of dryers. A contractor purchased a new asphalt pump to replace one causing delay and within a week the savings had offset the cost of the pump. These are typical examples of conditions found on many projects.

Think of Costs of Materials in Designing Mixes

Up to this point the discussion has dealt mainly with costs of labor and equipment which constituted 40.3 per cent of the total cost. Elimination of all avoidable delays would have reduced the second of the cost of the cos duced the cost of labor and equipment by 21.7 per cent, making them 34.5 per cent of the total cost. Such effi-ciency is within the reach of the average contractor who will then have 65.5 per cent of the total cost involved in materials. Under highly efficient manmaterials. Under highly efficient management they may be much higher since on the most efficient project studied labor and equipment costs were 46 per cent below the average. It is evident that a discussion of economy in construction of mixed bituminous pavements must take into consideration the relative quantities and costs of the materials.

Use of local materials sometimes

This is to certify that the average circulation per issue of Contractons and Engineers Monthly for the six months' period January 1, 1935 to June 30, 1935 is 25,000.

EDGAR J. BUTTENHEIM. ley of April, 1935.

EDWIN WAGNER, Notary.

Table 11.—Cost of Avoidable Delays on All Projects by

Cause of delay	Avoidable major delay	Cost of avoidable major delay	Avoidable minor delay	Cost of avoidable minor delay	Cost of all avoidable delay
Hauling equipment operation Bins empty or overflowing	Hours 44.0	\$1,549	Hours 613.5 638.5	\$37,208 38,725	\$38,757 38,725
Handling material at plant Lack of material at plant	108.6 149.5	3,823 5,263	83.4	5,058	8,881 5,263
Operative at plant	80.3	2.827	146.2	8,866	8,866
Miscellaneous Lack of subgrade	73.9 75.2	2,602 2,647 1,680	1.8	109	2,711
Heating material at plant Late start, management Handling asphaltic cement	47.7 45.9	1,616	************	**************	1,680 1,616
and fuelFinishing		************	45.3	2,747	2,747
Mechanical at street Mechanical at plant	31.6 7.1	1,113 250	***************************************	***************************************	1,113
Total	663.8	23,370	1,573.1	95,405	118,775

1	Table	12.—Cost	of	Avoidable	Delays	by	Projects
---	-------	----------	----	-----------	--------	----	----------

on Road, Massachusetts, on route from Worcester to Providence. Tarvia-built

offers the opportunity to make savings in their cost and in their transportation.

There has been some tendency toward

adopting this practice where conditions

are favorable. On two recent projects in the western states four sizes of aggregate were produced from local deposits with excellent results. In each case a

semi-portable aggregate plant of considerable size was installed and the output was sufficient to care for the maximum production of the mixing plant.

10.1 6.1 2.0 13.7 20.6 100.5 48.0 44.8 109.2 41.3 43.6 6.2 6.3 59.3 5.6 43.0 10.3 \$53, 20 \$5, 60 28, 00 28, 00 66, 00 17, 50 25, 60 22, 80 66, 20 16, 30 32, 50 51, 10 29, 10 17, 30 25, 90 34, 50 46, 70 90, 50 58, 30 35, 70 54, 20 86, 20 92, 00 35.20 1,016 60.65 68.4 4,148

in 1913, before the World War, this Tarvia road remains as smooth, easy-riding and skid-safe as it was the year it was laid. GOOD ROADS AT LOW COST 1913



To road officials and highway engineers traffic-safety of a road is equally as important as its durability and low cost. Tarvia roads qualify on all counts. Tarvia penetrates deeply into the road crust, holding the stone or gravel firmly exposed on the road surface. The resulting slightly granular surface, which is characteristic of Tarvia road types, provides an effectual tread-hold for automobile tires. Let the Tarvia field man help you provide safe roads.

THE BARRETT COMPANY New York Chicago Philadelphia Cleveland Birmingham St. Louis Toledo Milwaukee Detroit Baltimore Columbus Youngstown Lebanon Buffalo Syracuse Bethlehem Rochester Portland, Me. In Canada: THE BARRETT COMPANY, LTD. Montreal Toronto

A Planned Program of National Highways

Of late we have heard a lot about a planned national highway program. This is merely our old friend in a new suit of clothes. Highways, unlike many other public works activities, have been well planned. For a great many years the states in cooperation with the Bureau of Public Roads have been developing plans and programs for highways, covering all phases of construction and development. Many of these plans are based on intensive transportation surveys and in practically every case the results of these surveys justify to the fullest degree the plans and designs of construction already undertaken.

It has been intimated that a new agency may undertake the work of planning a national highway program. While such a program is highly essential to insure economic progress in developing our highway system, why duplicate work already largely accomplished? The several states in conjunction with the Bureau of Public Roads already have developed such a plan. Future studies will continue to improve this plan and to coordinate other public works projects and transportation systems. There is no agency so completely qualified and with such a wealth of experience to continue this work as the U. S. Bureau of Public Roads.

We have only to analyze the accomplishments of the state highway departments and the Bureau during the period immediately following the passage of the National Recovery Act to see that no highway planning can be undertaken without utilizing the experience and facilities of the Bureau and the state highway departments. In spite of the fact that new phases of work, new at least to the state highway departments, were brought into the picture, detailed programs and plans from nearly every state in the Union poured into the Bureau of Public Roads.

This alone justifies the statement that highway planning should be undertaken by the now existing agencies, the Bureau of Public Roads and the state highway departments, which have already contributed so much to our present highway system.

-From a paper by H. C. Whitehurst, presented before the American Road Builders' Association.



New Pump Catalog

A new 32-page catalog No. 35 covering the complete line of Sterling Quality self-priming centrifugal pumping units has recently been issued by the Sterling Machinery Corp., 411 Southwest Blvd.,

Kansas City, Mo.

This company has recently brought out a complete line of self-priming centrifugal pumps arranged for belt drive, which are described in this catalog. It also contains complete information on the individual models designed for gasoline power or electric moton and in addition contains considerable engineering information of interest to contractors and engineers.

Copies of this catalog may be secured gratis direct from the Sterling Machinery Corp.



CMC Has What it Takes!

- A Complete Line To Pick From
- Modern Design Lower Prices


Investigate

Wonder Tilting Mixers, Hoists, Pumps, Wheel Barrows, Master & Silverstreak Drum Type Mixers, Saw Rigs, Plaster and Mortar Mixers, Concrete Carts.

Write For Free Descriptive Bulletins

CONSTRUCTION MACHINERY COMPANY

500 Glenwood St., Waterloo, la.



THE HESSELMAN STARTS EASILY

It is as easy to start a Waukesha-Hesselman Oil Engine as a gasoline engine. A primer is used as with a gasoline engine and hand cranking is just as feasible. The primer atomizes and sprays a small charge of priming gasoline into the air intake manifold. And the charge flows readily into the cylinder through the overhead valves.

The cup shaped Hesselman piston head, which forms the combustion chamber, catches and retains any excess priming charge.

And it is burned instead of de-

stroying the cylinder wall lubricating film.

The Hesselman piston head is designed with extra metal. This aids in supplying and holding sufficient heat to insure a combustible mixture at the spark plug. As soon as the engine fires, it begins to function on fuel oil. Even in the coldest weather, a Hesselman requires no more priming,

nor any longer warm-up period than a gasoline engine.

Write for Bulletin 1000.

Waukesha Motor Company,
Waukesha, Wisconsin.



The location of the rings provides an unobstructed path for heat flow from the

THIS IS NO. 4 OF A SERIES on the Hesselman Oil Engine. No. 5 will appear next month. A reprint of the complete series will be mailed on request.

WAUKESHA ENGINES*

Mai Are

A numainter of the state of the

lected,

ardous to spre

guaran right to equipp with the smooth and the care. ous marked and the care such in this we if follows. traffic

the dri

Rej

torists bridges and meing of compass work.
Guairail sl The ve a part it is li place. made part it is li place.

N. H

worth

Wal N. H., Hampe its an Other Lang, Presid Sleepe

5

Maintenance Men Are Born, Not Made

Machin

IY

Y

lm.

ned

ing

on

ion

er,

ng,

iod

0.

ny,

A number of new developments in A number of new developments in maintenance operations and a survey of the accepted methods were discussed by C. W. McClain, Engineer of Maintenance, Indiana State Highway Commission, before the Twenty-First Annual Purdue Road School. Mr. McClain's comments on the phase of maintenance dealing with repairs follow.

Patching of Surface

Patching of Surface

This class of work is frequently neglected, allowing surfaces to become hazardous to traffic, and permitting failures to spread unduly over great areas. To assure proper methods of repair and to guarantee that the work be done at the right time, there should be properly equipped gangs for this work. Men with the ability to make uniform and smooth patches "are born, not made" and the crews should be chosen with care. Methods of patching with various materials are well outlined in literature of reputable manufacturers of such materials. The instructions for this work are presented in detail and if followed will result in satisfactory such materials. The instructions for this work are presented in detail and if followed will result in satisfactory jobs. Because of the great increase in traffic speed, shoulder patching should receive the same care and attention as the driving surface.

Replacement of Structure Parts

One of the favorite exercises of motorists is battering the end posts of steel bridges. We have found that it is safer and more economical to let the furnishing of steel and its installation to steel companies familiar with this class of

Guard rail posts of either cable or rail should be replaced immediately. The very fact the guard rail was hit at a particular location is good evidence it is liable to be hit again at the same place. Repairs of this nature should be made promptly. Such promptness may save a life. Bridge floors ought to be repaired at once and, if replaced, attention is called to the desirability of using creosoted lumber, if lumber is used. Its added life, due to treatment, is well worth the difference in cost. Again it should be stressed that a "stitch in time saves nine." Also keep equipment well lubricated and painted.

N. H. Good Roads Assn. **Elects Officers**

Wallace F. Purrington of Concord, N. H., was elected President of the New Hampshire Good Roads Association at its annual meeting held in Concord. Other officers elected were: Fred W. Lang, City Engineer of Concord, Vice Lang, City Engineer of Concord, Vice President for two years; Frank D. Sleeper of Lakeport, Secretary-Treas-

South Bend

Bituminous Pressure Distributors Street Flushers Street Sprinklers

Literature and prices on request

MUNICIPAL SUPPLY COMPANY

SOUTH BEND, INDIANA

urer; Leroy F. Johnson, Maintenance Engineer, State Highway Department, and J. Harold Johnson, Secretary to the

State Highway Commissioner, Directors for two years. Other officers elected last year for two-year terms and who continue in office are: Hartford Nay, Division En-

gineer, State Highway Department, Vice President; Harold Ingham of Concord and Austin Page of Concord, Directors.

Republic's N. Y. Office Moves to New Quarters

The New York District Sales Office of the Republic Steel Corp. has moved from the Lincoln Building to new quarters in the Chrysler Building. quarters in the Chrysler Building. W. H. Oliver continues in charge of the office as District Sales Manager. The Export Department, under the direction of D. H. Bellamore, General Export Manager, will also occupy a portion of Republic's new suite in the Chrysler Building.

Better Rural Roads

Poets have long pointed out that spring brings thoughts of romance, flowers that bloom, the awakening of nature and all that sort of thing. Spring also brings thaws, freshets and with them rutted, muddy country roads, often times impassable, in sections where the farmto-market route is of great importance to the community.

Fortunately, progress in road build-ing has made the vision of good roads a reality and it is possible to build and maintain hard-surfaced rural roads. Stable all-weather roads, developed through soil studies by the U.S. Bureau of Public Roads, and constructed by the proper mixture of local materials and calcium chloride, are inexpensive in first cost and greatly reduce the cost of

Hundreds of miles of such roads have already been constructed, principally in Michigan, Indiana, Minnesota and Ohio, and the method of construction is rapidly becoming standardized. Safe, hard-surfaced rural roads are a definite business asset to every community.



Resharpen Your Rock Bits
with a Quick-Way Bit Grinder.
Resharpen them again and again at a
cost of from 2c to 4c per bit.

C. H. CARLSON MFG. CO. 13-15 Main St. N. E. Minneapolis, Min



One of the CUMMINS Diesel-powered LINN Tractors owned by J. Robert Bazely, Inc., Contracting Engineers, Pottsville, Pa. Owner reports that fuel costs average less than ¼ that of gasoline power.

Replace gasoline engines with

CUMMINS Diesel Engines

for superior power performance and amazing economy


WHEREVER you now use gasoline engines for automotive, portable and stationary equipment-CUMMINS Diesel Engines will do a better job, at a big saving in cost.

These modern, efficient Diesel engines have the "backbone" for the toughest jobs. They have greater capacity—they handle heavier loads—they speed up your operations. They give dependable, trouble-free performance at an amazingly low operating cost. A check-up with any user will confirm these facts.

Don't confuse CUMMINS Diesels with ordinary Diesels. CUMMINS pioneered in producing compact, high-speed Diesel engines to replace gasoline power. As a result, CUMMINS engineers developed many radical improvements in Diesel design, construction and operation. These important features are exclusive with CUMMINS Diesels.

CUMMINS offers a complete line of Diesels from 35 to 400 H. P. Ask us for complete facts. In writing, please list your gasoline-powered equipment.

CUMMINS ENGINE CO. -The Leader in Diesel COLUMBUS, INDIANA . SALES AND SERVICE IN PRINCIPAL CITIES THROUGHOUT THE U. S. .



Tunnel Section

New Water Tunnel through Rockies

(Continued from page 11)

especially developed to speed up tunnel driving. They have no vents so that moisture can not get inside to cause

Four Cycles in 24 Hours

Four Cycles in 24 Hours

Three 8-hour shifts were worked at each face and four cycles were completed each 24 hours. From 2½ to 3 hours after the mucking was finished were required to set up and drill a round and mucking was completed in about the same length of time. The total of 5 to 6 hours is very fast for setting up drills, drilling, blasting, ventilating, and mucking in a 9½-foot tunnel, even under the best conditions.

Pneumatic Equipment

There were four Gardner-Denver No. 17 drills used at each heading, the top machine drilling the 12 holes above the center, while the bottom machines center, while the bottom machines drilled the remaining 14 holes in the round. This procedure was varied in individual individual rounds, inasmuch as the rounds varied from 25 to 30 holes.

The contractor used 1½-inch hollow round Crusca drill steel. After each shot, the steel car was pushed in and removed the used steel which was taken

removed the used steel which was taken to the shop and resharpened on Gardner-Denver drill sharpeners.

Compressed air for the drills was furnished by two Ingersoll-Rand, Imperial XCB-2 compressors, driven by General Electric Type KT 200-horse-power motors. The face was ventilated by air supplied by a 15-horsepower American blower at each portal delivering through du Pont Ventube and Bemis Flexpipe flexible tubing.

Mucking

Mucking

The face was mucked with a Sullivan
3-drum scraper hoist which was pulled
up a slide so that the rock was loaded
direct into 52-foot Koppel cars. Each
heading had 20 of these side-dump, allsteel roller bearing cars which were
usually sufficient for mucking one
round. An O'Rourke switcher was used
so that cars could be switched without
a side track. Two Mancha Mules at
each portal hauled the loaded muck
cars to the dumps. cars to the dumps.

Concreting

The progress in concrete lining has averaged about 150 feet a day. Eight sections of 25 feet each of Blaw-Knox collapsible steel forms are used. The concrete is mixed outside and hauled concrete is mixed outside and hauled into the tunnel in 1½-yard rocker dump cars, eight to ten yards to a train. From the cars it is dumped on an elevating conveyor which feeds the hopper above the Pressweld concrete placer.

Personnel

O. R. Smith is Chief Engineer in charge of construction for the Twin Lakes Reservoir Canal Co., while Myron Beswick, General Superintendent, has been in active charge of the job for the contractor, with Ross R. May, Chief

Engineer, and Frank J. Kane, Tunnel Superintendent for both portals. Allan Rogers is Assistant Superintendent at the west portal and Lawrence Wright, Assistant Superintendent at the east portal. Platt Rogers, President and General Manager of Platt Rogers, Inc., spent considerable time on the job.

Still Much Work to Do on Our Highway System

Among the activities necessary to a balanced highway program, provision should be made for the following types of work, according to a paper presented by H. C. Whitehurst before the American Road Builders' Association.

1. Extension of the existing system

where traffic justifies, including the filling in of all gaps in the present

primary system.

Modernization of existing conditions to insure safety and to meet traffic requirements adequately in an effort to relieve congestion.

Development of the secondary sys-tem consistent with traffic needs in an economical and sound manner.

Improvement of municipal main thoroughfares.

Maintenance of all highways to prevent rapid deterioration and insure safe operating conditions.

A reasonable program of replacement such as conditions justify.

Construction of footways along main highways, particularly in and

near metropolitan areas. Roadside beautification to the ex-

Pic

shut-d

of thei

The

with t

the co

one co

ticular and v

The b

in the smiled


fun o

machi

tent of restoring natural beauty and preventing erosion.

Care of Safety Lines

Safety lines should be installed on all items of a floating plant as follows: a section of 34-inch hemp line should be spliced or otherwise securely fastened to each cavel or timber head. Overhand each cavel or timber head. Overhand knots should be tied in the line at intervals of one foot. The section of line should be long enough to reach the surface of the water when the deck is at the highest point above the water it is likely to reach in ordinary service. When damaged or deteriorated from exposure these lines should be replaced. these lines should be replaced.



Picks and Shovels

ex-

n all

s: a
d be
ed to
nand
nter-

line

surt the kely (Continued from page 1)

shut-downs at the plant, and the quality of their work fell off.


The Superintendent talked it over with the Foreman and finally came to the conclusion that in half an hour no one could lose much at penny ante, particularly at the slow pace they played and with long interludes of kidding. The ban was lifted and what a change in the men! They worked twice as hard, smiled at their work, and got twice the fun out of the game down behind the machine shop.

Maintaining County Roads

Gravel, slag, stone or cinder roads must be dragged regularly unless they have had a bituminous treatment. Some of the less important roads may not require more than one dragging a month while the most important ones may require three or four draggings a week.

A multiple blade maintainer pulled by a tractor is the most suitable equipment for this work. Small road drags and power graders and truck scrapers are used to augment the maintainers during certain seasons when extra work is necessary. A light resurfacing of a fine gravel is required from time to time to replace the worn out material. Paved road surfaces require constant attention. Holes which develop must be broken out and patched. Settled places are brought back to grade by forcing mud under the slabs. Expansion joints and contraction cracks must be well sealed with bituminous material to prevent serious damage to the pavement from water and ice.

Neglect of this will soon make more expensive repairs to the pavement necessary. The use of a bituminous premix has proved very satisfactory for the repair of small holes and depressions. A portable asphalt plant is now used for the mixing of this material, by Wayne County, Mich. This has resulted in considerable saving compared to previous methods.



Crossing a Railroad Trestle with a Crawler Crane.

Not As Easy As It Looks

Crossing the White River on a railway trestle only 10 feet wide with crawlers 9½ feet wide has its thrills, according to Eddie Leak, dragline operator for the C. E. Jefferson Co., of Indianapolis. Rotating a series of 12 x 12 timbers astride the rails to form a solid footing for the 24-ton P & H machine, straight travel and perfect balance were necessary all the way to avoid a nose dive into the flood below.

Grinders for Rock Bits

The Quick-Way grinder for detachable rock bits, manufactured by the C. H. Carlson Mfg. Co., 13-15 Main St., N. E., Minneapolis, Minn., is made in two standard sizes, either one sufficiently large for grinding all sizes of rock bits. Model G is designed for moderate production and Model LG for high production, operating with two men if desired.

Model G, which is particularly adapted to contractors and portable work, is powered by an AC 60-cycle 110 or 220-phase, ball-bearing, 3,600-rpm dust-proof motor. The grinder is designed for dry grinding and the grinding wheels are constructed for speedy and efficient service. It is claimed that any style or make of bit can be resharpened in from two to four minutes. Model G has a net weight of 140 pounds.

Model LG, with a 2-hp motor, is more adapted to permanent jobs or jobs running over a greater period. This model is equipped with guards over the grinding wheels so constructed that a suction blower can be mounted to take the dust away from the operator. The slides are adjustable and ways are fitted with gibs to compensate for any wear.

It is claimed that the Model LG resharpens bits in about 1½ minutes. Both models index the bits which makes all cutting edges the same height and is claimed to give longer life to the bits and lessen the strain on the steel rod that extends from the bit to the hammer.

Highway Department Employed Farmers

Farmers and teams were hired by the Minnesota State Highway Department to drag secondary roads which would not support motorized equipment during the spring break-up.

District maintenance engineers throughout the state were instructed to arrange with farmers in their territory for whatever help of the kind was needed. Included in the 4,500 miles of county roads taken into the trunk system last year are many miles not well enough constructed to hold up standard motorized equipment when the frost was coming out of the ground.

Load restrictions were also placed on many of the secondary routes, which were strictly enforced to prevent the roads from becoming entirely impassable during the spring.



OIL TRACTORS

V:8

Performance is saving time . . .

Economy is saving money for

CONTRACTORS



... AND HERE'S HOW TO PROVE YOU CAN SAVE TOO!

V-8 Performance is saving time and speeding up service...how V-8 Economy saves money in operating costs...how owners are enjoying amazingly low maintenance and repair costs. Many owners report 100,000 miles of economical, reliable service. Hundreds more express their appreciation of the money-saving Ford Engine Exchange Plan and other parts exchange privileges ... advantages that assure low cost of up-keep.

Thus, Ford V-8 Trucks and Commercial Cars have proved in service the outstanding superiority of V-8 Performance, V-8 Economy and V-8 Reliability. Your Ford dealer is so proud of this record ... he is so confident that the 1935 Ford V-8 Trucks and Commercial Cars are the greatest ever to bear the Ford name ... that he invites you to make your own "on-the-job" test ... with your own loads ... over your own routes ... with your own driver ... and let you draw your own conclusions.

FORD V-8 TRUCKS AND COMMERCIAL CARS

Stal a R

best rethe mapacting Where will pudinary A s necessare keep it conditions and the conditions are the conditi

damp.
too mi
materi
weathe
to su
means
impor
clay
cause

is use per so 3 inching the square spread road in be the of the method composite of few do pacted

If used top I calcinface square produced the ding t

HU

Hub far free ings tand high

Stabilized Roads a Real Job

10

01

e

of

1d

S

Iľ ur

T

(Continued from page 17)

best results can be obtained by laying the material down, leveling and com-pacting in approximately 3-inch layers. Where it is available a tamping roller will produce better results than the orroad roller.

A sufficient amount of moisture is sary in the material at all times to keep it in a compact, dense, impervious condition. Dry material will dust off condition. Dry material will dust off under traffic in dry weather unless kept damp. On the other hand, clay alone or damp. On the other hand, clay alone or too much clay in a mixture with coarse material will become plastic in wet weather. Consequently, it is necessary to supply the moisture by artificial means in dry weather, and it is likewise important that there is not too much clay present in the mixture so as to cause trouble in wet weather.

Calcium Chloride Binder

Calcium chloride is used to supply the required moisture. There are two methods of using it; the integral mix and surface application. If the integral mix is used, 2 pounds of calcium chloride per square yard is applied to the top 3 inches of the mixed material. Following this not more than 1½ pounds per square yard of calcium chloride is spread over the loose top layer of mixed road material. The chloride should then be thoroughly mixed with the top layer of the material by any of the above methods and then spread, leveled and compacted. The surface should be main-tained by blading and dragging for a few days until it is rather firmly com-pacted and should then be followed by 1/2-pound per square yard surface application with calcium chloride.

plication with calcium chloride.

If the surface application method is used the shaping and compacting of the top layer should be completed and the calcium chloride then spread on the surface at the rate of 1 to 1½ pounds per square yard. The surface method will produce best results if applied late in the day or after rains. After completing the application of calcium chloride, the road should be kept under maintenance for several days by blading and tenance for several days by blading and dragging until compacted firm and smooth. The conditions will govern the amount of maintenance and type of

HUBER ANNOUNCES

THE GREATEST

equipment which should be used. Make The Crown Right

Too much attention cannot be paid to working in the proper crown on the completed surface. This should be approximately ½-inch to the foot. A flat crown will permit pools of water to lay on the surface after rains and will soon result in a surface full of potholes. The water must be taken off the surface quickly if the road is to be kept smooth and intact. This matter of crown is one and intact. This matter of crown is one of the most important items in stabilized construction.

Conclusion

In conclusion it may be said that the stabilized road properly constructed fits very conveniently into the low-cost construction field and is very well adapted to the use of native local materials where they are available. Proper construction and a knowledge of main-tenance is essential to secure satisfac-tory results. The application of theory and laboratory control must be done in a practical manner so as to secure good results without involving unreasonable costs to obtain unnecessary refinement.

From an A.R.B.A. convention paper.

Small-Size Rooters for 35, 50-Hp Tractors

The Type S rooter, designed for use with 35 and 50-hp tractors, has recently been announced by R. G. Le Tourneau, Inc., Stockton, Calif. In general, it follows the same design of the larger Le Tourneau rooters, with rugged, allwelded special steel construction, but is lightened somewhat to assure efficient use with tractors of from 35 to 50 hp.

Its length overall is $13\frac{1}{2}$ feet, its overall width, 75 inches, with 24-inch diameter wheels and it is equipped with high-duty Timken bearings. The three-tooth model weighs 4,280 pounds and the five-tooth model, 4,760 pounds.

Maintenance Book Free

A 52-page booklet entitled "Road Maintenance with Tarvia" has recently been issued by the Barrett Co., 40 Rector St., New York City. This booklet covers the various phases of maintenance, including patching, filling cracks and joints, surface treatment, traffic-bound roads, curing slippery pavements, resurfacing, widening and reducing ex-

ROLLER

cessive crown, as well as the various types of road construction. The book is profusely illustrated and also contains a table showing the grades and purposes of the various types of Tarvia and Tarvia-Lithic.

Copies of the booklet are available free to readers of Contractors and ENGINEERS MONTHLY by writing direct to the company or to this magazine.



RAPID HEATING ACCURATE APPLICATION NO DRIPPING FROM NOZZLES

All of these—plus economical operation—are yours when you buy a Littleford Model "C" Pressure Distributor. Find out what this Distributor will do for you. Write for complete information covering whatever size you desire.





the successful and economical use of the new Metal Air Joints in concrete highway construction. Complete puddling of the concrete adjacent to the joint, with 100% bond between steel and slab is insured . . . and spading costs are reduced because ONE MAN with ONE VIBRO-SPADE easily spades the transverse and longitudinal joints and side forms. For jobs of all types and sizes, contractors prefer JACKSON VIBRO-SPADES.

models or sises . . . VS-E1, VS-2, VS-3 and VS-4 . . . for

EVER BUII

Huber again sets the pace with a brand new 5-TON hydraulic road roller. It's by fer the greatest value ever offered. Features include a guaranteed positive trouble-free reverse with single lever control; a six-cylinder, heavy-duty engine; roller bear-ings throughout; full hydraulic control; dual steering (hand or power—instan-taneous change-over); removable drive roll rims; short turns; four speeds both ways; high transport speed. These are but a few of the outstanding qualifications that make the Huber the greatest 5-Ton Road Roller ever built. Send for complete

THE HUBER MANUFACTURING CO., MARION, OHIO

breause ACKSON VIBRO-SPADES

are more dependable . . . easier to handle . . . do more jobs and do them better . . . are more economical to operate and maintain . . . sturdier . . . and place stronger, denser concrete with better bond between layers and between concrete and reinforcing, with greater uniformity, with greater water-tightness, and with definite savings in cement and labor.

Designed, engineered and built by the originators of vibratory concrete placing equipment, JACKSON VIBRO-SPADES lead the field in this important type of construction equipment. Constantly improved and developed, they simplify and perfect vibratory concrete placement on work of all types. Furnished in four sizes . . . with portable power plants if desired. Write for complete information. ELECTRIC TAMPER & EQUIPMENT CO., LUDINGTON, MICHIGAN.

Paving 6.97 Miles With Sand Asphalt

(Continued from page 5)

end. A Mack engine was used to rotate the drier and a Le Roi engine to drive a small compressor which supplied air for moving the asphalt and air pressure for the drier torches. The dried material discharged into an open chute for free inspection where a same chute for free inspection where a sample of sand mixture could be obtained before it was delivered to the boot of the hot elevator. The bucket elevator the hot elevator. The bucket elevator delivered the dry sand to a rotary screen which, on this contract, discarded all material over 10-mesh in size. Beneath the hot sand storage bin was a weighing batcher for the sand made by R. D. Cole of Newman, Ga.

A vertical steam boiler mounted in front of the plant supplied steam for the burners of the drier, for running the steam asphalt nump, and for heat-

the burners of the drier, for running the steam asphalt pump, and for heat-ing the storage tank, the steam jacket of the mixing drum and the hollow blades of the mixer. It also furnished steam for the water pump.

Shell 50 to 60 penetration asphalt was received by tank car at Orchard, Ala., about 4½ miles from the plant. A steam booster plant at the spur track where the tank car was spotted maintained the temperature of the asphalt. Hauling to the mixing plant was done with a 600-gallon tank well insulated and mounted on a Mack 3½-ton truck. The truck delivered the hot asphalt to a 9,000-gallon storage tank at the plant, the material being forced from the tank

truck to the storage tank by air pressure,
A Worthington reciprocating water pump was used to move the asphalt from the storage tank to the superheater, a coal-fired kettle where the temperature was raised to 275-350 degrees Fahrenheit. From the super-heater the asphalt flowed by gravity to the weighing cylinder or closed tank mounted on beam scales. From the weigh tank it was raised to the rotary mixer drum by air pressure. The mixer was operated by a Le Roi gasoline engine.

Batch Handling

The batches for the base and top varied somewhat in composition as follows: Base, 9,280 pounds of sand, 720 pounds of asphalt; Top, 8,420 pounds of sand, 960 pounds of asphalt and 620 pounds of limestone dust. The batches were all mixed 5 minutes and one batch constituted a truck load.

The batches were hauled to the grade by a fleet of six trucks with sheet iron bodies made for A. G. Boone of Columbia, S. C., hauling 10,000-pound batches to the load without any difficulty. The truck bodies were oiled about every third load to prepare ticking third load to prevent sticking.

Labor Organization

When running base, a crew of four-teen men was required to operate the





The Rotary Mixing Plant Which Averaged 300 Tons of Hot Mix a Day.

plant but two more were added when running top to handle the limestone dust. The plant and road crews each worked 12-hour shifts, or 10-hour shifts with the extra 2 hours to make up for lost time due to bad weather, of which there was plenty on this contract. Paving was started April 19 and between that date and August 10 they were able (Continued on page 35)

Line of Core Drills for Highway Testing

Class PT Calyx core drills, particularly adaptable for drilling sample cores from concrete highways, are part of a complete line of Calyx drills made by the Ingersoll-Rand Co., 11 Broadway, New York City. In this capacity the machine produces a sample which shows the exact condition of the road, and its base and subsoil.

In most cases these drills are mounted on motor trucks but special self-propelled mounted units are available. These, operated in pairs or as units of a fleet, permit very rapid and efficient sampling of long stretches of highway at frequent intervals. Gasoline power is standard on these drills, but an electric-motor-driven drill is available for town pavement testing or for stationary laboratory experimental stationary

holes for electric light standards, holes through concrete slabs for filling underlying seams, 18 to 24-inch holes for manholes through pavement or side walks holes for safety zone standards and incident the standards and standards and standards and standards are standards. similar purposes.

A complete description of these units as well as the other members of the line of Calyx drills will be found in a new 48-page catalog No. 9501 which may be secured free direct from the company.



Easily carried by one man; 100% automatic

2" Self-Priming Centrifugal Pump



Record Pay B

that they tires and often they o recogni bottom co he will k he will k
know hov
he does no
ing; and
of real us
"I don
ords," th
claims.

he a simplify the operations a business ost imp somethir The truing should have a retruck, cheplies neattention.

on the tir

to tabula Firesto

Ohio, h system.
Tag, on serial n and place speedom when it and the In the make up reading hicle Re Mileage life, and

and in a From

rapid tr

various

tires cos

tire is faster t on a fr chanica can be mainte proved. personn maintai mooth

and by show h best to chase p Other t

"The

Records on Your Tires Pay Big Dividends

unite

Most contractors will say off-hand that they know their cost per mile on tires and other truck equipment. But often they do not know definitely enough to recognize the difference between rock-bottom costs and expense that eats into the business. If the operator has records be will know these costs and he will he will know these costs, and he will know how to prevent road delays. If he does not have the records, he is guess-

ing; and his guesses are too vague to be of real use.

"I don't have time to keep tire records," the operator of a truck often claims. But keeping such records can be a simple matter, and it is necessary if the operation of the fleet is to be on a business-like basis. Tire records are most important, operators find, because "something can always be done about

The truck driver's part in record keeping should be very simple. He should have a report card to turn in with the truck, checking the listed items of supplies needed or the parts requiring attention. For tires, a tag which he puts on the tire as it comes off the wheel and which is then passed on for the office

Firestone Tire & Rubber Co., Akron, Ohio, has developed a simple and efficient truck mileage and cost record system. It consists of a Tire Change Tag, on which can be recorded the serial number of the tire, the determined plants of the control of lag, on which can be recorded the serial number of the tire, the date and place of change, vehicle number, speedometer reading, position of tire when it came off and when it went on, cause of removal, who made the change,

cause of removal, who made the change, and the final disposition.

In the office, these tags are used to make up the monthly Vehicle Record, which shows the daily speedometer reading of the vehicle and the serial number of each of its tires. This Vehicle Record is used to make the Tire Mileage Record for each tire during its life, and shows its mileage on any truck and in any position it has served.

and in any position it has served.

From this record, a glance will show rapid tread wear and wheel position on which it occurred; mileage you get from various makes of tires; and accurate tires costs. Premature tire wear may be traced and its causes determined. If a tire is worn out at 12,000 miles or faster than the average, and has been on a front wheel, misalignment or me-chanical irregularity is indicated and

The record shows how good your maintenance is and how it can be improved. It is the job of your garage personnel to get more tire mileage by maintaining proper pressure, by putting smooth tires on the inside when duals are used, by putting new tires on front, and by rotating tires. These records show how well this is done.

They also show what tires are the best to buy, for cost per mile, not pur-chase price, is the business basis of cost. Other truck records similar to those for

"The Strongest Geared Power for Its Weight in the World"—

BEEBE ALL-STEEL HAND HOIST

Capacity—5 tons straight line Weight—110 pounds Size—16x17x13" high Two speeds—4 to 1; 24 to 1 Positive internal brake Price \$75. Write for list of dealers

BEEBE BROS. SEATTLE,

of records will help to prevent unnecessary expense, delay and accidents, adding an important margin of profit for the contractor and cutting down the overhead for highway departments.

Sets of blanks for these tire records are available gratis to readers of Contractors and Engineers Monthly by writing direct to Firestone or to this magazine.

New Detroit Distributor Appointed by Link-Belt

R. G. Moeller Co., 14415 Meyers Road, Detroit, Mich., has recently been appointed distributor of Link-Belt crawler shovels, cranes, draglines, and locomotive track-type cranes by the Link-Belt Co., Chicago, Ill. The Moeller organization was established in 1924 and has twice moved to larger quarters to take care of increased business. R. G. Moeller is President; O. H. Baker, Secretary; C. C. Huebner, Vice President; and T. C. Moeller, Sales Manager.



You've got to watch costs on haulage jobs



and CHEVROLET VALVE-IN-HEAD SIXES cut costs to a minimum"

CHEVROLET Chevrolet trucks are precisionengineered to deliver outstanding results on the cost ledger as well as on the job. The improved Blue-Flame six-cylinder truck engine is a masterpiece of power efficiencygiving full power at hauling speeds, along with unusual operating economy. Extra-strong axles,

husky transmissions, rugged springs . . . each and every sturdy part . . . assure more payload hours and smaller maintenance costs. Your Chevrolet dealer invites you to get the "Owner's Simplified Operating Record" and learn of Chevrolet's low operating costs.

CHEVROLET MOTOR CO., DETROIT, MICHIGAN

Compare Chevrolet's low delivered prices and easy G. M. A. C. terms. A General Motors Value.

WORLD'S LOWEST PRICED LINE OF TRUCKS

CHEVROLET TRUCKS

	FREE! Mail coupon for
"OW	NER'S SIMPLIFIED OPERATING RECORD"
Chevrolet Detroit, J	Motor Co. (Dept. 20). dich.
Simplified	n: Without obligation on my part, send me the "Owner Operating Record" booklet which enables truck owner perating costs quickly and accurately.
Name	and title
Comp	any

Analysis of 1334 Injuries on Highway Construction

This is the season when highway construction is at its peak. It might be well, therefore, to give some thought to making this highway construction season a safe one, free from all avoidable acci-

Thomas Soule of the Industrial In-demnity Exchange made the following analysis of 1,334 injuries on highway construction, which offers some food for

Explosives
Falls of persons from elevations
Stopping on nails Stationery machinery and Fall of rock Struck by falling objects Caught between objects sery and equipment sirms on the state of the state

The percentages refer only to the number of accidents reported. An analysis prepared by E. N. Goldstine, General Chairman of the Executive Committee of the Construction Section of the Na tional Safety Council gave comparable accident frequency figures. The per-centage of days lost time for rock slides was 35 per cent; for truck accidents, 44 per cent; but only 58 accidents were covered, of which 21 were disabling.

18.0

Ten severe injuries in this latter group resulted in four times as many days lost from work as eleven other disabling in-juries. This would seem that some haz-ards should receive at least four times

as much attention as others.

—From the News Letter of the Const.

of the National Safety Council.

Changes in Territories of A. I. S. C.

Changes in the territories served by the District Engineers of the American Institute of Steel Construction have recently been announced by F. H. Frank-land, Technical Director of the Institute. The following is the list of engineers and the territories they will serve. Mr. Frankland himself represents the Insti-tute in New York City and Washington,

District No. 1-E. N. Adams, 2 Homer St., Worcester, Mass.—Connecticut, Maine, Massachusetts, New Hampshire, New York (except southern portion), Rhode Island, Vermont.

AMERICAN GOPHER



The 1 Yard Model 400 "ON THE JOB"

BACK in 1905, we built the American Ditcher Shovel, the first shovel type machine made. Today, American Gopher Shovels are a complete line of successful shovels, built in sizes ½ yd., ½ yd., 1 yd., 1½ yd.,



AMERICAN HOIST & DERRICK COMPANY ST. PAUL, MINNESOTA

District No. 2—B. F. Hastings, 15 East Wilmot Ave., Llanerch, Upper Darby, Pa.—Alabama, Delaware, Flor-ida, Georgia, Maryland, New Jersey, southeastern New York, North Carolina, Pannsylvania South Carolina, Virginia Pennaylvania, South Carolina, Virginia.

District No. 3—Alexander Miller, 2124 Guarantee Title Bldg., Cleveland, -Indiana (except northern por tion), Kentucky, eastern Louisiana, Michigan, Mississippi, Ohio, north-western Pennsylvania, Tennessee, West


District No. 4—Henry Penn, Room 1443, 53 W. Jackson Blvd., Chicago, Ill.—Illinois, northern Indiana, Iowa, Minnesota, Montana, North Dakota, South Dakota, Wisconsin.

District No. 5—Jack Singleton, 640 New England Bldg., Topeka, Kans.— Arkansas, Colorado, Kansas, western Louisiana, Nebraska, Missouri, New Mexico, Oklahoma, Texas, Wyoming.

District No. 6-W. E. Emmett, Russ Bldg., San Francisco, Calif.— Arizona, California, Idaho, Nevada, Oregon, Utah, Washington.



Is it really GOLD



in Michigan

In addition to roller bearing jaw and roll crushers, the 1935 DIAMOND Crushing and Screening Plant has anti-friction bearings throughout, all babbit bearings having been eliminated. This is a further step in producing a crushing and screening plant to operate at the absolute minimum cost.

Write for illustrated folder describing the many superior features of DIAMOND Crushing and Screening Plants.



piece of gold on one section of the frontier. It was a gold headed cane. It belonged to an early settler who had brought it the hundreds of weary miles separating him from New York. Upon the resemblance of of new found metal to this cane head, claims were staked, fortunes made or lost.

The great expanse of roadless America made it impossible for even those sturdy pioneers to return with their precious finds to determine whether they were digging precious gold or worthless "fools' gold."

Today great highways bring these far flung frontiers within quick and easy access. Diamond road building equipment has

contributed greatly to this important phase



ESTABLISHED-1880

Iron Works, Inc. MINNEAPOLIS, MINN. U.S.A.

with

chute ha

the back concretiz down th dryness, concrete. start wo progress as pour stopped, feet of s puddlers orms ar started 1 the conc der the the finis Cu

One n piles of placed t edging l bags wer dle read the time so that twice as single th possible ing and kept we different The bur a minim

the mo crew of with de permitti 2,000 fe nhead o length each da



A 3-Foot Widening Strip Ready for Pouring

Texas Road Widened with Truck Mixers

(Continued from page 8)

chute had been placed on its pivot at the back of the truck. One man of the concreting crew regulated the flow from the drum, two were required to push it down the chute because of its relative dryness, two men spread or puddled the concrete, and one finisher was ready to concrete, and one finisher was ready to start work as soon as the material had progressed far enough ahead. As soon as pouring from one truck mixer stopped, and one load poured about 22 feet of strip, two of the concrete crew went back on the longitudinal float, the puddlers began spading against the forms and the old slab, and the finisher started his important function. After started his important function. After the concrete had been straight-edged under the direction of the State Inspector the finisher was permitted to edge it against the forms

Curing and Pulling Forms

One man was responsible for the entire curing operation. He wet down piles of burlap rice bags and then placed them on the strip as soon as the edging had been completed. The rice bags were about the proper size to handle readily, were particularly cheap at the time, and were of double thickness so that they held the water more than twice as long as the regulation weight single thickness of burlap, so that it was possible to use the same man for placing and sprinkling the burlap. It was kept wet day and night, there being a different operator for the night shift. The burlap was left on the concrete for a minimum of 72 hours.

The forms were regularly stripped the morning following pouring. A crew of eight men handled this work with definite duties assigned to each, permitting the rapid handling of the 2,000 feet of forms that had to be kept ahead of the pouring because of the length of strip that could be poured each day. The crew split up into sections with two men unlatching the forms, pulling the pins and dropping

overy state. A quality line priced right. BHUREDRY and FULTEX Tarpaulies. Fulton Bag & Cotton Mills

them on the pavement; then two other men set up the forms on the pavement, leaving the edge of the strip exposed for inspection. Two other men started at once loading the forms on the Chev-rolet utility truck for hauling ahead, while the remaining members of the crew began backfilling against the edge of the strip. As soon as each other pair of the strip. As soon as each other pair completed their work they too assisted in the backfilling.

Shoulders

The shoulders were formed from the material excavated from the old shoulders to permit pouring the widening strip. As sufficient material could not be secured in this manner for the 5-foot shoulders graded to a 2 to 1 slope, a large amount of overhaul was necessary from the eastern end of the project where banks on either side of the old pavement produced an excess of excavated material.

The contractor worked two complete crews, dividing the week with one outfit working 10 hours a day for Monday, Tuesday and Wednesday and the second crew completing the week.

Personnel

This contract which was started on July 9, 1934 was completed by August 15. For the contractor, Broussard-Warfield Co., Beaumont, Texas, M. E. Mills, Jr., was Engineer and Superintendent, W. E. Suter was Resident Engineer for the Texas State Highway Department and Edward C. Jancik was Inspector.

Highway Lighting Systems In Europe Reduce Glare

Europe has set an example in raising the center of its highway lights to 25 feet. Ease of accessibility seems willingly sacrificed for improved uniformity of illumination and greatly reduced glare, according to Samuel G. Hibben, Director of Applied Lighting, Westinghouse Lamp Co.

One of the latest European inter-city highways employs light sources at a height of 30 feet, center suspension, on catenary cable supported above the center-line of the roadway. Other typical cases of the new installations, and exemplifying the radical improvements,

exemplifying the radical improvem is the placement along highways of light sources that tend toward average sizes at relatively closer spacings, instead of uncomfortably brilliant sources at such

wide spacings that the ratio of height to distance would be on the order of 1 to 10. As a matter of fact, ratios of 1 to 2 are being studied, and 1 to 5 are not at all uncommon.

One of the newer suburban installations of high-intensity mercury vapor lamps in a large European capital employs 275-watt sources spaced 225 feet apart but staggered on both sides of a 50-foot roadway. Other studies are being made of a 300-foot spacing of concrete poles, these extending 42 feet above ground, and with such uniform distribution of light on the road or or night driving speeds may equal or ex-ceed those of the daytime and with ap-

parently as good visibility.

Readers may secure copies of a fourpage reprint on European Highway Lighting by writing direct to the West-inghouse Lamp Co., Bloomfield, N.J.



A Complete Range of Sizes—2" to 8"—Sized and powered for every pumping job

THE MOST FOOT GALLONS PER HOUR -PER DOLLAR OF COST-FOR PUMP—FUEL—LUBRICATION AND LABOR



SIZE FOR SIZE POWER FOR POWER LIFT FOR LIFT



Send for full information

AIN BELT COMPAN

Bidg., New York, N. Y. Southern Divisi West Coast Division: 909 Harrison St., San Fr



1000-Gallon Kinney Distributor Mounted on Ford-Warford Truck

*2. Kinney Distributors load, get to the job, and apply faster!

This means more work with the same labor cost; more contracts per season; lower demurrage charges; and the lower operating costs allow you to quote prices which get se contracts.

- . The Kinney jacketed pump easily handles sluggish materials within approximately 30° F, of their melting point or at temperatures up to 450° F., providing a pumping unit suitable for loading bitumen or applying it under pressure.
- Kinneys get to the job faster from the source of supply because their larger pump capacity makes it unnecessary to gear down the truck to meet application requirements. Thus a Kinney, with its 400 G.P.M. pump, can operate 400/300ths or one and a third times as fast as a distributor with a 300 gallon pump!

pump!
The difference means 40-mile-an-hour trucks instead of 30more pay loads per day—and that means more profit!

c. Kinneys will apply 2.5 gallons per square yard to a 20-ft, wide road at one application at a speed of 0.8 miles per hour —or any quantity from 0.1 to 3.0 gallons per square yard at

#One of 7 reasons why Kinneys help you make more profit. Others are given in Bulletin A-1935, address

3531 Washington St.

Boston, Mass.

W YORK CHICAGO Church St. 1262 Buskingham Bidg. PHILADELPHIA 725 Commercial Trust Bidg. 13

KANSAS CITY, SI7 Finance Blds LOS ANGELES

Surface Types on PWA Projects

The character of improvements on Federal Public Works projects covers the entire range of surface types. The wide variety of types of roadways built with Federal Aid and their proper relation to the formula requirements is particular. tion to traffic requirements is particu-larly noticeable in the classification of surface types included in the public

works program.

The improvements planned on 25,479 miles of highways and streets in projects approved to September 1934 are classified by types as follows:

Typo Miles 5,609 Low typo, and clay, gravel, macadam, low-cost bit. mixes High typo, bituminous macadam, puriland coment concrets, brick 5,647 85.1 22.9 100.0 25,479

The variation of these percentages in these three groups of types shows the reasonableness of the adjustment of the improvements to traffic needs.

In the case of projects for improve-ents on extensions of the Federal-Aid ments on extensions of the Federal-Aid highway system into and through municipalities 68.5 per cent of the mileage has been planned to have high-type surfacing, 24.2 per cent low-type surfacing and 7.3 per cent is being graded for later surfacing. In contrast the improvements on secondary or feeder roads call for only 11.6 per cent of high-type pavements, 64.2 per cent of low-type surfaces and 24.2 per cent of grading preliminary to surfacing.

low-type surfaces and 24.2 per cent of grading preliminary to surfacing.

The improvements on rural sections of the Federal-Aid system outside the corporate limits of municipalities are largely of lower type than the municipal projects and of higher type than the secondary road projects. In this classification high-type pavements are 52.7 per cent of the total, low-type surfaces 24.7 per cent and the grading projects, 22.6 per cent.

Prem a paper by C. N. Conner, Sonior Highway Design

From a paper by C. N. Conner, Senior Highway Design Engineer, U. S. B. P. R., presented before the American Road Builders' Association.

Improved Bucket Elevators Described in New Catalog

Catalog No. 565 of 112 pages, covering a broad field of elevator requirements, has recently been issued by Jeffrey Manufacturing Co., Columbus, Ohio. The first chapter of the book is devoted to the fundamentals of design devoted to the fundamentals of design, application and operation and contains many helpful suggestions for selecting



DERRICKS

REVOLVERS

BLOCKS

HEAVES

LE

RIVERS

OCOMOTIVE

NEW 1/2 YARD, Model 390 For greater line pulls, larger capacities, faster speed, less weight, and low operating costs, we invite investigation and comparison

Send for new roto pub-lication, "American Gopher Shovels" Illus-trated, showing action pictures "on the job."

PAMERICAN HOIST & DERRICK CO. ST. PAUL, MINN.


the type of elevator best suited to the


requirements of the job.

The catalog also includes information on the increased number of vertical-space type centrifugal discharge elevators with the buckets mounted on chain or belt, and a line of heavy-duty continuous bucket elevators in casings.

These elevators are equipped with new short heavy rigid pillow blocks for shafting bearings, and are furnished with cut gears in place of large cast tooth gears. Head sections are designed more rigid and compact, with bearing supports where they do the most good. Redesigns include a new Universal boot applicable to any type of Jeffrey elevator, which gives flexibility in the vertical location of the feed spout. With it, the pit depth may be kept to a minimum when handling free-flowing materials.

Copies of this new catalog are available gratis to readers of this magazine





on highway and street projects, smoothing the path for traffic-handling tons of dirt and rock

-literally moving mountains.

For Hercules Engines are standard on many of America's leading makes of road building machinery and contractors equipment. There is no type of modern heavy-duty machinery

For over twenty years Hercules has specialized in the designing and building of internal combustion engines for the world's foremost manufacturers of all types of powered equipment.

And that long experience is reflected in the efficiency, economy and reliability of every engine and power unit Hercules builds today.

HERCULES MOTORS CORPORATION, CANTON, OHIO America's Foremost Engine Manufacturer . Power Plants from 4 to 200 H. P

Dred to W

ide and

ions so me-half ection of two secti nek cut for the fir remainde The next four strip way, also 8 feet 6 3 x 10 p inches sp to get a l inch tim whole co greater i 4 feet lo ongitudi the upri ection v the same cept that

slope. The b

about on consisted and ther boat and

The F

The p feet lon cylinder by a new of the tr bulged and wea 8 inches the pont cross sec slipped held fire clamps of built up correspo pipe itse the thick to the he steel spi

SA FIN

bulge on deal of

Ma

THE V

Dredge Pumped Fill to Widen Highway

(Continued from page 2)

S

wide and were built in two 10-foot sections so that traffic could be put over ane-half the road and work done on the section of pipe on the other side. These two sections were built of 7 x 10-inch stock cut down wedge-shaped to 1 x 10 for the first timber and similarly for the remainder to form a ramp of low grade. The next section on either side had four stringers for one-half of the roadway, also cut wedge-shaped and were 8 feet 6 inches long. These carried 3 x 10 planking laid crosswise with 2 inches space between to make the section lighter and to give the men a place to get a hold on the section for moving. This section was carried on a 3 x 14-inch timber at the center so that the whole could be bolted together to give greater solidarity. The next two sections, one on either side, were 3 x 14's 4 feet long with the top planks running longitudinally and with 2 x 4's under the uprights at the center edge to take care of the pipe diameter. The center section was also 4 feet long and built the same as the adjacent sections except that it was horizontal and not on a slope.

a stope.

The bridge and pipe line were moved about once in six days. The land crew consisted of about seven men per shift and there were five men on the dredge boat and dredge tender.

The Pontoon Section of the Line

The pontoon sections, measuring 70 feet long, were carried on four steel cylinders or floats and were connected by a new sleeve which eliminated many of the troubles of the old sleeve which bulged out and caused undue friction and wear in the rubber sleeve. About 8 inches back from the end of each of the pontoon pipes a ring, half oval in cross section, 1½-inch x ½ inch wide, was welded and then the rubber sleeve, made by the U. S. Rubber Co., was slipped over the rings and the whole held firmly in place by two bands or clamps on the end of each pipe, one on either side of the ring. The sleeve was built up in steps with the inner section corresponding to the diameter of the pipe itself. The first step was equal to the thickness of the pipe and the second to the height of the welded ring. Close to the outside of the sleeve a precoiled steel spring was imbedded to prevent the flexible sleeve from bulging. The bulge on the old sleeves caused a great deal of turbulance and loss of head with the consequent wear on both the sleeve and the end of the pipe. The

SAVE CRANE TIME! FINISH JOBS FASTER! Make MORE Profit!

Ye a real conception of hat digains you should not the Williams "Champier" Power-Arm Bucket he act to ni Exchaire undination of lower and Much-and-inakis assured Supr-power . . And shorter cable overhead outs time between buckettuis.



We also build Williams Multiple-Rope Buckets and Dragline Buckets. May we send you builetims?

THE WELLMAN ENGINEERING CO.

WILLIAMS



. & E. M. Photo

New Rubber Sleeve for Pontoon Line

pontoons were 36 inches in diameter and varied from 14 to 20 feet long. The Dredge Manatee

The new dredge Manatee, built from designs of R. C. Pierce, Assoc. Mem., Am. Soc. C. E., and Vice President and Treasurer of the company, has an overall length of 120 feet, is 7 feet 7 inches in depth and has a beam of 34 feet. The design and operation of the Manatee will be described in detail in

the June issue of this magazine.

Shifts and Labor Organization

The work of dredging was carried on 24 hours a day for 6 days a week, using Sundays for adjustments and repairs. The shifts worked from 7 A.M. to 3 P.M., from 3 P.M. to 11 P.M. and from 11 P.M. to 7 A.M. The week was split in the middle to comply with the 30-hour a week requirement for NRH work. The engineers and operators were exempt and were permitted to work 40 hours a week. One extra operator was carried who was also an engineer and he took up the split shifts.

engineer and he took up the split shifts.


The operating crew for the dredge was as follows for each shift: one operator, one tug boat captain, one deck mate who moved the anchors and cared for the pontoon line, two deck hands, one shift engineer and one oiler.

Personnel

This contract for 2,200,000 cubic yards of material in place in the highway fill was awarded to Wilbanks & Pierce, Inc., of New Orleans, La., for 14.40 cents per cubic yard. The owners, J. R. Wilbanks and R. C. Pierce, were frequently on the work which was in general charge of H. W. Nugent as General Manager for Wilbanks & Pierce, Inc., and in direct charge of R. R. Runck as Superintendent, with Capt. D. E. Chalker in command of the dredge Manatee. For the Louisiana Highway Commission, W. C. Youngs was Resident Engineer.



R. R. Runck, Supt., and Captain D. E. Chalker.



THE SHOW-DOWN

New records for economy and dependability, a new basis for the estimating of power costs—the performance of thousands of "Caterpillar" Diesel Tractors on hundreds of operations is making engineers and contractors sit up and take notice. Your dealer can show you complete, comparative figures on "Caterpillar" Diesels now at work, and let you put one to the test yourself. Caterpillar Tractor Co., Peorla, Illinois, U. S. A.

CATERPILLAR PER DIESEL

Fighting the Dust Hazard

Gravel, cinder, slag and stone roads are dusty in dry weather unless treated with a dust palliative. Dust is not alone dangerous to traffic trying to drive through it, but it is also a nuisance and a detriment to the health of the people living along the roads.

The laying of dust is accomplished by either the application of calcium chloride to the surface or treatment of the surface with a bituminous material. The former method is much cheaper but gives only temporary results. Because of the cost there have been no attempts made to lay the dust on all roads. Some very satisfactory results have been secured in Wayne County, (Detroit) Mich. by the application of several chloride treatments during the summer in front of dwellings through residential sections.

Approximately 7 miles of the more important gravel roads were given a bituminous treatment this past season in Detroit with very satisfactory results.

This treatment consisted of a 3-inch surface of a mixture of gravel and asphaltic oil. It was mixed and laid out on the road with graders, providing a smooth, dustless surface for traffic.

From the Twenty-Eighth Annual Report, Board of County Road Commissioners, Fayne County (Detroit), Mich.

Promotions at du Pont

John W. McCoy, General Manager of the Explosives Department of the du Pont Company, has been elected a member of the company's Board of Directors, and has also been made a Vice Preident and member of the Executive Committee. Mr. McCoy has been connected with the company since 1902. Since that time he has served continuously in a number of the company's plant in various parts of the country, in addition to a tour of duty in Mexico.

in various parts of the country, in addition to a tour of duty in Mexico.

Edward B. Yancey, who joined the du Pont organization twenty-seven year ago, succeeds McCoy as General Manager of the Explosives Department. It has been Assistant General Manager



Samuel C. Jacka, City Engineer of Lansing, is supervising the program that is making his city one of the best paved in the State of Michigan. A view of the State Capitol is shown above.

Well Paved... Economically

Look at

LANSING!

Lansing, Michigan, has been, and still is, building a reputation for well-paved streets. Selection of Plant Mixed Liquid Asphalt and Gravel as the material used on a major portion of this work speaks highly for the diligent economy of Lansing officials. This work has been carried forward for the past four years.

Blacked-in streets on the map above show the places in which Standard Asphalt Road Oil has been used since 1930—275,000 yards.

Stanolind Asphalt Products provide correct materials for every type of traffic demand. You'll find it pays to call in the Standard Oil representative on every paving job.

STANDARD OIL COMPANY (Indiana)
910 South Michigan Avenue, Chicago, Ill.

Copr. 1935, Standard Oil Co.



ASPHALT for every Purpose

Sphalt for paving... asphalt

of wor paid sk labor. Whe shall b enterpr

High

for

The are bas of \$800,000 For hig portion. The appropulation in the approp

llinois
adiana
owa
adiana
owa
(anana
(anana)
(ananana
(anana)
(ana

Maint Differ

"Main Stabilize bulletin Chloride compani of the p describes from us volved in value fruito consistics of Copies

Chloride Detroit, l Blanch Sales

Frank ager of S for Clim joined to Peoria, Il Sales De wide exp

Highway Program for 1935 Assured

ned th

en yean al Man-ent. He Manager

(Continued from page 1)

to predetermine for each state the hours paid skilled, intermediate and unskilled

Whenever practicable, full advantage shall be taken of the facilities of private nterprise (contract system).

The Act also continues the penalty clause for states diverting motor vehicle and gasoline taxes.

Apportionment of Funds

The allotments to states given below are based upon the total appropriation of \$800,000,000 authorized by the Act, with \$500,000,000 for roads and \$300,-000,000 for grade crossing elimination. For highways, roads and streets, the apportionment is based seven-eights on federal Aid and one-eighth on population. For grade crossing elimination, the apportionment is based one-half on population, one-quarter on miles of F-A highway system and one-quarter on miles of railroad.

BASIS OF APPORTIONMENT
Highway Grade
Roads Grossing

	Roads	Grossing	
STATE	Streets	Elimination	TOTAL
Alabama	10,645,000	\$ 6,219,000	\$ 16,864,000
Arisona	6,590,000	1,956,000	8,546,000
Arkansas	8,595,000	5,493,000	14,088,000
California	19,865,000	11,382,000	31,247,000
Colorado	8,710,000	4,086,000	12,796,000
Connecticut	3,640,000	2,622,000	6,262,000
Delaware	2.310,000	663,000	2,973,000
Florida	6,660,000	4,350,000	11,010,000
Georgia	12,795,000	7,566,000	20,361,000
Idaho	5,700,000	2.610,000	8.310,000
Illinois	22,290,000	15,780,000	38,070,000
Indiana	12,670,000	7,872,000	20,542,000
love	12,890,000	8.595,000	21,395,000
	12,805,000	7,932,000	20,737,000
Kansas	9,555,000	5,682,000	15,237,000
Kentucky	7,410,000	4,950,000	12,360,000
Louisiana			
Maine	4.300,000	2,202,000	6,502,000
Maryland	4,490,000	3,210,000	7,700,000
Massachusetts	8,365,000	6,330,000	14,695,000
Michigan	16,160,000	10,146,000	26,306,000
Minnesota	13,530,000	8,280,000	21,810,000
Mississippi	8,865,000	5,025,000	13,890,000
Missouri	15,415,000	9,492,000	24,907,000
Montana	9,425,000	4,284,000	13,709,000
Nebraska	9,925,000	5,556,000	15,481,000
Nevada	5,750,000	1,371,000	7,121,000
New Hampshire	2,425,000	1,272,000	3,697,000
New Jersey	8,020,000	6,114,000	14,134,000
New Mexico	7,365,000	2,742,000	10,107,000
New York	28,325,000	20,790,000	49,115,000
North Carolina	12,105,000	7,470,000	19,575,000
North Dakota	7.350,000	5,106,000	12,456,000
Ohio	19,670,000	12,840,000	32,510,000
Oklahoma	11,745,000	7,149,000	18,894,000
Oregon	7,790,000	3,633,000	11,423,000
Pennsylvania	23,965,000	17,703,000	41,668,000
Rhode Island	2,535,000	1,077,000	3,612,000
South Carolina	6,930,000	4,530,000	11,460,000
South Dakota	7,630,000	4,392,000	12,022,000
Tennessee	10,750,000	5,829,000	16,579,000
Texas	30,740,000	16,773,000	47,513,000
Utah	5,305,000	1,923,000	7,228,000
Vermont	2,370,000	1,128,000	3,498,000
Virginia	9,365,000	5,817,000	15,182,000
Washington	7,760,000	4,707,000	12,467,000
West Virginia	5,720,000	4,125,000	9,845,000
Wisconsin	12,370,000	7,734,000	20,104,000
Wyoming	5,690,000	2.178,000	7.868,000
Diet. of Col	2,435,000	603,000	3,038,000
Hawaii	2,375,000	711,000	3,986,000
TOTAL	500,000,000	\$300,000,000	\$800,000,000

Maintenance Methods Differ for Stabilized Roads


"Maintainence of Calcium Chloride Stabilized Roads" is the title of a new bulletin recently issued by the Calcium Chloride Association and its member companies. Designed for the guidance of the practical engineer, this bulletin describes the procedure as differing from usual maintenance methods inm usual maintenance methods inolved in obtaining the highest service value from stabilized surfaces, taking nto consideration the special character-

stics of this type of surface.

Copies of this Bulletin No. 18 may
be secured gratis from the Calcium
Chloride Association, Penobscot Bldg., etroit, Mich.

Blanchard Joins Caterpillar Sales Force

Frank E. Blanchard, formerly Maner of Sales in the southeastern states or Climax Engineering Co., recently oined the Caterpillar Tractor Co., Peoria, Ill., as a member of the Special sales Department. Blanchard has had ride experience in engine sales and agineering fields.



The New Huber Grades

New Motor Grader Has Several Features

Among the features of the new Huber motor grader, recently announced by the Huber Manufacturing Co., Marion, Ohio, is the mounting of the engine. In-stead of the conventional design with

tractor mounted in the rear, the new Huber Superior No. 4 has the engine mounted toward the front of the frame, the power being transmitted to the rear axle assembly through a shaft, similar to the method employed in heavy truck construction. Instead of drawing the blade by drawbars attached to the front of the frame, the blade is pushed, bull-

dozer style, by a heavy tube attached direct to the rear axle housing.

The blade may be used in any position, right or left, from straight across to horizontal with the frame. It will ditch on either right or left side without changing the position of the blade on the hangers. It has a side shift of 36 inches and a blade clearance of about 18 inches when fully raised.

18 inches when fully raised.
Other features of this new roller are Other features of this new roller are a heavy-duty six-cylinder engine; a folding scarifier which, when raised, automatically folds up completely out of the way of all grader operations; dual steering, with hand or power instantly interchangeable; differential lock by means of pressure on a foot pedal; and direct-connected hydraulic control.


The manufacturer states that tests of this new-type grader have been so satisfactory that all previous models will be discontinued. The Superior No. 4 is now available in the 12,000-pound class but both smaller and larger sizes are being developed.

"We need this shovel's speed!"

* says the Workman

JUSH is the order when repairs are made on Rush is the Older beneath the busy traffic of Fifth Avenue and 52d Street. So to Thomas Burke, workman, who was using Wood's new Closed-Back Shovel on this rush job, Wood investigators put this question: "How do you like this improved shovel?"

"We need this shovel's speed!" said Thomas



Under actual working conditions Burke quickly discovered how the resiliency, better balance, lightness and strength of Wood's new CLOSED-BACK Shovels helped him to finish his tough job quickly. Buyers note the reasons for this efficiency, appreciate other advantages:

- 1. The Closed-Back Shovel combines stress-defying one-piece design, the unrivaled strength of the heat-treated shank, and an absolutely smooth back. No strap welds to pull loose.
- 2. The Turned Shoulder strengthens blade, saves shoes, makes shoveling easier.
- 3. The Tapered Socket gives strength and solidity where handle joins blade, fits the hand better.
- 4. Heat Treating makes the high-grade steels in Wood's "Moly," Big Fist, Wood and Stuart grades hard, to resist wear and last longer.
- 5. Reduced Inventory: The CLOSED-BACK Shovel OB SHOVEL AND TOOK supersedes strap weld, solid shank, CLOSED BACK and hollow-back shovels, makes it possible to cut your shovel inventory.

Buyers Beware: Wood's Engineers invented the CLOSED - BACK Shovel, developed the special welding process which fastens the CLOSED-BACK strip permanently without decarbonizing and weakening the blade. This is an exclusive Wood process, used on no other shovel.

Address The Wood Shovel and Tool Co., Piqua, O., U.S.A.



Prolonging the Life of Conveyor Belts

From the Chief Engineer's Desk of the Link-Belt News comes some helpful suggestions for the care of conveyor belts in order to prolong their life. These we are glad to pass on.

Belt Most Expensive Part

The belt is the most expensive part of a belt conveyor and should, therefore, be protected against injury and wear. If a belt is allowed to run improperly trained, its life will be greatly shortened and even the highest grade belt will be a disappointment. Conveyor belts usually run true for long periods, once they are properly trained.

When a belt runs out of line, the

When a belt runs out of line, the cause should be found and corrected immediately. Unless the belt runs true on the carrying and return idlers, the edges will wear off against the frames or other obstructions, the bottom of the belt is liable to injury by riding on the edges of the troughing idlers and in addition, the material will spill.

Conveyor belts should be trained while empty, and if they run out of line when loaded, it is probably due to uncentral or side loading. Correction of the loading chute is the preferable

Variations Caused by Material

Variations in wind pressure sidewise of the conveyor, or in the volume, sizes, percentage of lumps, and moisture con-tent of the materials fed to the belt at tent of the materials fed to the belt at different times may make it impossible to keep the loaded belt in alignment by means of either the supporting idlers or alterations to the loading chute. When varying materials cause the belt to be loaded more heavily on one side of its center line, the heavily loaded side seeks a lower level, thereby crowding the belt off-center with the idlers. Pivoted self-aligning idlers should be used for cor-recting these conditions. recting these conditions.

Belts can not be made to run true by adjustment of take-up screws, or of the head pulley. Both head and tail pulleys should be set in alignment and kept so.
All other training should be done by
the idlers, or if possible, by correction
of the loading chute.

Idlers at Work

The center roll of the troughing idlers must be in contact with the belt, for they steer or train the belt, unless the belt is over-plied or too stiff to assume the shape of the idlers when empty, and thus fails to make contact with the center roll.

Idlers should be kept square with the belt, and when training the belt by lining up the idlers, always work with the direction of belt travel. Stuck or sluggish idler rolls always tend to de-flect the belt and cause unnecessary wear. Foundation or conveyor supports may be responsible for bad alignment

TRY THIS HOBART WELDER FOR 30 DAYS—AT OUR RISK

of belts, if not secure and rigid.

It is a mistake to try to train a belt by increasing the tension. This not only strains the driving mechanism but increases the horsepower requirements, puts an unnecessary stress on the belt, weakens the splice, reduces the troughing of the belt, and thus prevents the effective training action of the center

Trippers should be inspected regu-larly, to see that the belts do not scrape against the frame, and that the belt runs true over the pulleys of the tripper.

Self-Aligning Idlers

Self-aligning idlers resemble stationary idlers, except that they are pivotally mounted and swivel automatically when the belt is misaligned, thereby leading the belt and maintaining it central with the supporting idlers. These should not be used, however, while training a belt. Self-aligning, idlers correct misalign. Self-aligning idlers correct misalignment without harming the belt, thus saving the wear and tear which naturally follows continuous misalignment.

CRUSHERS UNIVERSAL

The Oldest Overhead Eccentric Type Crusher on the Market. Around It Are Built Many Combinations for Stone and Gravel



ward Plants similar to this are contributing mu

Modern crushing equipments demand sturdy and dependable machinery that will produce larger quantities of stone and gravel speedily and economically. THE OLD RELIABLE UNIVERSAL CRUSHER is the heart of more than fifty combination with capacities up to 1500 tons in ten hours depending on the amount of oversize. Write for details.

UNIVERSAL CRUSHER COMPANY

620 C Ave., West Cedar Rapids, Iowa



Pavin Witl

tal of 98 uding Su La

The 6-in the dirt inch rai chine to the 5-inch a 3-inch h material w sheet met it to the g ters for each rakers wor shift. The or straight faithfully, moothly One man j leveled or dumped th nd a up and a strips of forms for chine with run on, tl foreman.

Two Bu ers, an 8-1 gas roller, roller was of 1.500 top per plant was e outpu ns was however, 12 hours.

The sho operations orms we ity to the the should with grass

The co Sam E. whom F. For the A. V. A. Bat

Test fo

A conte ractors v earth mo DeWitt C or of Ki Three in the tes

diesels ar motor. C by the comonth's tractor, p er, cost coops w

MALL

Paving 6.97 Miles With Sand Asphalt

(Continued from page 26)

to use only 58 working days out of a total of 98 possible working days, excluding Sundays.

Laying the Hot Mix

The 6-inch forms were set 1½ inches in the dirt for bearing so that with the ½ inch rail set on top for the finishing machine to run on there was space for the 5-inch sand asphalt pavement with a 3-inch base and a 2-inch top. The material was dumped on a 10 x 12-foot sheet metal dumping board pulled shead by the trucks and shoveled from it to the grade. There were eight cuters for each shift who alternated on the loads with four for a load. The four rakers worked all the time during the shift. Then there was one back-surface or straight-edge man who did his work faithfully, for the pavement rode smoothly at 30 or 60 miles per hour. One man just ahead of the asphalt crew leveled off the subgrade, one man dumped the asphalt trucks as they came up and attached the dumping board, and there was a rail boy placing the strips of ½-inch metal on top of the forms for the Lakewood finishing machine with a special strike-off blade to run on, the machine operator and the foreman.

Two Buffalo-Springfield tandem rollers, an 8-ton steam roller and a 10-ton gas roller, rolled base and the subgrade roller was taken back when top was being run. This crew laid an average of 1,500 feet of base or 1,700 feet of top per 12-hour working day. The plant was rated as 500 tons but its average output under Alabama specifications was about 300 tons a day. It did, however, run as high as 420 tons in 12 hours.

Shoulders

The shoulders were dressed from the material cored out from the grading operations by the blade grader. The forms were left in place to give stability to the edge of the pavement until the shoulders had had time to solidify with grass.

Personnel

The contractor for this work was Sam E. Finley of Atlanta, Ga., for whom F. E. Bird was Superintendent. For the Alabama Highway Department V. A. Bates was Resident Engineer.

Test for Fuel Economy

A contest between gasoline and diesel tractors was recently held on a heavy-earth moving contract of the Porter-DeWitt Construction Co., road contractor of Kirkwood Mo.

tor of Kirkwood, Mo.

Three Caterpillar tractors were used in the test, two of them equipped with diesels and one powered by a gasoline motor. Costs records were closely kept by the owners and during a typical month's operation, the 60-hp gasoline tractor, pulling a blade scraper or scarifier, cost \$104.75 in gasoline. The two diesels of 83 and 56 hp, pulling heavy scoops with a combined capacity of 15

CONCRETE

LECTRIC MOTOR OR GASOLINE ENGINE DRIVEN

WRITE FOR CATALOG

MALL TOOL COMPANY

CHICAGO, ILLINOIS

yards, consumed low-priced fuel costing only \$128.82, this amount being for both tractors.

Inasmuch as some variation in the numbers of hours existed, the contractor analyzed the per hour cost. For the gasoline tractor, this cost was 61 cents and for the diesels, 16 cents.

gasoline tractor, this cost was 61 cents and for the diesels, 16 cents.

The diesel Seventy-Five consumed 3.72 gallons of fuel oil per hour while loaded with 12 yards of dirt. An average of 95 cubic yards per hour of pay dirt was moved by the outfit for 250 hours. The diesel Fifty, pulling a scraper, used 2½ gallons of fuel oil per hour during 1,570 hours of operation in nine months.

Howes Joins Worthington

As a result of increased activity in its diesel and gas engine lines, Worthington Pump & Machinery Co., Harrison, N. J., has amplified the supervision of business in these lines in its eastern district by creating the Eastern

Oil Power Division under the field management of Ray L. Howes, with headquarters at Worthington's New York City office at 2 Park Avenue.

Howes, who is well-known in the diesel engine field, has for the past 22 years been connected with the diesel

sales division of Fairbanks, Morse & Co.
Through Worthington's field organization in the territories of the district offices of Boston, New York, Philadelphia, Washington and Atlanta, Howes will supervise diesel engine sales in these territories.

Good Roads CHAMPION HEATING KETTLES

Spreaders for

Stone Chips — Cinders — Sand

The "Autograder"

Drawn Graders — Road Drags

Champion & Climax Rock Crushing Equipment



GOOD ROADS MACHINERY CORPORATION

KENNETT SQUARE

PENNSYLVANIA



Constructed 1932 with Standard Priming Oil and R. C. No. 1, Socony Brand; sealed 1934 with Asphalt Emulsion, Socony Brand; Grand Isle, Vt.



Standard Asphalt Road Oils
Standard Asphalt Joint Fillers
Standard Waterproofing Asphalt
Standard Cut-Back Surfacing Asphalt
Standard Asphalt Binder A for surface treatment
Standard Refined Asphalt for sheet asphalt paving
Standard Cold Patch Asphalt for all types of patchin

Standard Cold Patch Asphalt for all types of patching Standard Asphalt Binders B & C for penetration work (Asphalt Macadam)

Standard Paving Asphalt 51-60 and 61-70 Penetration for the mixing method (Asphaltic Concrete)

Standard Asphalt Emulsion for Surface Treatment, Penetration, Road and Plant Mix, and Patching

Specifications and all other particulars furnished on request.

SOCONY-VACUUM OIL CO.

INCORPORATED
STANDARD OIL OF NEW YORK DIVISION

Concreting Plant for Apalach. Bridge

(Continued from page 15)

bucket was replaced by a special 22-cubic foot Blaw-Knox bottom-dump oncrete bucket, 14 feet long, with a

roller gate and protection apron.

For unwatering the cofferdams and also for keeping them dry during the construction above the seal the contracconstruction above the seal the contractor used one 10-inch Barnes centrifugal with a 24-hp Hercules engine; one 10-inch Morris centrifugal with a 24-hp Continental engine; one 6-inch centrifugal with a 10-hp motor; one Novo double diaphragm pump with a 2-cylinder engine; and eight Jaeger self-priming pumps with Wisconsin motors.

Yard Equipment

The yard equipment included the following for furnishing form work as needed and also for repairs to other equipment: one Fay & Egan table saw with 7½-hp Fairbanks-Morse engine; one National bolt machine; one standard new divines cutters. ard navy diving outfit; one complete acetylene cutting and welding outfit; one Cameron 5B pump for barge bilge and furnishing water under pressure for washing the cofferdam walls before pouring concrete; one geared pipe threader; and one 2½-inch Typhoon centrifugal pump with a 6-hp Fairbanks-Morse engine on a well for water sup-ply for the steam equipment. There was also a Moon steam turbine, Kohler and Homelite portable lighting plants, and a 100-cubic foot Ingersoll-Rand air compressor. compressor.

Personnel

The contract for the construction of the nine concrete piers of the Apalachicola Bay Bridge was awarded to the Hardaway Contracting Co., of Columbus, Ga., for \$137,336.20. For the contractor, Robert Hardaway, Jr., was Superintendent and for the State Road Department of Florida, E. S. Fraser was Project Engineer. W. S. Gudgell was Resident Engineer-Inspector for the Public Works Administration. The contract for the construction of

New Public Works Dept. Mgr. for Autocar Co.

The Autocar Co., of Ardmore, Pa., manufacturer of heavy-duty trucks, has announced the appointment of E. B. Sinclair as Manager of the Public Works Department, with headquarters at the Autocar Branch in New York City. Sinclair, who previously was con-nected with the Indiana truck organiza-tion and later was in charge of public works sales for Brockway, is well known to state, county and municipal officials throughout the East.

CONSTRUCTION EQUIPMENT

McKIERNAN-TERRY Pile Hammers, Pile Extractors

LAMBERT-NATIONAL Hoists, Derricks, Cableways and Whirlers

STEELE & CONDICT Special Machinery, Movable Bridge Machinery

Write for descriptive catalogs

McKiernan-Terry Corp. 19 Park Row, New York Distributors in Principal Cities

Boye Reelected President of Asphalt Institute

At the annual meeting of the Board of Directors of The Asphalt Institute, representing four-fifths of the major producers of the United States and Canada, B. L. Boye was reelected President. Mr. Boye has been with Socony-Vacuum for 35 years and now heads that company's asphalt and fuel oil activities.

otivities.
Other officers elected were: Vice Presidents, A. M. Maxwell, Standard Oil Co. of Ohio; Leroy M. Law, Shell Petroleum Corp.; J. A. Blood, Standard Oil Co. of California; and T. M. Martin, Lion Oil Refining Co. of Arkansas. W. W. McFarland, President of Warner-Quinlan Co., was reelected Secretary and Herbert Spencer, Standard of New Jersey, was reelected Treasurer. The Board of Directors renamed C. W. Bayliss, Barber Asphalt Co. to be Chairman of the Executive Committee, and elected McFarland, Martin and Blood

Meets copper-bearing pure iron requirements in all accepted specifications for corrugated metal culverts.

as the other committee members, Mr. Boye being a member ex-officio. J. E. Pennybacker continues as Managing

The Institute announced the opening of a regional office in Cincinnati; additional offices are located in Washington, San Francisco, and Kansas City.



GOHI IN EAST NORTH CENTRAL STATES



OHI Corrugated Pipe asks no favors. Wherever installed, Gohi GOHI Corrugated Pipe asks no lavors. Wherever the Corrugated Pipe asks no lavors. Wherever the Pure Iron-Copper Alloy Culverts, measured by any standard of performance, give value in service, dependability and satisfaction, many times beyond their cost.

The ability to withstand the severest abuse and punishment under any and all conditions of traffic, weather, and location is inherent in Gohi, the outstanding culvert metal that is daily writing its records under the highways of every state—records of longevity, wear-, weather- and correspondent from conditions and contract the state of the second se rosion-resistance, freedom from costly upkeep and repairs.

Gohi, the one culvert metal you can depend upon implicitly, is the ac-

cepted standard of quality for all highway drainage use.

Consult the Fabricator Nearest You

Bancroft & Martin Rolling Mill Co S. Portland, Maint
Denver Steel & Iron Works Co Denver, Colo.
Feenaughty Machinery Co Portland, Oregot
St. Paul Corrugating Co St. Paul, Minn
The Newport Culvert Co Newport, Ky.
New England Bolt Co Everett, Mass
Tennison Brothers Texarkana, Ark
Central Culvert CoOttumwa, Iowa
Capital City Culvert Co Madison, Wis
F. Yeager Bridge & Culvert Works, Port Huron, Mich

PRONOUNCED "GO-HIGH

CULVERT MANUFACTURERS Comple FACE HAN AUTO

Anti-

Reduci

a pro for pla Co., Chic

the way

of the ri

there are slide. T tread is risers at

Thus, which there is skidding. The ri

comforts There a

tired veh


rolls on

lations a and nois damage

When Multigri for comp the entir

> MIX e guard on at b perating MILES

> > Cha M6 Pleas your



R

BOX

9 to with-

NY

H

S

ohi per-

ohi

the cor-

ac-

laine

egon finn

Ку.

fass.

Ark.

lows Wis. lich.

One-Half Actual Size Multigrip Floor Plate

Anti-Skid Floor Plate for Highway Bridges

Reducing skidding on highway bridges is a problem facing every state and county highway department. Multigrip floor plate, developed by Illinois Steel Co., Chicago, Ill., aims to provide maximum skid resistance regardless of the way the plate is laid or the angle from which it is approached. The design of the risers on this plate is such that there are no long surfaces on which to side. The spacing is such that a tire tread is always in contact with several tread is always in contact with several risers at right angles to one another. Thus, whether the plate is wet or dry there is proper resistance to sliding or skidding.

The risers are scientifically distributand are flat on top so that they are comfortable for pedestrians to walk on. There are no gutters in which a thin tired vehicle wheel may catch. A wheel rolls on the risers, not between them.

rolls on the risers, not between them.

When laid directly on old planking,
Multigrip floor plate eliminates the need
for complete reflooring and strengthens
the entire bridge roadway. Such installations are claimed to reduce vibration
and noise under traffic, eliminate the
menace of rising spikes, and prevent
damage to the roadway from anti-skid
chains. Concentrated loads from heavy

CONCRETE EQUIPMENT

Complete line—including:

FACE DOWN BLOCK MACHINES, HAND AND POWER STRIPPERS, AUTOMATIC POWER TAMPERS, OVERHEAD FEEDERS, ELEVATORS AND FEEDERS, MIXERS, CARS AND TRACKS

guarantee our customers a larger produc-at both a lower first cost and a lower rating cost. Write for catalog.

MILES MFG. CO.

JACKSON MICH

Change of Address Slip

Contractors and Engineers Monthly 470 Fourth Ave., New York Please change my address on your records

FROM

TO

trucks are distributed over greater areas, with consequent reduction stresses on the bridge floor.

Skyline Contract at Thornton Gap, Va.

The southerly of the three contracts now under way on the Skyline Drive in Virginia between Front Royal and Thornton Gap was awarded to Albert Bros. Contractors, Inc., of Salem, Va. on its bid of \$304,464.50, for the 9.7on its bid of \$304,464.50, for the 9.7-mile stretch. This firm consists of three brothers, Charles, Archie and Lewis, and L. J. Messemer who is Superintendent and Engineer. The contract calls for the excavating of approximately 300,000 cubic yards.

Included in the equipment for this work are two Lorain shovels, one gasoline-engine driven and the other dieselengine driven. five Euclid crawler

engine driven, five Euclid crawler wagons, two Type 20 I-R portable com-pressors, one Type D I-R wagon drill,

six I-R jackhammers and a Type 40 I-R drill-steel sharpener.

The contract immediately north of this section operated by Sammons-Robertson Co. of Huntington, West Va., was described in the January issue of Contractors and Engineers Monthly. We are indebted to Compressed Air Magazine for the data on the Albert Bros. contract. Bros. contract.

State Highway Buys Sixteen Maintenance Kettles

The North Carolina State Highway and Public Works Commission recent-ly purchased from the E. F. Craven Co., ly purchased from the E. F. Craven Co., equipment distributor, Greensboro, N. C., sixteen Model 84-HD Littleford tar and asphalt heating kettles for use in highway maintenance. These kettles, which are mounted on pneumatic rubber tires for easy portability, are equipped with a hand spraying attachment, making it a complete maintenance unit for shoulder work, penetration surfacing shoulder work, penetration surfacing over small areas, and skin patching.



DETROIT MOTOR


DETROIT HARVESTER CO.



We have developed new and better wire rope for construction work and heavy duty that has heretofore been considered an engineering impossibility. Better ropes than we have ever thought could be made. Let us discuss with you your needs at once for the big contracts let for 1935.

We are in position to furnish quickly every type of conveyor equipment for economical transportation, regardless of the technical problems they must encounter.

Aerial transportation is Real Economy on large undertakings.



Main Office and Works: WILLIAMSPORT, PENNA

Bulletins and Pamphlets

For free distribution to contractors, engineers and officials. Write for the catalogs you need.

Movie Shots Truck Book Free

Since States rates book rree

States book, containing all the details of the 1935 Dodge and many striking photos of the Dodge in service are available free on request to those interested by writing direct to Dodge Div., Chrysler Motors, Dept. CEM-4, Detroit, Mich.

Fast-Acting Clamshell Bucket

352 The Williams Champion power-arm clamshell, a feature of which is the power-arm combination of lever and block-and-tackle, is described in literature which the Wellman Engineering Co., 7012 Central Ave., Cleveland, Ohio will be glad to send on request.

Screeding Black-Top or Concrete Roads

353 Flexible Road Joint Machine Co., Warren, Ohio, will be glad to send to interested contractors and engineers complete information on the Flex-Plane machine which will screed concrete and black-top roads 3 to 50 feet wide as well as install contraction joints in concrete roads.

Three-Cylinder Diesel Tractor

354 Caterpillar Tractor Co., Peoria, Ill., has announced the Caterpillar diesel Forty with a 3-cylinder diesel engine developing 44 horsepower at the drawbar and 49 horsepower on the belt. It will pull a 6 to 8-yard wagon and the frame is drilled for mounting all types of tractor equipment.

Street and Road Equipment

Chas. Hvass & Co., Inc., 508 E. 19th St., New York City, manufacturer of Hvass bituminous distributors, heavy-duty trailers, sand and chip spreaders, sweepers, sprinklers and heating kettles, will be glad to send complete information on any of this street and road equipment to interested contractors and engineers.

Complete Line of Drilling Tools

356 Catalog No. 983, a 49-page booklet describing and illustrating the complete line of Bucyrus-Armstrong drilling and fishing tools to meet the requirements of all kinds of drilling, may be secured free upon request from the Bucyrus-Erie Co., South Milwaukee, Wis.

Contractors' Automatic-Priming Pumps

357 G and R Never-Fail self-priming self-cleaning centrifugal pumping units with 100 percent automatic rapid prime by an en-tirely new method, in a variety of sizes and types, are described and illustrated in litera-ture which the Gorman-Rupp Co., Mansfield, Ohio, will be glad to send on request.

Simplified Arc Welding

358 Copies of the booklet "The Many Profitable Uses of Simplified Arc Welding" as well as a complete description of the Hobart portable welder may be secured free by interested contractors and engineers from Hobart Bros., Box CE-55, Troy, Ohio.

Cableways and Scrapers for Dirt Moving

359 Sauerman Bros., 464 So. Clinton St., Chicago, Ill., will be glad to send to those interested complete information on its slackline cableways for underwater excavation and on Crescent scrapers for long range dirt moving.

TRACTORS and ENGINEERS MONTHLY Please send me the following literature, without cost or obligation (Indicate by numbers)

P.S. also send me catalogs a prices on_

Compressor with Improved Design

360 Gardner-Denver Co., Quincy, Ill., will be glad to send to those interested complete information on its new 6-cylinder two-stage, water-cooled air compressors, the unusual design of which is claimed to provide more delivered air, with a resultant saving in power cost.

New Hand Shovels

Wood Shovel & Tool Co., Piqua, Ohio, will be glad to send to those interested complete information on the new Wood Closed-Back shovel, among the features of which is the exclusive closed-back design.

Cutting and Welding Apparatus

362 The complete line of Milburn cutting and welding apparatus for all types of light and heavy work is described in literature which the Alexander Milburn Co., 1409 W. Baltimore St., Baltimore, Md., will be glad to send on request.

Oil, Tar and Asphalt Distributors

363 Complete literature and prices on any of the Emyre oil, tar and asphalt distributors may be secured by interested contractors and highway department officials from E. D. Etnyre & Co., 400 Jefferson St., Oregon, III.

Trucks for Construction Jobs

364 General Motors Truck Co., Pontiac, Mich., will be glad to send to interested contractors and highway department officials complete information on GMC trucks, including the 47 important features in the design and construction of these trucks.

Complete Line of Road Rollers

365 Buffalo-Springfield road rollers, which are obtainable in sizes from 1½ to 17 tons, three-wheel or tandem, with scarifier and other attachments optional, are described in a catalog which Buffalo-Springfield Roller Co., Springfield, Ohio, will be glad to send on request.

Reliable Digging Buckets

366 Complete information on Hayward buckets which it is claimed will keep the job going ahead on scheduled time may be secured by interested contractors from the Hayward Co., 32-36 Dey St., New York City.

New 1935 Low-Price Trucks

367 Literature describing the new 1935 Fed V-8 truck, which has a number of new and improved features and is available win several body styles, may be secured by one tractors, state and county highway officials from Ford Motor Co., Dearborn, Mich.

Placing Concrete by Vibration

368 Electric Tamper & Equipment Ca.
Ludington, Mich., will be glad to seed to interested contractors and engineers in new literature describing Jackson high frequency concrete birators for the Vibro Cast method of placing concrete in structure, highways, etc.

Heavy-Duty 3/4-Yard Shovel

369 Catalog 52-A describing the Bay-Quy Model 52 heavy-duty %-yard showly which is readily convertible to dragline, craretrench hoe and clamshell services, may be secured by interested contractors from Bay-City Shovels, Bay City, Mich.

Concrete Equipment

370 Miles complete line of concrete equipment is described in literature which the Miles Manufacturing Co., Jackson, Michael will be glad to send to interested contracts on request.

DOWN GO YARDAGE COSTS



WHEN YOU USE Model C lib in trace on Mfg polis, M E OURNEAU **EQUIPMENT**

That's why the contractors on the Jack Rabbit Trail
—1,200,000 cubic yards of roadway excavation—chose
LeTourneau Equipment, 30 units of it.

Precipitous slopes, tough grades as steep as 30% with an average of 11½%, huge fills—one requiring 175,000 cubic yards—cuts up to 185 feet, but LeTourneau Equipment is setting new dirtmoving records there, moving such yardages as this:

Working tandem, six 12-Yard Carryall Scrapers are delivering 65 pay yards per tandem unit per hour on a 4,000-foot round-trip haul.

Lower yardage costs—that's why the contractors on the Broadway Low Level Tunnel, mile-long bore through the hills back of Oakland, California, chose LeTour-neau Equipment. For them 25-Yard Buggies are plac-ing 100 cubic yards per Buggy hour on a 500-foot round-trip haul.

Ask our Engineers for further information—if you will write us, describing your dirtmoving problems, our Engineers will gladly advise you as to what LeTourneau Units are best fitted to your job.

R. G. LeTourneau, Inc.

Peoria, Illinois

Stockton, California

Cable Address: "BOBLETORNO"

Manufacturers of Angledozers, Bulldozers, Buggies, Carryall Scrapers, Derricks, Rooters, Sheep's Foot Rollers, Power Control Units.

LaTourneau Bulldozers (left) bring down big yardages on the Jack Rabbi Trail. Loading the Buggy (below left) is easy—extreme care in spotting is unnecessary. Working tandem (below) takes no more power on the Jack Rabbit Trail, but ups the yardages and cuts the cost.



w-Pric 373 Co

Air Fil

I Co

irt Mon

m Ne

hading j 374 Th in a 68-

376 A 19,000 a washers,

the Wro anverti 377 B hovels, ble in v

378 T or wire

What Yo

Air Filters for Construction Equipment

Complete information on Air-Maze air
filters for the engines of construction
anipment, the use of which increases engine
defency, may be secured by those interested
from the Air-Maze Corp., 812 Huron Road,
Gereland, Ohio.

1935 Feel per of new lable with d by on-ty officials ch.

Bay-Cay rd show ine, crane, may be from Bay-

ete equipure which on, Mich, contracton

t Trail

with 175,-eTour-ecords

rs are

ors on prough eTour-plac-O-foot

s, our

urneau

nc.

fornia

ment Ca, dit to seal dist moving Equipment dist moving equipment, including the carryall scraper, buggies and bulldozers, has been issued by R. G. Le Tourneau, structura, structura, contractors and highway engineers

Law-Priced Trucks

Complete information on Chevrolet low-priced trucks, which are built to handle lasting jobs day after day at small operating ost, may be secured by interested contractors and highway department officials from Chev-rolet Motor Co., Detroit, Mich.

New Signal Torch

The new Storm King signal torch, with a number of new features and imprevements, tests of which show it will burn is a 68-mile gale, is described in literature which the Shanklin Mfg. Co., Springfield, Ill., will be glad to send to contractors and highway engineers on request.

ders for Rock Bits

Ouick-Way grinders for detachable rock bits, which are made in two sizes, Model G of which it is claimed will resharpen its in two to four minutes, are described and illustrated in literature which the C. H. Carlson Mig. Co., 13-15 Main St., N. E., Minnespolis, Minn., will be glad to send on request.

pecial Washers and Stampings

Special Washers and Stampings

A new handbook entitled "Special
Washers and Stampings," listing over
19,000 shapes, sizes and specifications of
vashers, stampings, and related items used in
construction, has recently been brought out by
the Wrought Washer Mfg. Co., 2100 S. Bay
St., Milwaukee, Wis. Copies may be secured
by readers of this magazine direct from the

overtible Shovels, Cranes, Draglines

Bulletin No. 72, describing and illustrating Orton Unit-Cast convertible shovels, draglines and cranes, which are available in various capacities and are built for the heaviest type of excavation and material handling, may be secured by interested contractors from the Orton Crane & Shovel Co., 608 So. Dearborn St., Chicago, Ill.

What You Should Know About Wire Rope

This is the title of a 20-page booklet describing and illustrating the construction and uses of Flex-Set preformed Yellow Strand wire rope. Copies of this hand book for wire rope buyers may be secured by those interested from the Broderick & Bascom Rope Ca, St. Louis, Mo.

Time Locking Device for Asphalt Mixers

Time Locking Device for Asphalt Mixers
379 A new all-mechanical time locking
device for asphalt mixers, which is a
complete self-contained unit mounted on one
side of the mixer and which also locks the
mixer gate valve from the time the aggregate
is introduced to the mixer until the batch is
discharged, is described in Bulletin TL-12
which Hetherington & Berner, Inc., Indianapolis, Ind., will be glad to send on request.

Two-Stage, Air-Cooled Compressors

380 Bulletin 758, issued by Chicago Pneumatic Tool Co., 6 E. 44th St., New York City, describes the new C-P line of two-stage, air-cooled portable compressors with 6-cylinder gasoline engines, or diesel engines if desired, and with various mountings, the whole being designed for greater economy.

Features of New Crushing Plant

381 The Diamond 1935 Model No. 65 portable crushing and screening plant which incorporates all the features of previous models with many additional new refinements is described in literature which Diamond Iron Works, Inc., Minneapolis, Minn., will be glad to send on request.

Truck Operators' Handbook Free

The 1935 "Operators' Handbook" containing information on various kinds on industrial tires, including the factors governing their selection, and a load and service diagram, is available to all those interested in tire performance. Write to the B. F. Goodrich Co., Akron, Ohio.

Electric Equipment for Power Shovels

383 This is the title of a 20-page booklet describing and illustrating G-E electric equipment for power shovels, copies of which may be secured by interested contractors from the General Electric Co., Schenectady, N. Y.

Changes in Personnel of Robert W. Hunt Co.

Robert W. Hunt Co., Engineers, conducting a national and international engineering inspection, testing and consultation service, with general offices in Chicago, has accepted the resignation of C. B. Nolte, President, who has accepted the presidency of the Crane Co. of Chicago.

of Chicago.

James C. Ogden, formerly Vice President in charge of the company's eastern and foreign activities at New York, succeeds Mr. Nolte as President. Mr. Ogden has been actively engaged in the organization for the past thirty-five years and has served in an executive capacity since 1908. F. M. Randlett, Pacific Coast Manager since 1926, will assist Mr. Ogden as Vice President and General Manager.

General Manager.
Robert W. Hunt Co. was organized by Captain Robert W. Hunt and associates in 1888 and has been identified with private and governmental transportation and construction work through-out the world.

Soil Erosion Control

One of the most pertinent and dis-cussed problems today is that of soil erosion, the effects of which are being There are two general types of erosion, sheet erosion and gullying, both of which can be controlled.

JAEGER "SURE PRIME" PUMPS **511500** 135,000 GALS) Extra for Rubber Tires buys this 8500 Gal. "Handy Model" 4





WORTHINGTON ROCK MASTER SPEEDS UP DRILLING

... at any angle ... on every type of job


LIGHT, mobile rig...can be readily moved from place to A place...and taken on any job where you can take a hand drill.

The U-bar, adjustable to any position, in combination with the universal drill seat, assures the desired set-up. Peg legs, adjustable in length and position, assure rigidity.

Equipped with quick and effective Hole Spotter, the rig can be furnished with feeds for 3 ft., 4 ft., or 6 ft., maximum steel change... Recommended for holes up to 20 ft. depth.

Write for literature giving complete details

Ask for a demonstration



WORTHINGTON FUMP AND MACHINERY CORPORATION WORZEMNOTON

Bulletin 1383 of the Austin-Western Road Machinery Co. describes the various methods for preventing soil erosion and the Austin-Western equipment designed for this purpose, including terracers, blade graders, elevating graders, trail builders, rip-rooters, scrapers and plows.

Copies of this 16-page illustrated bulletin may be secured gratis by those interested from the Austin-Western Road Machinery Co., Aurora, Ill.



F-M Model "36" Diesel engine and generator set-light, portable, powerful, efficient

 Electric power for tools and for every construction needwhere you want it, when you want it-that's what the F-M Model "36" Diesel engine-generator unit offers every contractor.

No matter where the job may be -far beneath a city street or along a levee miles from established power facilities—you can now generate your own current for tools, lighting and a hundred other purposes, at a fraction of the cost. Light in weight, readily portable, this simple fool-proof power unit burns low cost fuels with complete Diesel efficiency, furnishing power as you need it without fussing or attention.

F-M Model "36" Diesels perform a wide variety of jobs for builders and contractors. Units for direct drives on earth-handling machinery, pumps and compressors in capacities from 10- to 160-hp. For full information address Fairbanks, Morse & Co., 900 S. Wabash Ave., Chicago, Ill. 32 branches at your service throughout the United States.

FAIRBANKS-MORSE



DIESEL ENGINES

TURNER SUPPLY COMPANY N. W. Corner of St. Louis and Commerce Sts.

MOBILE ALABAMA

Representing

Ther" Air and Electric Tools Drag, Braper, Wheeler Troub Presson, Flosche Buckets and Dragline Buckets BATES—Bar The Wile Repo Domestic—Pumps and Rioists.

M & M Form Chappe WYOMING—Ref 1 E d g e Bissveis, Scoops

LINK-BELT CO.—Crawler Crance, Shovels, London McKIERNAN-TERRY
CORP.—Pile Hammers
INDEPENDENT PN EUMATIC TOOL CO.—
SCRAPER CO.—WheelTher' As and Electric ors. Drags. Scraper.

SHEPHERD TRACTOR & EQUIP. CO.

150 W. Jefferson St. Los Angeles, Calif.

Distributors for

CATERPILLAR-Tractors, Graders and Diesel Power Units
LE TOURNEAU—Carryall Scrapers, Angle Dozers, Bull Dozers, Booters, 25-Yd. Wagons
WILLAMETTE—Holsts and Winches
KILLEFER—Scrapers, Road Discs and Rooters
DAVEY—Air Compressers
ATHEY—Track Wagons and Trues Wheele

"CATERPILLAR" Tyactors, Graders, Power Units, etc.

Gyaders, Power Units, etc.

Higs, Boad Pumps

Buls, Boad Pumps

Bump Vargon, Bullsharers

Bunners

WAIIATA, Ga.

**Conpressors, Tools

Drag Scrapers

Bunners

Bunners

WINSLOW Beales

LITLEFOND Asphalt

Tools, Rettles

MUNDY Hoisting Equip
BUFFALO-SPHINGFIELD

Broad Rollers

WARD Boad Plows

Bulldoners

Bulldon

YANCEY BROTHERS, INC.

634 Whitehall St., SW Atlanta, Ga.

Member: Associated Equipment Distributors

INDIANA EQUIP. CO., INC. 327-329 West Market St., Indiana

Represe Representing
ATHEY TRUSS—Wapons, IN GERSOLL-RAND—
Bullimers Co.—
Comprehens, Tools
Comprehens, Tools
Loaders and Conveyors
BUFALO-SPRINGFIELD
NALO-SPRINGFIELD
NALO-SPRINGFIELD
NAGARA—Vibratis and Crasses
NAGARA—Vibratis and Crasses
NAGARA—Vibratis and Crasses BUFFALO-SPRINGFILE

BORDON

"CATERPILLAR"—Boad
Machinery
"CATERPILLAR"—Tractors

EUCLIO—Wagens, Strapers,
Bulldoors

Bu

Bulkhozers
Bulkhozers
GENERAL—Shovels
and
Cranes

SAUE n
Scrapers
UNIVERSAL—Cruthers,
Pulverisers Member: Associated Equipment Distributors

ARIZONA TRACTOR & EQUIP. CO. 138 So. First Ave.

"CATERPILLAR" Tractors KILLEFER Road Tools
"GATERPILLAR" Road LapLANT-CHOATE Snow Machiners Road Carther Road Scattlers and Scattlers ATHEY Truss Wheels ATHEY Truss Wheels
BUFFALO-SPRINGFIELD
Rollers
CLEVELAND Rock Drills
BUCYRUS-ERIE Shovels

WILLAMETTE-HYSTER Holsts Member: Associated Equipment Distributors SMITH BOOTH USHER CO. Los Angeles, Calif.

2001 Santa Fe Ave. BARBER-GREENE—Ditchers, Excavators, Loaders
CEDAR RAPIDS—Crushers
CLEVELAND—Ora wiler
LIMA—Power Shovels,
LIMA—Power Shovels, CEDAR RAPIDS—Crushers
CLEVELAND—Cre w 1 or
CLEVELAND—Rock Drills
CLYDE—Holists
CASTON—Industrial Cars
FREEMAN—Turchables
GALION—Trackers, Rollers
H O U G H-UNIVERBAL—
WYPRESBURE JENNY—
Cleaners
JAEGER—Mixers, Hoists,
Pumps, Tower Equipment
JEFFHEY—Locconotives, etc., WILLETT—Street Sweepers
JOHNSON—Dins, Batchers

LIMA—Power Revowler, Settler, Street Cranser Revolution, Street Canada Allow Proceedings of the Company of the

Member: Associated Equipment Distributors

F. H. BURLEW COMPANY 221-225 West Huron St., Chicago, Ill. Telephone: SUPerior 5804 Represen

Representing

BARNES—Pumps
BATES—Wire Ties, etc.
BEBBE BROS.—Holsts
INGERSOLI-RAND—Air
Compressors and Tools
JONES-SUPERIOR—Port
able Gas & Elec. Power

Game Superior Superio

LEACH — Concrete Misers Williams Ducksen, LEACH — Concrete Towns and Tower Equipment HRSLEY — Concrete Towers, Chutting, Cranes, Shovels, Cheker Hooks

McKiernan-Terry-Pile Hammors, Extractor, Lambert-Matienel-Hoista, Cableways Steele & Condict-Special Machinery beelbarrous, Concrete Carts, Hose, Cable, Rope, etc., carried in stock

GIERKE-ROBINSON CO. 4th & Ripley Sts. Davenport, Iowa

Representing

BLAW-KNOX.—Steel Road, Curb and Gutter Forms, Bins, Batchers, Clamshell Buckots, Truck Turntables, Ord Concrete Road Finishers CHAIN BELT.—Mixers, Pavers, Pumps, Saw Rigs, Con-verors, Elevators veyors, Elevators
CLYDE—Gasoline and Steam Holsts, Degricks
HOUGH-UNIVERSAL—Sweepers
SULLIVAN—Air Compressors, Tools
TRACKSOM—Crawlers, Shovels and Bulldoners
THEW-LOBAIH—Cranes, Shovels, Draglines
TIMKEN—Detachable Ruck Bits, Steels
UNIVERSAL—Truck Cranes
UNIVERSAL—Truck Cranes
UNIVERSAL—Truck Cranes

NEIL B. McGINNIS CO. 1401 S. Center St. Box 1615 Phoenix, Ariz.

Representing

EDWARD R. BACON CO. Folsom at 17th St. San Francisco

Adnum Black Top Pavers
Baareat Excavators
Bureh Spreaders
Byres Shovels, Cranes
Cleveland Rock Drills
Cleveland Teachors
Debbie Derricks
Erie Tandem Rollers
Erie Tandem Rollers
Horralds Prouch Units
Hyperssure Jenny Cleaners
Hough Sweepers
Houber Road Rollers
Interestate Tramways
Iowa Crushers, Roadouk Pl.
Jaeger Mixers, Hoista, Pumps
Johnson Bins, Batchers
Johnson Gins, Batchers
Johnson Bins, Batchers
Jacks Willed Plows
Lakeweed Road Pinishers,
Ecomy Cleating
Mix (Lakeweed Road Pinishers,
Forms, Cleating
Mix (Lakeweed Road Pi

Member: Associated Equipment Distributors

O. T. CHRISTERSON CO. 122 So. Michigan Ave. Chicago, Ill.

Representing KOEHRING COMPANY—Mixers, Pavers, Crance, Shorel Dumptors, Mud Jacks
KWIK-MIX COMPANY—Cencrete and Bituminous Mix-

C. H. & E. MFG. CO.—Pumps, Saw Rigs, Hoists
GORMAN-RUPP CO.—Self-Priming Centrifugal Pumps
MICHIGAN POWER SHOVEL CO.—Crawler Shovels,
Cranes; Truck Shovels, Cranes; %-yard
PARSONS COMPANY—Trench Machines, Turbo Mixers
LE ROI COMPANY—The Compressors
LITTLEFORD BROS.—Distributors, Tar Kettles, Heaters, Troybe ers, Torches CLEVELAND FORMGRADER CO.—Graders, Scrapers, Rooters, Form Graders, Straight Edges, Finishing

HELTZEL STEEL FORM & IRON CO.—Road Forms,

THOMAS L. BARRET 112-114 So. Second St., Louisville, Kentucky

C, H. & E. Pumps and Contractors Equipment Will. IAMS Clam Shell and Drag Line Buckets and Material Handling Equipment Harmonian Harmoni

RONSTADT HARDWARE & MACHINERY CO.

"Pioneers in Good Merchandising"

TUCSON BROOKVILLE Locomotives STERLING Portable BAY GITY Shovels

GALION Graders and RolPumps

Pomona Turbine

McCORMICK-DEER-ING Diesel and Gas Power Units

REX Concrete Mixers and Puzzes STERLING Hoists

ARIZONA

lers
MCCORMICK-DEERING Industrial and Crawler Tractors
Crawler Tractors

TOLEDO Road

NORRIS K. DAVIS, INC.

Representing

Representing

LE ROI CO.—Gasoline Power Units and Paris

MINN. STL. & MACHY. CO.—Twin City Engines, paris

HANSON CLUTCH & MACHY. CO.—Full Revolving

Shovels, Cranes, Draglines, §, §, and §, yd.

KEYSTONE DRILLER COMPANY—Excavating Machines, Shovels, Cranes, Draglines, Pull-Scoops, Skimmers, Plunger Shovels, Pavement Breakers

DAVIS COMPANY—Large Tilting Mizers, 1, 2, 2, and

4-yd. Welsh Batchers, Batching Plants, Manual or

Full Automatic Operation, Readymix Concrete Plants

and Equipment, Motor Truck Concrete Mixers and

Carriers, Electrically Operated and Controlled Water

Meters, Ricel Silos, Bins, Bunkers, Hoppers, Bunker

Gates, Chutes O. K. CLUTCH & MACHY, CO.—Holsta & Compressors

MENT CO. Chicago, Ill. PAUL COCHRAN EQUIP-228 N. LaSalle St.

Representing

Representing
Thew Shovel Co.
Universal Crane Co.
Worthington Pump & Machy. Co.
Novo Engine Co.
The Knickerbocker Co.
Fairfield Engineering Co.—Conveyors
R. B. Equip. Co.—Power Subgraders
Iowa Manufacturing Co.
Aeroil Burner Co.

Used Equipment—Rentals

Brandeis Machinery & Supply

201 Warnock St. Louisville, Ky. Representing

BROWN-BEVIS EQUIP. CO. 49th St. & Santa Fe Ave., Los Angeles, Calif.

Merican Saw Mill Masky, Co.—Saw Mill, Weodworking American Saw Mill Manny, Co.—Saw Shile, Vecciones Machinery Barnes Mig. Co.—Pumps Barnes Mig. Co.—Pumps Briggs and Stratton Corp.—Engines Buckeye Treation Ditcher Co.—Trenching Machinery J. I. Case Co.—Industrial Tractors Chain Belt Co.—Hex Mixers, Pavers, Pumps Continental Meters Gep.—Gas Engines Drake-Williams-Mount—"Omasha" Dragline Buckets Geo.—Williams-Mount—"Omasha" Dragline Buckets Geo.—Hills Mig. Co.—Honders Huber Mig. Co.—Honders Huber Mig. Co.—Holist Compressors, Air Tools Lispersod Mig. Co.—Holist
The Mast.cod Co.—Asphalt Rests. Tools, etc.
Manley Leggler Equipment Co.—Hicks
Tolscher Pressed Steel Co.—Terches, Horses

Member: Associated Equipo

THE HENRY H. MEYER CO.

658 Munsey Bldg., Washington, D. C. 110 S. Howard St., Baltimore, Md.

Representing
Austin Machinery Co.
Blaw-Knax Co.
Beaton & Lockport Block Co.
Brockvillo Locometivo Co.
Byorn Machine Co.
Chausso Oil Burner Co.
Countery & Co., Inc.
Domestic Engine & Pump
Co.
Li du Pont de Nemours
& Co.
Dobbie Fdy. & Mashine Co.
Duff Mfg. Co.
Duff Mfg. Co.

Representing
A. B. Farquhar Co., Ltd.
Harrington Co.
Pulsometer Steam Pump Co.
Ramsesic Concrete Mach. Co.
Sterling Wheelbarrow Co.
Tompleton, Kenly & Co.
Union Iron Works
Union Iron Works
Universal Road Mashy. Co.

SUPERIOR CONSTR. EQ. CO. Chicago, Ill. 1850 South Kostner Ave.

Construction Machinery Co. Elec. Tamper & Eq. Co.—
Mixers, Saw Rigs
Air & Electric Vibro Vi-

—Misers, Saw Riss
Foote Company, The—Concrete and Black-Top Pareers
Independent Pasu, Teel Co.
—Air Tools
Byers Mach, Co.—Cranes,
Shoveis, Draglines, etc.
Schramm, Inc.—Air Compressors, Tools
O, K. Clutth & Machy. Co.
—Holists
Rogers Bres. Corp.—Trailors

Grant & Electric Vibro Vibration
Freeman Mfg. Co.—Truck
Turntables
Markl-Bemedt Corp.—Shoulder Machines
Huse Mfg. Co.—Trailors
William Mfg. Co.—Trailors

Grant Mfg.

A Complete Lize of Construction Tools and Equipment Carried in Chicago. Tel.: Crawford 6200

ROY C. WHAYNE SUPPLY CO. Cor. 8th & Main Sts., Louisville, Ky.

Representation of the control of the

CROOK COMPANY 2900 Santa Fe Ave. Los Angeles, Cal.

Southern California Distributors for

Allis-Chalmers —Tractors
Breanels —Discs, Rippers, Chicals
Bucyrus-Erie —Shovels, Crames, Draglines
Buffals-Eigringfield —Ballers
D-A —Lubricants D-A —La
Holtzel —St
Hutchins —B
Saultices —A D-A —Lubricants
Holtzel —Steel Forms
Hutchins —Backfillers, Buildoners
Mask Weoldridge —Buildoners, Scrapers
Sullivan —Air Compressors, Drills, Sharp
T. L. Smith —Concrete Mixers

Member: Associated Equipment Distributor

M. D. MOODY

ACL No. 2-Sect. 1, Riverside Viaduct Jacksonville, Florida

Representing
Buffale-Springfield Roller Co.
Cyclone Fonce Co.
The Elgin Cerporation
E. D. Etnyre & Co.
De Walt Preducts Co.
Iowa Mfg. Co.
Littleferd Brothers
Rawls Mfg. Co.
Pago Engineering Co.
Washanha
Motor Co.

PEORIA TRACTOR & EQUIPMENT CO.

400 Franklin Street Peoria, Illinois

Representing Representing

Allsteel Products Mfg. Co.
Athey Truss Wheel Co.
Caterpillar Tractor Co.
Gardner-Denver Co.
The Frank G. Hough Co.
Killefer Mfg. Corp.
LaPlant-Choate Mfg. Co.
R. G. LeTourneau, Inc.
Speeder Machinery Corp.
Willamette-Hyster Co.
Wisconsin Foundry & Machine Co.

Telephone 6177

HENRY A. PETTER SUPPLY COMPANY Kentucky

Paducah

Alamiries Equipment
American Wire Rope, Menh
Bates Hard Holsts
Blank & Desker Tools
Gafar Rapids Crushers
Chain Belt (Rez) Mizers
D-A Lubricanis
D-A Lubricanis
D-A Lubricanis
Chain Belt (Rez) Mizers
D-A Lubricanis
Chain Belt (Rez) Mizers
D-A Lubricanis
Chain Belt Repricks
Elastite Expansion Joint
Farquhar Engines, Boild
Farquhar Engines, Boild
Farquhar Engines, Holorocing
Guiff States Heinforcing
Stoel
Blank A Description
Hannes Excuszions
Hanse Excuszions
Hannes Excuszions
Hannes Excuszions
Wert Graders
Werther Road Machinery
Werthington Pumps
Johnson Blan and Hoppers
Lidgerwood Holsting Machy.

GARLINGHOUSE BROS.

2416 E. 16th St. Los Angeles, Calif.
Southern California Distributors for Southern California Distributors for RANSOME—Concrete Mixors, Pavers, Pneu, Placers, Grouter, Concrete Placing Equipment, Street Forms WORTHINGTON—Portable Compressors, Prosenatic Tools, DOMESTICS—Pumps EROWNING—Truck Cranes, Shorets, Lecenotive Cranes EYERS—Cravier Shorets and Cranes OWEN—Clamabell Buckets
WMITCOMS—Gasoline, Diesel, Electric Lecenotives
A. LESCHEN & SONS—Wire Racy
LAMBERT.-NATIONAL—Floids and Cableways
DAMOND IRON WORKS—Crushers and Portable Gravel
Plants
DAMOND IRON WORKS—Crushers and Portable Gravel
Plants

Member: Associated Equipment Distributors

R. S. ARMSTRONG & BRO.CO. 676 Marietta St. Atlanta, Ga.

Representing
Tractors Representing
Tractors
AMES-SALDWIN-WYOMING Shovels, Scoops
BEEET Rand Hoists
BUTLEN Blins
CARBIC Lights
CARBIC Lights
CARBIC Lights
Air Compressors
DOMESTIC Pumps
EMERSON Fumps, Valves
GALION Read Machinery
GENERAL ELECTRIC
Mistors
JAEGER COCKYGE Mixers
JAEGER COCKYGE MIXERS
WORTHINGTON Pumps Member: Associated Equipment Distributors

BOWMAN-RALSTON TRAC-TOR & EQUIPMENT CO. 401 E. Florida St. Evansville, Ind.

Representing Athey Truss Wheel Co. LaPlant-Choate Mfg. Co. Baker Manufacturing Co. Thew Shovel Company Killefer Manufacturing Co.

Schramm, Inc.—Compressors
Willamette-Ersted Co.—Hoists Pioneer Gravel Equip. Mfg. Co. Anthony Company

Equitable Equipment Co., Inc.

Equitable Equipment Co., Inc.

410 Camp Street

BROWNING Crance and fibreria.

C A M E R O N Centrifugal Mediution Gears

C A M E R O N Centrifugal Morris Deciding Machy.

Gummins Dissed Engines

CUMMINS Dissed Engines

DEAN BROS. Heam and Power Pumps

EDGE MOOR Water Tube

STEPHENS-ADAMSON

Consequer

EMERAL ELECTRIC Motors, Are Welders, etc.

HOOIL Goulds Oil Puri
NGERSOLL-RAND AND TROOP, YERGER G.

NGERSOLL-RAND AND TROOP, YERGER G.

NGERSOLL-RAND AND TROOP, YERGER G.

STEPHENS-ADAMSON

Conveyors

TROV-ERGBERG Generators, Procs. Tools, Promps. Bagines

INTERNATIONAL Vickel, Moned Metal, Incomel

MERRELL Pipe Machines

ARCHER Towing Equipm
BUTLER Bins
CLYDE Hois
and Detrick
FREEMAN T
GALION GraLE ROI-RIX
Compressors LE ROI Gas LINK-BELT Crance and

Equipme

FLETCH

Magazi

LITTLEFORD Member: ALBAN 725-27 E

"CATERPILL"
"CATER ber: D. C.

115 S. C

Roshring Co. Kwik-Mix Co Imicy Mfs. (Parsons Co. C. M. & E. Goo. Haiss M Saverman Br Allis-Chalmed Gardner-Den Linn Mfg. Co Owen Bucket Lalbert Co., Emerson Putt Member: **JOHN** 511 W.

JAEGER—Co Pumps, Tri LAKEWOOD Forms, To AMERICAN Lay Wire HORTH WES Shovels, D Shovels, D BUTLER—B CENTAUR— WORTHING pressors, I ADAMS—Le Graders Member:

THE F 110

628 M

Blaw-Knox Section & Le Spers Machi Phillip Care Chausso Oil Connery & C Domestic En Dobble Fdry Duff-Norton Gallon Iron A. B. Farqu Harrington Member:

CLAR 790-798 RANGOME-NORTHWE BLAW-KNO

CARTER—INGERSOL ROOS—Sho HAUCK—O HAISS—EIL BAKER—B SARGENT— BEEEE BF CLEVELAN C. R. JAHY BURCH—R Member: TH 30 Pres

Link-Be Ingerso Willia

Homelie CC Member:

FLETCHER EQUIP. CO., INC. New Orleans, La.

309 Magazine Street

ARCHER Towers and Couting Equipment Burkets Owen Clamps OWEN Clamp

di-

me, los,

ky

and

ly

ζy.

Ca

0.

Y

ies

c.

Compressions and Carts and Carts the Rol Gas Enginee, Cranes and Shovets to LITLEFORD Heaters, Ketiles (MOD Molybdenum Stock Shorels)

Member: Associated Equipment Distributors

HEDGE & MATTHEIS CO. 285 DORCHESTER AVE.

BOSTON, MASS. Providence, B.I.; Portland, Ms.; Hartford, New Haven, Conn.; Springfield, Worcester, Mass.; Concord, N.H.

Aeroll Burner Cs.
American Tubular Elevator
Co.
American Tubular Elevator
Co.
Beasument-Birch Co.
Debble Fdy. & Mach. Co.
Electric Tamper & Es.
Electric Tamper & Es.
Electric Tamper & Es.
Electric Tamper & Es.
Elevator Co.
Eric Steel Construction Co.
Huber Mfg. Co.
Ingernell-Rand Co.
Iowa Mfg. Co.
Josep Machine Co.
Lakouvod Engineering Co.
Lakouvod

Member: Associated Equipment Distributors

THORMAN W. ROSHOLT CO.

THORMAN W. ROSHOLT CO.

928 So. Fourth St.

Representing

10WA "Codar Bapids"
Crusher Plants and Equipment

KOEHRING Pavers, Mixterm, Cranes

INSLEY Towers and %-yard
Shovels Trunching
MaHeCORNICA Trunching
MaHeCORNICA DEERING
LIndustrial Tractors
C. H. & E. Saw Bigs.
Roists, Pumps
KWIK-MIX Misers
RIDDELL Power Grader
JOHNSON Batchers and
Demountable Bins

Marpher: Associated Equipment Distributors

Associated Formaler and Bituninous Distributors

\$TOCKLAND Graders

WALTER Trucks

GORMAN-RUPP CO. BelfPriming Centrifugal

Pumps

Marpher: Associated Equipment Distributors

nber: Associated Equipment Distributors

C. F. RABBEITT, INC. 1523 N. Broadway St. Louis, Mo.

C. H. & E. Mfg. Company Littleford Bros.
Cleaver-Brooks Company Parson Company
Cleveland Fermgrader Co.
Huber Mfg. Company
Insley Mfg. Company
Frank G. Hough Company Frank G. Hough Company Lidgorwood Mfg. Company Sterling Machinery Corp.

Member: Associated Equipment Distributors THE GEO. F. SMITH CO.

Ingersoil-Rand—Compressors, Air Twels
Sors, Air Twels
Clyde—Hoists and Derricks
Owen—Clamshell Burkets
Hautk—Heaters
Sasgen—Derricks & Winches
Skilsaw—Electric Saws,
Skilsaw—Electric

Member: Associated Equipment Distributors

Franklin & Channing Aves., St. 1

Complete Plants Rented

ALBAN TRACTOR CO., INC. 725-27 East 25th St. Baltimore, Md.

725-27 East 25th St. Baltim

**CATERPILLAR"* Diesel Tractors. Motors

**CATERPILLAR"* Combine Harvesters

**ERNELLAR"* Combine Harvesters

**ERNELLAR"* Combine Harvesters

**ERNELLAR"* Combine Harvesters

**ERNELLAR"* Combine Harvesters

ERNELLAR Combine Harvesters

ERNELLAR Componition

ERNELLAR Componition

ELLAR Tillage Tools

**LIMK-BELT Shovels & Cranes

**EUCLID ROAD MACHINERY CO.

**LEVELAND ROCK DANILL CO.

**LEVELAND ROCK DANILL CO.

**BALCRE MFG. CO.

**BALC nt Distributer ber: Associated Equipme

D. C. ELPHINSTONE, INC.

Baltimore, Md. 115 S. Calvert St. 976 National Press Bldg. Washington, D.C.

Representing

Reshring Co.

Kwik. Mix Co.
Indiv) Mfs. Co.
Minus
Gardier-Dervier Co.
Lies Mfs. Curp.
Own Bucket Co.
Labour Co., Inc.
Labour Co., Inc.
Labour Co.
Memple Valve Co.

lows Mfg. Co.
H. K. Perter Co.
H. K. Perter Co.
H. E. Perter Corp.
Lambert-National Hoists
Goodall Rubber Co.
Minwax Co.
E. D. Enyre & Co.
W. A. Riddell Co.
Hough-Universal «weepers
C. S. Johnson Company).
Hubber Mfg. Co.
Equipment Distributors

511 W. Pratt St. Baltimore, Md.

Bhorels, Drakines
BUTLER—Bins
GENTAUR—Boad Mowers
WORTHINGTON—Compressors, Drills, etc.
ADAMS—Leaning-Wheel
Graders
Graders

Graders

TIMKEN—Detachable Mook
Bits
HLYARD - N E W B O L D—
Hot or Cold Asphalts Mixing Plants
ALABAMA—Cast Iron Pipe

JAEGER—Concrete Mixers, etc.
Frunps, Truck Mixers, etc.
LAKEWOOD—Finishers,
Forms, Towers
MERICAN CABLE—TruLay Wire Rope
RORT HW EST—Cranss,
Rhorels, Draglines
SUILER—Bland Monors
Timken—Detachable Rock

Member: Associated Equipment Distributors

THOMAS G. ABRAMS, INC.

Construction Equipment
2411 Fourteenth St. Detroit, Mich.

Representing

Representing
Aeroil Burner Co.
Archer Iron Works
Brookville Locomo.ive Co.
(McCormick-Deering Power)
Butler Bin Company
Burch Corporation
Byers Machine Co.
LeRoi-Rix Compressors
St. Regis Paper Company
Sasgen Derrick Company
T. L. Smith Company
Smith Engineering Works
Sterling Wheelbarrow Co.
Toledo Pressed Steel Co.

KELLER TRACTOR & EQ. CO., Inc. 5163-69 Martin Ave., Detroit, Mich.

Atecs—Dirt-moring equipment and buildosers
Baker Mfg. Co.—Grow plows, read machinery
Blaw-Knex Company plows, read machinery
Blaw-Knex Company
bins, batchers and buckets
Bueyrus-Frie Company—Shovels, cranes, draglines
Chain Belt Co.—Alixers, pavers, pemps
Caterpillar Tracter Co.—Tractors, graders, read machinery
D-A Lubricant Ca.—Lubricants
Brit Co.—Hercules spreaders
Gardner-Denver Co.—Air compressors and tools
Killefer Mfg. Cor.—Hood and farm tools
LaPlant-Choute Mfg. Co.—Buildosers, backfillers, wagons,
snow plows

snow piows
A. Leschen & Sans Rage Ca.—Wire rope
E. D. Etnyre & Ca.—Oil and tar distributors and heaters
Timken—Rock bits
Universal Crusher Ca.—Gravel Equipment

Member: Associated Equipment Distributors

WM. H. ZIEGLER CO., INC. finneapelis, St. Paul, Duluth, Minn., Glasgow, Mont.

Mont.

"CATERPILLAR" — Tractors, Engines, Road Machinery
LA PLANT-CHOATE—
Bulldosers, Bnow Plows,
Dump Wagons
Le TOURNEAU — Dirt
Movine, Road Equipment
KILLEFER—Road Rippers,
Scrapers,
LEECHER—Wire Rose

KILLEFER-Road Riporest, Scrapers
ATHEY—Crawlers, D ump
Wagons, Trailers
BUCYRUS-RRIE — Power
Shovels, Cranes, Draglines
PIONEER—Crushers, Gravet
el Plants
REX—Mixers, Pavers, Moto-Mixers, Pumpe, Baw
Rigs
BUTLER—Bins, Baitchere

Member: Associated Equipment Distributors

BUBLITZ MACHINERY CO. 2141 Washington St., Kansas City, Mo.

Representing

Representing
Jasper Manhine Co.
Lakewood Engineering Cs.
Thew Shovel Cc.
Barber-Greene Company
Iowa Manufacturing Co.
McKlornan-Torry Corg.
Worthington Pump & Machy. Co.
Bufter Bin Co.
"Williams".—Buckets and Trailers
Slusser-McLoan Seraper Co.
Ames Baldwin Wysming Cs.
Had Str.
Freducts Cs.
Sasgen Derrick Co.
Climax Engineering Cs.

Member: Associated Equipment Distributors

TULLEY EQUIPMENT CO., INC. 4215 Clayton Ave. St. Louis, Mo.

ORTON-Cranes, Shovels, Draglines, Buckets LEACH-Mixers, Tower Outfits, Saw Rigs ROGERS BROS.-Trailers HUMPHREYS-Pumps MILWAUKEE—Gasoline Locomotives

McLANAHAN & STONE—Crushers, Screens Reinforcing Steel and Accessories Asphait and Rubber Expansion Joint Road Building Materials

JOHN C. LOUIS COMPANY

CONTRACTORS MACHY. CO. 530 Monroe Ave., N.W. Grand Rapids, Mich.

Jaeger Mashine Company
Lakewood Engineering Co.
Worthwest Engineering Co.
Sultivan Mashinery Co.
Pleneer Gravel Equipment
Mfs. Co.
American Steel & Wire
Lead To.
American Steel Co.
American Steel & Wire
Lead Company
Sauerman Brothers

Synther Company
Leftel Company
Moritz-Company
Company
Moritz-Company
Company
Moritz-Company
Moritz-Company
Company
Moritz-Company
Moritz-Company
Company
Moritz-Company
Moritz

Member: Associated Equipment Distributors

O. B. AVERY COMPANY

1325 Macklind Avenue St. Louis, Mo.

Exclusive Distributors for Exclusive Distributors for American Steel Works
Austin-Western Road Machinery Ce.
Blaw-Knox Co.
Chain Belt Ce.
Dayten-Sure Grip & Shere Co.
C. R. Jahn Co.
Kewanee Machinery & Conveyer Co.
Kewanee Machinery & Conveyer Co.
McKlernan-Terry Cerp.
Northwest Engineering Co.
R. B. Equipment Mfg. Co.
Sullivan Machinery Co.
Vuican Locomotive Works
Koppel Industrial Car & Equip. Co.

Member: Associated Equipment Distributors

CONNELLY MACHINERY CO.

2706 Montana Ave. Billings, Mont.

Distributors of
Caterpillar Tractors, Engines, Rosd Machinery
Flower Gravel Plant Equip.
Busyrus-Fire Shovels, Dractilloss and Cranes
Busyrus-Fire Loadmaters
Buskrys- Ditchers, BackillBusfale-Springfeid Bad
Rollers
D-A Lubricanta, Olls
Howitt Belting, Hoop
Tracter-operated Heists, Scrapers, Dirtmewers, Rippers,

Tractic-operated Heists, Scrapors, Dirtmovers, Rippers, Scariffers, Buildecres, Trailbuilders, Backfillers, Snew Plows, Loaders, Track-type and Wheeled Wagens and Trailers, etc.

Member: Associated Equipment Distributors

THE HENRY H. MEYER CO.

110 S. Howard St., Baltimore, Md. 628 Munsey Building, Washington, D.C.

Representing

Blur-Knex Co.
Botton & Lorkport Bl. Co.
Byers Mackine Co.
Byers Mackine Co.
Classos Oil Burner Co.
Classos Oil Burner Co.
Classos Oil Burner Co.
Dibble Ford. & Mark. Co.
Bible Ford. & Mark. Co.
Bible Ford. & Mark. Co.
Bible Iron Wks. & Mfg. Co.
Galian Iron Wks. & Mfg. Co.
Rerington Co.
Rerington Co.
Rerington Co.
Rerington Co.

Member: Associated Equipment Distributors

E. K. S. EQUIPMENT CO. 18 Grandville Ave., S.W. Grand Rapids, Mich.

Representing

Representing

ALLIS-CHALMERS—Tractors, Gradors, Wapons, Shoreis

For Gradors, Wapons, Shoreis

For Gradors, Wapons, Shoreis

For Gradors, Wapons, Shoreis

GENRING—Shorels, CENTERS

KWIK-MIX—Misers

LITLEFORD—Kettles, Hesters, Asphalt Machinery

FOUR-WHEEL DRIVE—

Batchers

FOUR WHEEL DRIVE—

HELTZEL—Forms, Bins, Batchers

HUBER—Rollers

HUBER—Rollers

ROMATISON—Show Fence MACWHYTE—Wire Rope

ARGONS—Transbers, Batchers

SCHRAMM—Air Compressors, Tools

SCHRAMM—Air Compressors, Tools

SCHRAMM—Air Compressors, Tools

SMALL TOOLS

SMALL TOOLS

SMALL TOOLS

MALL TOOLS

SMALL TOOLS

SMALL TOOLS

MALL TOOLS

SMALL TOOLS

MALL TOOLS

SMALL TOOLS

MALL TOOLS

SMALL TOOLS

MALL TO SHOVELS, PICKS and SMALL TOOLS

CORBY SUPPLY COMPANY 3942-46 W. Pine Blvd., St. Louis, Mo.

DETROIT HOIST & MACH. CO.—Air and Electric Hoists BUCKEYE TWIST DRILL CO.—Twist Drills and Beamers
BUHL CO.—Portable Air Compressors
CHAMPION RIVET CO.—Rivets and Welding Red
DETROIT HOIST & MACHINE CO.—Air Hoists
HARDSCCG WONDER DRILL CO.—Reck Drills, Par-

HARDSOCG WONDER DRILL CO.—Reck Drills, ing Broekers R. M. H. KELLER, INC.—Super Procumatic Tools WM. H. KELLER, INC.—Super Procumatic Tools DAVID ROUND & SON—Chain Hoists RIVET CUTTING GUN CO.—Rivet Busters N. A. STRAND & CO.—Fietble Shaft Equipment UNION—Portable Woodworking Tools VAN DORN—Electric Drills, Grinders, Buffers VICTOR—Welding and Cutting Torches VICTOR—Welding and Cutting Torches
WESTINGHOUSE—Are Welding Equipment
GUSTAV WIEDEKE & CO.—Tube Expanders

MIDLAND IMPLEMENT CO., Inc. Billings

FORDSON—Tractors and Industrial Equipment
BARBER-GREENE—Conveyors, Ditchers and Loaders
DIAMOND 180N WORKS—Cravel Equipment
BRENNEIS—Bippers and Scarifiers
WOOD—WIVE Snow Frence
HYSTER—Hoists and Winches
LANSING—Scrapers, Frence and Barrows
SCHRAMM—Compressors
WHEELING CORRUGATING CO.—Metal Culverts
KOEMRING—Shorels, Drag Lines and Concrete Mixers
INDUSTRIAL & TRUCK FLARES
BRODERICK & BASCOM WIRE NOPE CO.—Wire Bope
and Cable and Cable

ROSCO—Trail Dumpers and Olling Equipment

WM. BROS MFG. CO.—Gnow Plows and Rollers

GOOD RICH—Transmission and Conveyor Belting

KENSINGTON—Crusher Jawa, Caterpillar Treads, etc.

CLEVELAND—Rock Drills. Member: Associated Equipment Distributors

CLARK-WILCOX COMPANY 790-798 Albany St. Boston, Mass. Representing

RANSOME—Concrete Mixers, Chuting Equip.

NORTHWEST—Cranes, Showels, Draglines

SLAW-KNOX—Steel Forms, Bins, Buckets, "Ord" Fin-LAW-KNOX—Steel Forms, Dins, Dunsen, Idlers
CARTER—"Hundinger" Pumps
MRERSOLL-RAND—Air Compressors
NR-SEMBOWER—Hoists, Boilers, Mixers
ROOS—Shores and Clamps
HAUCK—Oil Burners and Heaters
HAISS—Elerators, Conveyers and Loaders
ALLIS-CHALMERS—Tractors
BAKER—Buildoners
BAKER—Buildoners
BAKER—Buildoners
BAKER—Buildoners
BEEBE BROS.—Hoists
CLEVELAND—Formgraders
CLEVELAND—Formgraders
CLEVELAND—Formgraders
BURCH—Ross Flows, Road Machinery
BURCH—Ross Flows, Road Machinery

Member: Associated Equipment Distributors

BORCHERT-INGERSOLL, INC. Duluth, Minn. St. Paul, Minn.

Allis-Chalmers Tractors and Graders (Garders Manuerlean)* Bulldoners, Honey Plows Blaw-Keev Bins, Forms, Buckets, Flaithers Bland Holsts, Derricks Clevish Formgraders Diamend Crushers, Screens Demestis Pumps Eastled Wagons, Berapers Eastled Wagons, Berapers Eastled Wagons, Berapers Bulliwan Compressors, Tools Topk Hereules Road Bigns Haiss Loaders Whethers (Dorecton Movers Whiteemb Locomotives Member: Associated

Member: Associated Equipment Distributors

Represents.

Represents.

Athey Truas Wheel Co.
Cleveland Rock Drill Co.
Blaw-Knox Company
Caterpillar Tracter Co.
Davey Compressor Co.
Euclid Road Machinery Co.
Killefer Mig. Co.
LaPlant-Choate Mig. Co.
Pioneer Gravel Equip. Mig. Co.
Thew Shovel Company
Willamette-Ersted Co.
W. K. M. Company

oment Distributor

HALL-PERRY MACHINERY CO. 802-12 E. Iron St., Butte, Mont.

Representing

Madeen from Works
Alies Imperial Diesel Eng.
Ce.
Butler Bin Co.
Chain Belt Co.
Climax Engineering Co.
Elgin Corporation
Etayre & Ce.
Gallon Iron Works & Mig.
Gallon Iron Works
Mig.
Smith Engineering Works
Gallon Iron Works & Mig.
Gallon Iron Works & Mig.
Gallon Iron Works & Mig.
The Works of Co.
Gallon Iron Works & Mig.
The Works of Co.
Gallon Iron Works & Mig.
The Massey Winehee
Heater Saver Brow Co.
Saverman Brow, Inc.
Gallon Iron Works
The Works

Member: Associated Equipment Distributors

THE EQUIPMENT CO.

30 Prentiss St.

Boston, Mass.

Link-Belt Cranes and Shovels Ingersoll-Rand Compressors and Tools

"Williams" Buckets and Trailers Homelite Pumps and Generators COMPLETE RENTAL SERVICE

Member: Associated Equipment Distributors

LANGE TRACTOR & EQ. CO. 304 Lake Ave., S. Duluth, Minn.

Acroil Tar Kettles, Heater Catveillar Road Machinery and Tractors Levinery and Tractors Levinery Road Tractors Replaced From Players, Scrapers, Scrapers, Blast Hale Drills
Diamed Gravel Crushing, Screening, Washing Flants, Couveyors Killefer Scrapers, Road Discs, Bippers
Davey Air-Cooled Air Compression Research Convented Air Compression Players, Conveyors Clevisian Rock Drills
Highway Karth Bering Machines

Lesinet Wagons chines
Ames Baidwin Wyoming Hand Shorels
Member: Associated Equipment Distributors

JOSEPH KESL TRACTOR & EQUIP. CO.

St. Louis, Mo. 1510 North 13th St.

10 North 13th St.

Representing
Allis-Chaimers Mfg. Co.
American Steel Seraper Co.
American Steel Seraper Co.
Cushman Meter Works
Eric Steel Construction Co.
Cushman Meter Works
Eric Steel Construction Co.
Gardener-Denver Co.
Mall Tool Co.
Mall Tool Co.
Mall Tool Co.
Contractors Machinery Corp.
Contractors Machinery Corp.
Democrit English & Mump Co.
Draw Company Corp.
Democrit English & Mump Co.
Draw Company Corp.
Mack Wooldridge Co., Ins.
Mack Wooldridge Co., Ins.

NORTHWEST EQUIP. CO., Inc. Box 1112 Great Falls, Mont.

Complete Line of Road Machinery and Contractors' Equipment

Representing
KOEHRING—Misers, Pavors, Shorels
PARBONS—Trenchers
COLEMAN—Trucks
Paires
SCHRAMM—Air Compressors
Paires

Fasers
INSLEY—Concrete Towers
& Chuting, Shovels
PANTHER—Oil and Gresse
Scrapers, Fromos, etc.

CLEVELAND-Book Drills STEEL BRIDGES AND TRAFFIC TREAD JAEGER Concrete Mixers JAEGER Placing Plants AEROIL Torches, Heaters

Steel Sidewalk and
Curb Forms
"Mud Hog" Pumps
Material Elevators
Air Compressors
Gasoline Hoists
Trench Pumps Trench Pumps Carbic Lights

ches, Heaters
Wheelbarrows
Mortar Tubs
Steel Mortar Boxes
Picks and Shovels
Tarpaulins
Scaffold Horses
Electric Drills & Saws
Chain Hoists

COMPLETE MACHINERY & EQUIPMENT CO., Inc.

"Specialists in Pumps"

Webster Ave. and Hancock St.
Long Island City
Representing
RALPH B. CARTER CO.—Humdinger SelfPriming Centrifugal Pumps
HUMPHREYS MFG. CO.—Diaphram, Plunger
and Centrifugal Pumps
LEACH CO.—Concrete Mixers and Centrifugal Pumps
LEACH CO.—Concrete Mixers
INGERSOLL-RAND CO.—Air Compressors
COMPLETE.—Well Point Systems
—Steel Blasting Mats—
RENTAL SERVICE Member: Associated Equip nt Distributors

JOHN REINER & CO., Inc. 29 Howard St. New York, N. Y.

Representing

NOVO ENGINE CO.—Gasoline Engines
WISCONSIN MOTOR CORP.—Gasoline Engines
and Power Units and Power Units

POWER MFG. CO.—Diesel Engines

PERFEX RADIATOR CO.—Radiators

MASON DIESEL ENGINE CO.—Diesel Engines
and Generating Sets TWIN DISC CLUTCH CO.—Clutches

Telephone CAnal 6-0286

THE BLAISDELL-FOLZ EQUIP. CO.

Equip

THE

285 Co

Harnisch LaPlant-Athey Tr Killefer I Baker Mr Willamet Blaw-Kne All Steel

SOUT

169-171

Allis-Chain lows Mfg. Oppod Co. General Ex Hercules C W. A. Rid Sobramm, I Cisvoland

CLYI

Portlan

Atlas Impe Ce. Blaw-Knex Corp. Clyde iron Homelite C Lincoln Ele Bucyrus-Er Ces. Haiss

Member:

HOWA

Pertland

internat'I (McCorm Industria Barber - Gre Cloveland F Marien - Ste Hughes - Ko Cloaver - Bre The Jaeger Nordberg R Crushers)

Crushers) McKiernan-Retary Snor Sohramm, It Universal

Chester

FORDSO UNIVERSI els 3 OSGOOD WEHR C

MICHIGA SCHRAM

BOW

Excava

1126 N

G

17th St

RANSOM

BLAW-K

Cont

205-219 West Pearl St. Cincinnati, Ohio Representing
Allis-Chaimers Mig. Ca.—Tractors, Road Machinery Chain Self Ca.—Rox Pavers, Molo-Mixers, Building Mis-

Vators Crusher Co.—Crushers
Universal Crusher Co.—Bins, Ratchers
Phe C. S. Johnson Co.—Bins, Ratchers
Deleter Machine Co.—Frat-O Vibrater Screenz
Wellman Engineeries Co.—Classical, Dragtine Buckets
Sasgen Derrick Co.—Derricks Member: Associated Equipment Distributors

DALE & RANKIN, INC.

113 Frelinghuysen Ave., Newark, N. J.

Representing

Representing
HELTZEL Road Forms and Bins
P & H Cranes and Excavating Equipment
P & H Hansen Electric Arc Welders
INGERSOLL-RAND Compressors and Tools
STERLING Wheelbarrows
AEROIL Heaters and Tools
ALEMITE Guns and Fittings
REX Mixers and Pavers
REX Pumps
REX Pumps
REX Saw Rigs
INTURNES EX Pumps EX Saw Rigs NIVERSAL Concrete Accessories INSLOW Scales

Member: Associated Equipment Distributors

GEORGE MALVESE & CO.

New Hyde Park, N. Y.

Long Island Distributors:

SARGENT Snow

CLETRAC Crawler LOCKE Power Mowers Tractors REX Pumps, Mixers PLYMOUTH Tractors EUCLID Scrapers ADAMS Graders OLIVER Impler BRODERICK & BAS-COM Wire Rope WORTHING-TON Power Mowers

United Hoisting Co., Inc.

165 Locust Avenue NEW YORK, N. Y.

Representing

Sullivan Machinery Co. Construction Machinery Co. G. M. T. Company

Member: Associated Equipment Distributors

THE MECHANICAL SUPPLIES COMPANY 205-207 Vine St. Cincinnati, Ohio

Representing

LAKEWOOD—Finishers, Subgraders, Graders
Forms, etc. Forms, etc.

NOVO—Gasoline Engines, Hoists, Pumps, etc.

WORTHINGTON—Air Compressors, Rock Drills, Paring Grakers, etc. Breakers, etc.

ENERAL—Shovels, Cranes, Ensavaturs, etc.

REGER—Truck Concrete Mixers

ILLEFER—Road Bippers and Rooters, Road Di

RILLEPEN-Hood Hippers and Howers, Hoo Strapers, etc. Off.—Pertable Saw Tables, etc. OLUMBUS—Elevators and Conveyors SIMPLICITY—Screens OSGOOD—Shorels, Crance, etc. HERCULES—Hollers

JOHNSON & DEALAMAN, INC.

GO Marshall Street Newark, N. J.

Representing
RANSOME Pavers, Mixers, Chuting Equipment
SCHRAMM Air Compressors, Tools
ALLIS-CHAIMERS Tractors, Graders
JAEGER-LAKEWOOD Read Finishing Machines, Truck
Mixers, Road Pumps
JOHNSON Steel Blins and Batchers
ERIE Gasoline Bollers
BAY CITY Truck Cranes
MARLOW Contrifugal, Disphragm and Plunger Pumps
ETNYRE Tar and Asphalt Distributors
WILLIAMS Trailers and Buckets
RED STAR Wheelbarrows, Batch Boxes, Column Clamps
and Adjustable Shores
OSGOOD Shovels, Cranes and Draglines
GENERAL Showels, Cranes and Draglines
HOTCHKISS Road and Sidewalk Forms

"Brooks for Concrete Equipment" R. E. BROOKS COMPANY

Equipment for Contractors

rch Street New York, N.Y.

NATIONAL EQUIPMENT CORP. PARSONS CO.

PARSONS CO.

C. H. & E. MFG. CO.

KOEHRING CO.

HANDY SACK BALER CO.

BLAW-KNOX CO. CLEAVER-BROOKS CO. ROSCO MFG. CO.

N. P. WALTON, JR. 50 Church Street New York, N. Y.

Representing
D. C. ELPHINSTONE, INC.—"BEST" Stone

and Chip Spreaders

ERIE STEEL CONSTRUCTION CO.—All-Steel
Bins, Complete Aggremeter Plants—Erie
Buckets—Clamshell, Dragline and Electric.

IOWA MFG. CO.—'CEDAR RAPIDS' Crushers, Material Handl. Equip., Sand, Gravel
and Asphalt Plants
THE KRON CO.—Full-capacity Springless
Dial Scales

Dial Scales
METAL FORMS CORPORATION—Metaform
Road Rails, Sidewalk and Curb Forms
THE "WHEELED ROLLER" CORP,—Wheeled-Type Portable Surface Rollera

THE CLETRAC OHIO SALES CO.

E. 193rd Street and Euclid Ave. Cleveland Ohio

Representing

THE CLEVELAND TRACTOR CO.—Crawler

THE DAVEY COMPRESSOR CO .- Air-Cooled

THE EUCLID ROAD MACHY. CO.—Crawler Wagons, Scrapers THE WALSH SNOW PLOW CO.—Snow Plow

D-A LUBRICANT CO.-Oil THE ROC COMPANY-Winches

SLADE TRACTOR CO., Inc. 36 Learned Street Albany, N. Y.

Representing

"GATERPILLAR" Trackross, Road Machinery, Combines LaPLANT-CHOATE Track Wheel Wagons, Buildouers and Snow Flows EUGLIO Botary and Wheel Scrapers, Track Wheel Wagons KILLEFER Agricultural Implements and Contracting Tools WILLAMETTE-HYSTER Hoists for "Caterpillar" Trackers

The Compensation of the Co

A. P. DIENST CO.

Contractors' Supplies

140th St. & 3rd Ave., New York, N. Y. Distributors for GREDAG Grease

TOLEDO Bull Frog Wheelbarrows WYOMING Red Edge Shovels **DUFF** Sewer Trench Braces CURRY Wire Ties KEYSTONE Grease

Telephone MOtt Haven 9-5430

BREWSTER & WILLIAMS, INC.

Contractors' Supplies and Equipment
306 S. Salina St. Syracuse, N. Y.

Representing

BUTLER Bins and Measuring Hoppers
C. H. & E. Cuntractors' Pumps, Hoists, Saw Rigs
HAISS Loaders, Excavators, Conveyors and Buckets
HOTCHKISS Steel Forms
LA CROSSE Tu-Way Trailers
LITTLEFORD Asphalt Heaters and Tools
OSGOOD Shorels, Draglines and Cranes
RANSOME Mixers, Pavers, Towers and Chules
SULLIVAN Compressors, Drills and Hoists
WEHR Purser Graders

Member: Associated Equipment Distributors

THE DAY & MADDOCK CO.

Equipment Headquarters
8201 Almira Ave., Cleveland, 0.

Representing

Representing

American Holata and Sinose
Plows
American Torry Derricks
American Scrapers & Boad
Drags
Barnes Pursanders
General Rep
General Rep
General Rep
General Rep
Holat Machines
And Vibrators & Grinden
Matiwal V-G Carbide Light
Saucemas Croscont Scrap
Saucemas Croscont Scrap
Bullivan Compressors, Test
Hose
Hose
Hose
Hose
Tester Tools

Electric Tools

Keppessors

Tester Torches
Universal Crushers

DOW & COMPANY, INC.

"Equipment for Highways"
Court & Wilkeson Sts., Buffalo, N.Y. C. H. & E.—Pumpe, Hoists, Saw Rigs BARCO—Gasoline Hammers CHICAGO PNEUMATIC TOOL CO.—Compressors, Drills ADAMS—Leaning Wheel Graders

ADAMS—Leaning Wheel Graders
BURGH—Spreader, Mintainers, etc.
BURGH—Spreader, Mintainers, etc.
BURGH—Spreader, Mintainers, etc.
BUGLID—Barth-Moring Equipment
HOUGH-UNIVERSAL—Sweepers
McCRMICK-DEERING—Tractors
"METAFORMS"—Concrete Forms
MOHAWK—"Hotstuf" Kettles, Burmers
THEW-LORAIN—Shovels, Cranes
UNIVERSAL-LORAIN—Shovels, Truck
UNIVERSAL-LORAIN—Shovels, Truck
"WILLIAMSPORT—Wire Rope
WALTER—Showelshiers, Trailer
WILLIAMSPORT—Wire Rope
WALTER—Showelshiers, Trailer
WALTER—Showelshiers, Tractor Trucks
FRINK—Bio Plows
FRINK—Bio Plows
FRINK—Bire Trucks

J. C. HOUSTON

50 Church Street New York, N. Y.

Representing

BROWNING CRANE & SHOVEL CO. HOISTING MACHINERY CO.

Warehouse

ELIZABETH, N.J.-L.V. R.R.

THE SYRACUSE SUPPLY CO. 314 W. Fayette St. Syracuse, N. Y. Warehouse 358 W. Jefferson St.

Warehouse 358 W. Jefferson St.

Atias Powder Ce.
Athey Truss Wheel Ce.
Barber-Greece Co.
Barber-Greece Co.
Caterpillar Tractor Ce.
Contaur Tractor Ce.
Clyde Seies Ce.
Euclid Mig. Ca.
Davis Comman Rung Ce.
Goodyear Tire & Rubber Ce.
Gorean Rung Ce.
Tompsteller B e ac i n a
Johns-Manville (Expansion Joint)
Timken Bits & Rods

Member: Associated Equipment Distributors

NORTH CAROLINA EQ. CO.

H. B. FULLER EQUIP. CO. 1836 Euclid Ave. Cleveland, Ohio

Representing

Blaw-Knex Company—Bins, Batches, Forms, Trukmires, Buckets, ORD Finishing Machines, Asphalt Plants Link-Beit Ca.—Shovels, Cranes, Draglines, Locumolin Cranes Cranes
Ransome Coner. Mashy. Co.—Pavers, Constr. Mixers, Tweers and Counting Equip.
Baidwis Leseastive Works (Internal Combustion Division—"Whitcomb Lecomotives")—Gaucine, Disselective Tampers & Equip. Ca.—Concrete Vibrators, Essentia Tampers

Meritz-Bennett Corp.—Road Shoulder Finishers, Fora Pullers
Concrete Surfacing Machinery Co.—"Borg" Surfacers
DeWait Products Corp.—Power Saws
Mohawk Asphalt Heater Co.—Asphalt Kettles, Heaters

LLOYD G. ROSS

3090 Main St.

Buffalo, N. Y.

General Excavator Co. Hercules Roller Co.

Sale and Rent of All Kinds of Construction Equipment

MAHONEY-CLARKE, INC.

Representing
BATES Wire Ties
HERCULES Road Rollers
LAY-SET Preformed Wire Rope
MARLO Self-Priming Pumps
MUNSELL Pneumatic Concrete Vibrators
OGGOOD Shovels, Cranes, etc.
STANLEY Electric Drills, Saws, etc.
THURSTON Detachable Bits
VULCAN Pile Hammers, Extractors and Parts
WILEY and BLAW-KNOX Concrete Buckets
GENERAL Shovels, Cranes, etc.
INGERSOLL-RAND Air Compressors

P.O. Drawer 426, 3116 Hillsbero St. RALEIGH, NORTH CAROLINA Complete Line of Contractors' Equipment and Supplies

217 Pearl Street New York, N. Y. Representing

RALEIGH, NORTH CAROLINA
American Cable Company
Acrell Burbar Company
Acrell Burbar Company
Company
Cleveland Rock Drill Cs.
Coctinectal Roll & Steal
Foundry Co.
Day Pulverizer Company
Ecutifd Rock Marky. Cs.
The Fear Wh. Dr. Autho
Callion Alliscel Body Cs.
Good Roads Marky. Cs.
Lowa Manufacturing Cs.

Schramm, Inc.
Schramm, Inc.
Walkerham Company
Willieft Manufacturing Co.
Ivwa Manufacturing Cs.

Weeked Roller Corporation
Weeked Roller Corporation
Wheeled Roller Corporation

Member: Associated Equipment Distributors

INDUSTRIAL ENGINE PARTS, INC.

1053 E. 61st St. Cleveland, Ohio

Representing

Minneapelis-Moline Power Impl. Co.
spinocring Co. Twin Diss Clutch Co. Climax Engineering Co. Twin t Fuller & Johnson Mfg. Co.

Wisconsin Motor Corp. (Air-Cooled) Stover Engine & Mfg. Co. Scintilia Magneto Co.

Wice Electric Co. Pertable Power Tool Corp. LeRal Ca.

Hereules Pred. Ca.

EUGENE F. VAN NAME 116 John Street Horseheads, N. Y.

ALLIS-CHALMERS—Tractors, Graders
A-W—Traffic Tread
BAKER—Road Drags, Snow Plows
C. M. C.—Wonder & March-Capron Mixers
HUBER—Rollers
HOTCHKISS—Sidewalk Forms
HANSON—Excavators
INGERSOLL-RAND—Air Compressors
JACKSON—Wheelbarrows
MILES—Concrete Block Machines
THE NORTHERN—Gravel & Coal Conveyors
WILLIAMSPORT—Wire Rope
WISCONSIN SPECIAL—Snow Plaws

H. O. PENN MACHY. CO., INC.

140th St. & East River Bronx, N. Y.

Representing

MARION Shorels—% to2-pd SPEEDER Showels, % to CATERPILLAR Tractors %-yd.
LaPLANT-CHOATE Wagens LaPOI Compressors and Enand Bulldozers
BLAW-KNOX Sco
MARLOW Pumps
WARCO Graders
PIERCE Rollers gines
HELTZEL Steel Bins
HOTCHKISS Forms
SMITH Mixers, Pavers
LE TOURNEAU Scrape

Warehouse Stock-Service Station

Member: Associated Equipment Distributors

CAROLINA TRACTOR & **EQUIPMENT COMPANY**

Salisbury, N. Car. S. Main Ext. Branch Office and Warehouse: 733-35 West Hargett St., Raleigh, N. Car.

WORTHINGTON—Air Compressors and Drills
ETNYRE—Bituminous Distributori, Flushers
GONMAN. RUPP—Contrifugal Pump.
GONMAN. RUPP—Contrifugal Pump.
GONMAN. RUPP—Contrifugal Pump.
GONMAN. ROPE—Contributori, Flushers
BLAW KMOX—Steel Force, Darse
BARBER. ROREENE—Conveyors, Car Uniosaters
DIAMOND—Roll, Jaw Crushers
BARBER. ROREENE—Conveyors, Car Uniosaters
DIAMOND—Roll, Jaw Crushers
BERGULER—Gas Road Rollers
LaPLANT. CHOATE—Wagons, Bulldosser
SUBSER. Maal. EAR—Whoelers, Rippurs, Fresnoe
WONDER—Misers, Pumps, Hoists

Member: Associated Equipment Distributors

W. T. WALSH EQUIPMENT CO.

W. I. WALDII

3068 West 106th St., Ceveland, Ohio. Tel. Lakewood 1001

Representing

American Floor Surfacing Hough-Universal—Sweepers

Mathine Co.—Surface Huber Mfg. Co.—Road Reli-Machine Ca.—Burrace
Grinder:
Acthosy Company—D um D
Trucks, Hydraulic Hoists
Bares Mig. Ca.—Ganoline
Hammer:
Hammers
H

CATERP Road M Special THE BA phragn NORTHV ORD_R

Columbus, Ohio

THE TAYLOR TRACTOR CO.

Catsrpillar Tractor Company—Tractors, Road Machinery, Diesel Engines
Harnischfeger Sales Corp.
LaPlant-Choate Mig. Co.
Athey Truss Wheel Co.
Killefer Manufacturing Corp.
Baker Manufacturing Corp.
Biker Manufacturing Co.
Willamette-Ersted Co.
Bigs-Knox Co. (Ateco Div.)
All Steel Products Mig. Co.

SOUTHERN OHIO EQUIP. CO.

169-171 W. Main St., Zanesville, Ohio

On Route 40

Phone 813 Distributors for

Allis-Chaimers Mfg. Co.
Iswa Mfg. Co.
Oppose Co.
Shunk Mfg. Co.
Shunk Mfg. Co.
Shunk Mfg. Co.
Shunk Mfg. Co.
MacWhyte Co.
Trackson Co.
W. A. Riddell Co.
Skiramm, Int.
Cloveland Rock Drill Co.

CLYDE EQUIPMENT CO.

Contractors' Equipment and Supplies

Atlas Imperial Diesel Eng.
Ca.
Sauerman Brethers
Sullivan Machinery Cc.
Blaw-Knox & Western Pipe
Cerp.
Cyte Iron Works
Hossilite Corp.
Hossilite Corp.
Buyern Statis Cs.

Member: Associated Equipment Distributors

HOWARD-COOPER CORPORATION

Pertland - Seattle - Spokane - Twin Falls

Representing

Representing

Busia Ca. (Discoel & Gas. (RicCormick-Deering Industrial Tractors) Citoesian Rock Drill Ga. Rarios-Steam Showel Ca. Rarios-Steam Showel Ca. Register Freek Ca. Seagrave Cers. Rockeye-Brooks Ca. (Synon Crushers)

Registry Snow Piew Ca. Rekram, Inc. (Compressors) Universal Power Shevel Ca. (Fire Steel Censt. Ca.

Member: Associated Equipment Distributors

GASH-STULL CO.

Representing

FORDSON Tractor and Equipment
UNIVERSAL POWER SHOVEL CO. Unit Shovels—61 % to ½-yd.
OSGOOD Shovels—all types
WEHR CO.—Road Graders, all sizes
TRACKSON CO.—Crawler Wagons, Crawlers
MICHIGAN Power Shovels
SCHRAMM Compressors

LOCOMOTIVES
HOISTS — SCRAPERS — WIRE ROPE
MANGANESE DIPPER TEETH

BOWEN MACHINERY CO.

Excavating-Construction-Industrial

1126 N. Delaware Ave., Philadelphia, Pa. Distributors for EYERS Shorels and Cranes
MKIERNAN-TERRY Pile Hammers and Derricks
LAMBERT-NATIONAL Holsts, Car Pullers, Cabloways
OAVEY Air Cooled Compressors
WELLMAN "Williams" Clamshell Buckets, Heavy-Duty
Twitiers

TAYLOR-WHARTON Manganese Shovel and Bucket

GILES & RANSOME

17th St. & Sedgley Ave., Philadelphia

Road Machinery
RICHMOND SCREW ANCHOR CO.—Concrete

EQUIPMENT

Representing

Seattle, Wash.

Pennsylvania

Portland, Ore.

285 Cozzens St.

Ohio

Ohio

20.

0.

d. O.

0.

rnor Ca.

Distributors

DOMESTIC ENGINE & PUMP CO.—Pumps

JONES SUPERIOR—Saw Rigs

LINK-BELT—Cranes and Shovels

PENNA. BOILER WORKS—Boilers

AUSTIN-WESTERN ROAD MACHINERY CO.

—Rollers, Graders, etc.

Additional Equipment in Stock: McKIERNAN-TERRY—Hammers INGERSOLL-RAND—Compressors UNIVERSAL—Truck Cranes

SERVICE SUPPLY CORPORATION 20th and Venango Sts., Philadelphia, Pa.

Representing

Representing
Chain Belt Ca.—Rex Pavers, Mirers, Truck Mixers, Pumpe
Owen Busket Ca.—Clamshell Buckets
Drave Equipment Ca.—American Tubular Towers
Hercules Ca.—Road Roller, Industrial Tractors, Crawlers
International Marvester Ca.—Industrial Tractors, Crawlers
Lidgerwood Mig. Ca.—Hoists, Winches, Cableways
Bay City Showels, inst.—Shorels, Cranes and Cranemobiles
W. A. Riddell Ca.—Crackers, Scrapers & Tracks for Tractors
Beaumont-Birch—Bins, all sizes
Chiesgo Penematis Teol Ca.—Air Compressors and Tools
Littieferd Bras.—Asphalt and Tool Heaters, Distributors

Member: Associated Equipment Distributors J. JACOB SHANNON & COMPANY

-Market Street-1744 PHILADELPHIA

Incape, LPHIA

Representing

Jasger Mashine Ca.—Concrete, Truck Mixers, Pumps

Lakewood Engineering Ca.—Road Finishers, Spreaders,

Material Towers

Allis-Chalmers Mig. Ce.—Tractors, Graders

Baker Mig. Ce.—Buldowers, Bnow Plows

American Hoist & Derrick Go.—Crawler Crames, Revolvers,

Derricks American Hoist & Derrick Co.—Cravist Cramm, Astronom, Derricks, American-Terry Derrick Co.—Dorricks, Travelers John A. Robbling's Sens Co.—Wire Rope, Cable Slings Co.—Craints and Varnishes Concrete Surfasing Machy, Co.—Craints and Varnishes Concrete Surfasing Machy, Co.—Craints and Varnishes Concrete Surfasing Machy, Co.—Concrete Accessories Sasgen Derrick Co.—Derricks and Winches Mundy Heisting Engine Co.—Cas, Electric and Steam Hoists
Ingersell-Rand Co.—Air Compressors, Pacumatic Tools

ALLEGHENY EQUIPMENT CORP.

1218 Grant Bldg. Pittsburgh, Pa.

Distributors for -CHALMERS Tractors and Allied Tractor Equipment
Tor Equipment
Tor Equipment
Tor Equipment
Torres
To REX Moto-Mixers, Building Mixers, Pavers and Pumps.

C. H. ARNOLD COMPANY, Inc.

Road and Street Machinery Contractors' Equipment 726-730 Park Bldg., Pittsburgh, Pa.

Representing
ADNUN ENGR. & MFG. CO. Blacktop Paver
BLAW-KNOX COMPANY Porns, Blas, FinBUFFALO-SPRINGF-LD ROLLER CO. Road Bollers
BARNES MFG. COMPANY Multiforde Pavers
LITLEFORD BROTHERS. Asphals Equipment
Flonker GRAVEL EQUIP. MFG. CO. Crushing
BULLIVAN MACHY. CO. Compressor & Tools
THEW SHOVEL COMPANY Showis, Cranes,
Draglinge

WESTERN MATERIAL CO.

Sioux Falls, Huron, Rapid City, Aberdeen, S.D. Atlas Conveyors
Blaw-Knex Company
Monary
Blaw-Knex Company
Monary
Blaw-Knex Company

Member: Associated Equipment Distributors

NIXON-HASSELLE COMPANY INC.

Contractors' Equipment

Chattanooga

Representing

BLAW-KNOX Buckets,
Forms
INGERBOLL-RAND Compressors
MUNDY Hoists
AUSTIN-WESTERN Grader, Crushers, Relices, etc.
BARBER-GREENE Loaders, Compressors
WEWPORT Culvert Pipe
VICAN Gaseline Locknotives ers, Couropurs
NORTHWEST Cranes,
Shovels
Also Wheelbarrews, Carts, Benders, Cutters, Shovels, etc.
Member: Associated Equipment Distributors

BROOKS-PAYNE-OSBORNE EQUIPMENT CO.

Knexville 408 Davenport Rd. Tenn Representing Busyrus-Erie Ce.—Shorois, Crane, Draglines international Harvester Ce.—Cravier, Tractors J. D. Adams Ca.—Road Machinery Gardner-Denver Co.—Compressors, Drills Timken Roller Bearing Co.—Detachable Bits Heltzel Steel Ferm & Iron Ce.—Elins, Batchers Continental Roll & Steel Ce.—Wooldridge Trailbud Jasger Mathins Ca. Lakewood Engineering Co. Jianding Roupenost Lieu Manufacturing Gorg.—Lake Tractors Inc. Miscry. Concentration of the Co.—Distribution of the Co.—Distribution of the Co.—Distribution of the Co.—Craving, Ser Physical Review Research Co.—Line Manufacturing Gorg.—Lake Tractors Inc. Miscry Line Manufacturing Corp.—Lake Tractors Inc. Miscry Line Manufacturing Corp.—Lake Misc. Ca.—Cruning, Ser Physical Review Research Line and Belts Pionese Gravel Equip. Mrg. U.S.—Cramba-Plants Hewitt Rubber Corp.—Hose and Belts Georgia-Carolina dil Ca.—Tractor Lubricants Independent Passematic Yool Ca.—Precs. & Else. Tools Taylor-Wharton Iron & Steel Ca.—Steel Castings

> WILSON-WEESNER-WILKINSON CO. Tennessee

Nashville

Keshring Co.
Insley Mfg. Co.
Allia-Chaimers Mfg. Co.
Blaw-Knet Ca.
C. H. & E. Mighy. Corp.
The Prasons Co.
Th. Smith Co.
Ingersoll-Rand Co.
Littleford Bros.
NASHVILLE—KNOXVILLE

Warehouse Stocks of Service
Reinforcing Steel and Mesh
Member: Associated Equipment Distributors

BROWNING-FERRIS MACHY, CO. 205 Exposition Ave.
Texas at Rice Sts.

Dallas, Texas
Houston, Texas

Texas at Rice Sts. Houston, Texas Representing
Heltzel Steel Form & Iron Co.
Lakewood Engineering Company
Ploneer Gravel Equip. Mfg. Co.
Barber-Greene Company
Sterling Whoelbarrow Co.
Jaeger Machine Company
Ingersoll-Rand Co.
Focto Co.—Pavers
Littleford Bross.
Thew Shovel Company
Trackson Co.—Crawlers, HoistsMcCormick-Deering—Tractors
Lidgerwood Mfg. Co.
Gallon Iron Works & Mfg. Co.
Chas, Hvass & Co., Inc.
Member: Associated Equipment Distributors Member: Associated Equipment Distributors

R. B. EVERETT & CO.

3112-18 Harrisburg Blvd. Houston, Texas

BLAW-KNOX Road Plant
Equipment. Bins, Clam
Shell Burkers
CLYDE Holsting Machy.
"P. & H." Gasoline Cranes
UNIVERSAL Form Clamb
MeKIERMAN-TERRY Pile
Hammers, etc.
CONNERY Asphalt Equip.
CHAIN BELT Concrete Mizers, Saw Bligs, Pavers
NOVO Engines, Hoists,
Pumps

SULLIVAN Compressors
STIVINAN Compressors
STIVINAN Explains
SULLIVAN Compressors
STIVINAN Compressors
STIVINAN Compressors
STIVINAN Compressors
STIVINAN Compressors

WYOMING Shovels, Picks FLYNN Surgrades Member: Associated Equipment Distributors

THE C. H. JONES COMPANY

Construction and Industrial Equipment 134-140 Pierpont Ave. Salt Lake City, Utah Distributors
CLETRAC Crawler Tractors and Allied Equip-

ment
GALION Graders and Road Building Mach'y
LIMA and BAY CITY Power Shovels
SULLIVAN Portable Air Compressors and DIAMOND Gravel Crushing and Screening

Plants
JAEGER Concrete Mixers, Pumps, Hoists
LINK-BELT Elevating and Conveying Mach'y
ATLAS IMPERIAL Diesel and Natural Gas

PHILLIPS MACHINERY CO.

900 East Cary St. Richmond, Va.
Representing

Representing
CLYDE SALES CO.
DeWALT PRODUCTS CORP.
ERIE STEEL CONSTRUCTION CO.
SAUERMAN BROTHERS, INC.
CHICAGO PNEUMATIC TOOL CO.
STEPHERS-ADAMSON MFG. CO.
ROGERS BROTHERS CORP.
GENERAL EXCAVATOR CO.
AEROIL BURNER CO.
MANITOWOC ENGINEEING WORKS
BRODERICK & BASCOM ROPE CO.
CHAIN BELT COMPANY
Also many other lines of Contractors' Equipment
Member: Associated Equipment Distributors

SOUTHERN MACHINERY & SUPPLY CO.
Roanoke Virginia

Roanoke Representing Representing
Austin Mochinery Corg.
Austin-Western Read MaLinn Mig. Corg.
Littleford Bro.
Columbus Company
Cleveland Tracture Co.
Columbus Conveyor Co.
Crocker-Wheeler Else. Mig.
Co.
Deming Company
Cardner-Denver Co.
Gruendler Crusher & Pulwer/zw Co.
George Halss Mig. Co.
Heitzel Steel Form & Iron
Co.

Resident Steels Form & Iron
Co.

Resident Steel Form & Iron
Co.

Resident Steel Co.

Res

Contractors' Equipment in Stock in Our Roanoke Warehouse

Machinery and Equipment
3200 4th So.

Representing
NORTHWEST—Gas and Electric Shovels,
Cranes and Draglines
BUHL—Air Compressors
TWIN DISC—Clutches for all purposes
PAGE—Scraper Buckets, Diesel Draglines
MINNEAPOLIS—"Twin City" Gas Engines
WISCONSIN—Gasoline Engines
WISCONSIN—Gasoline Engines
MARMON-HERRINGTON—Trucks
DAKE ENGINE CO.
PIONEER—Gravel Equipment
ISAACSON IRON WORKS—Buckets
CLETRAC—Tractors
Member: Associated Equipment Distributors

PACIFIC HOIST & DERRICK CO.

Machinery and Equipment th So. Seattle, Wash

CONSTRUCTION EQUIPMENT CO.

BOEHCK EQUIPMENT CO.

Representing
Barber-Greene Ce.
Jaeger Machine Co.
LeReir Ce.
A. Leschen & Seas Rope Ce.
Wellman Engineering Co.
W. Toepfor & Sons Co.
Hutter Steel Form & Iron
Co.
Homestend Valve Mig. Co.
Homestend Valve Mig. Co.
Sasgen Derrick Co.
Member:

Member:

Member:

Milwaukee, Wis.
Milwaukee,

Member: Associated Equipment Distributors

DROTT TRACTOR CO., Inc.

3841 W. Wisconsin Ave. Wisconsin

Milwaukee

Representing

ALLIS-CHALMERS Industry

& Track Type Tractors; TORG Highway Mowers

& Blade Graders, Motor
Patrol Graders, Motor
Patrol Graders, Track
Type Wagons
PIONEER Gravel Equip.
DROTT Bulldoners, Scarifiers, Scarers, Eliminates

BUSSELL Plows, Scrapers, WAUSAU Snow Plows

WAUKESHA Power Units

Mamback

Mamback

Mamback

Associated

Associated

Residence Track

Wisconsin

Winney Road Oilers

A GROSSE Tu-Way Mowers

LEVELAND Rock Drills

HAUGK Tar Kottlet, Heaters

WAUKESHA Power Units

TIMKIN Roller Bearings

THINKIN Roller Bearings

Member: Associated Equipment Distributors

HUNTER

HUNTER
TRACTOR & MACHY. CO.

Phone: Orchard-6580

327 So. 16th St.

Representing
Arrall Burner Ca.
American Steel & Wire Co.
Archer Iron Works
Bates Wire Ties
Blaw-Knox Co.
Burner Cer.
Burner Cer.
Chain Bell Ca.
Burner Cer.
Chain Bell Ca.
Eutild Read Machy. Co.
Godfrey Conveyer Co.
Iewa Mfg. Ca.
Killefer Mfg. Corp., Ltd.
Member: Associated

HUNTER
Milwaukee, Wis.

Milwaukee, Wis.

Milwaukee, Wis.

Milwaukee, Wis.

Milwaukee, Wis.

Parieman Terry Corp.
Pariement Pump Co.
Sauerman Bron.
Sterling Wheelburrow Co.
Sterli

JUST EQUIPMENT & SUPPLY CO., Ltd.

CO., Ltd.

173 Colborne Street
Aftey Truss Wheel Ca.
Buffalo-Byringfield Relier
Co.
Caterpillar Treater Co.
Caterpillar Treater Co.
All Steel Products Mfg. Co.
LaPlant-Choate Mfg. Co.
LaPlant-Choate

THE ALBERT OLSON CO., Ltd. 1148-50 Osler Street

REGINA, SASKATCHEWAN CANADA

CANADA
Representing
"CATERPILLAR" Tractors
Road Equipment
Combined Harvesters
PIONEER Gravel Equipment
LENHART Dump Wagons
LA PLANT-CHOATE Equipment
KILLEFER Scrapers
EUCLID Equipment
P. & H. Shovels and Cranes
PEDLAR PEOPLE'S Culverts

Contractors and Engineers Monthly

